



FEATURES:

- Ideal for providing a temporary jumper wire between surface mount devices.

MATERIALS:

SMD Grabber® test clip

Contact - Stainless Steel

Spring - Stainless Steel

Cap - Glass filled nylon. Color matches color of wire

Barrel - Glass filled nylon. Color matches color of wire

Marking: "POMONA GRABBER®"

Finish: Gold plated

Wire: 22 AWG, PVC insulated

Marking: "Model 5301"

RATINGS:

Operating Temperature: +102°C (+216°F) Max.

Voltage: Hand-held testing 33 Vrms/70 Vdc Max.

Hands free testing in controlled voltage environments: 150 WVDC Max.

Current: .5 Amperes

ORDERING INFORMATION: Model 5301-XX-*

XX = Standard Lengths in Inches, 12" and 24"

* = Color, -0 Black, -2 Red

Ordering Example: 5301-12-2 Indicates 12", color is red.

5521 Kit contains 10 pieces of model 5301-24, 1 each of 10 colors.

All dimensions are in inches. Tolerances (except noted): .xx = ± 0.02 " (.51 mm), .xxx = ± 0.005 " (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pomona:

[5301-12-2](#) [5301-12-0](#) [5521](#) [5301-24-0](#) [5301-24-2](#)