

XS208BLPAL2

inductive sensor XS2 M8 - L42mm - brass - Sn2.5mm - 12..24VDC - cable 2m

Product availability: Stock - Normally stocked in distribution facility



Main

Commercial Status	Commercialised
Range of product	OsiSense XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Product specific application	-
Sensor name	XS2
Sensor design	Cylindrical M8
Size	42 mm
Body type	Fixed
Enclosure material	Nickel plated brass
Type of output signal	Discrete
Wiring technique	3-wire
[Sn] nominal sensing distance	0.1 in (2.5 mm)
Discrete output function	1 NO
Discrete output type	PNP
Electrical connection	Cable
Cable length	6.56 ft (2 m)
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
Switching capacity in mA	<= 100 mA with overload and short-circuit protection
IP degree of protection	IP67 conforming to IEC 60529

Complementary

ISO thread	M8 x 1
Detection face	Frontal
Detector flush mounting acceptance	Non flush mountable
Material	Metal
Front material	PPS
Differential travel	1...15% of Sr
Output circuit type	DC
Cable composition	3 x 0.11 mm ²
Wire insulation material	PVC
Status LED	1 LED yellow for output state
Supply voltage limits	10...36 V DC
Voltage drop	<= 2 V at closed state
Current consumption	<= 10 mA at no-load
Delay first up	<= 5 ms
Delay response	<= 0.5 ms
Delay recovery	<= 1 ms
Marking	CE
Threaded length	1.42 in (36 mm)
Height	0.31 in (8 mm)
Length	1.65 in (42 mm)
Product weight	0.08 lb(US) (0.035 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Product certifications	CSA UL
Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Vibration resistance	25 gn amplitude = +/- 2 mm (f = 10...55 Hz) conforming to IEC 60068-2-6
Shock resistance	50 gn for 11 ms conforming to IEC 60068-2-27

Ordering and shipping details

Category	21571 - SENSORS, ELECTRONIC BASIC XU & XS
Discount Schedule	DS2
GTIN	00785901491941
Nbr. of units in pkg.	1
Package weight(Lbs)	0.15
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	ID

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0903 - Schneider Electric declaration of conformity
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Available Download End Of Life Manual

Contractual warranty

Period	18 months
--------	-----------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric:

[XS218SAPAM12](#) [XS212SANAL5](#) [XS218AAPAL10](#) [XS2M12MA250](#) [XS2M12KP340L1](#) [XS218SAMAU20](#)
[XS230BLPBL2](#) [XS218AANAL2](#) [XS218SAPAL5](#) [XS230SAMAU20](#) [XS2M18KP340L1TF](#) [XS218SAPAL10](#)
[XS2M18KP340](#) [XS2N18NC410D](#) [XS218SANAL5](#) [XS230AAMAU20](#) [XS218BLNAM12](#) [XS2M18KP340L1](#)
[XS230BLNAM12](#) [XS218SANAL10](#) [XS230SAPAL10](#) [XS2M30MA250L1](#) [XS218AAMAU20](#) [XS2M30MA250K](#)
[XS212AAPAL2](#) [XS2M30MA250](#) [XS2M08MA230](#) [XS2M18MB250K](#) [XS230AAPAL2](#) [XS208BLPAL5](#) [XS208BLNAL2](#)
[XS212SAPAL5](#) [XS230AANAM12](#) [XS230AANAL2](#) [XS2L2SANAL2](#) [XS212AANAL2](#) [XS2N12NC410](#) [XS2L2SAPAL2](#)
[XS212BLNBL2](#) [XS2M30KP340D](#) [XS212BLPAM12](#) [XS2M18MA250](#) [XS230SAPAL2](#) [XS218BLNAL2](#) [XS2M08PC410D](#)
[XS212SANAM12](#) [XS218AAMAL2](#) [XS2N30NC410D](#) [XS212BLNAL2](#) [XS2M12KP340](#) [XS2L2SAPAM12](#)
[XS218AANAM12](#) [XS2L2SANAM12](#) [XS218SANAL2](#) [XS2M12KP340D](#) [XS230BLPAL5](#) [XS212SAPAM12](#)
[XS2M30MB250K](#) [XS218SANAM12](#) [XS230SAPAL5](#) [XS230BLPAL2](#) [XS2N12NC410D](#) [XS212BLPAL2](#) [XS2M08PC410](#)
[XS230AAMAL2](#) [XS208BLPAM8](#) [XS208BLPAL2](#) [XS230SANAL2](#) [XS2M30KP340](#) [XS212AAPAL10](#) [XS230AAPAL5](#)
[XS2M18MB250](#) [XS212AAPAM12](#) [XS218SAPAL2](#) [XS2M30MA250A](#) [XS230SANAM12](#) [XS218AAPAL2](#)
[XS2M12KP340L2](#) [XS212AANAM12](#) [XS218SAMAL2](#) [XS218BLPAL5](#) [XS218AAMAL10](#) [XS212BLPAL5](#)
[XS218SAMAL10](#) [XS212AAPAL5](#) [XS230SAMAL2](#) [XS2M08NC410](#) [XS212SAPAL10](#) [XS218BLPAM12](#)
[XS2M18MA250K](#) [XS2M18KP340L2TF](#) [XS2M30MA250L2](#) [XS212SANAL2](#) [XS208BLPAM12](#) [XS218AAPAL5](#)
[XS218BLNBL2](#) [XS230SAMAL10](#) [XS2M08MA230K](#) [XS212SAPAL2](#) [XS230AAMAL5](#)