

TJM112603

NOTES:

1. REQUIREMENTS:

- A) MEETS PERFORMANCE AND ENVIRONMENTAL REQUIREMENTS OF MIL-T-81714 REV. F.
B) MODULES ARE TO BE MOUNTED INTO RACK ASSEMBLY M81714/5 OR /16 OR COMMERCIAL EQUIVALENT.
C) DIELECTRIC WITHSTANDING VOLTAGE: 1500VRMS, 2mA LEAKAGE, 25° C AT SEA LEVEL, CONTACT TO MOUNTING RACK.
D) OPERATING TEMPERATURE: -65° C TO 200° C.

2. MATERIALS:




- A) HOUSING - POLYETHERIMIDE, COLOR: BLACK.
B) GROMMET - SILICONE ELASTOMER, COLOR: BLUE.
C) INTERNAL CONTACTS - COPPER ALLOY, GOLD PLATED
D) CONTACT RETAINERS - BERYLLIUM COPPER.

3. PIN CONTACT CRIMP AND INSTALLATION TOOLS ARE NOT INCLUDED. REQUIREMENTS BELOW ARE FOR REFERENCE ONLY.

- A) PIN CONTACTS - SEE TABLE
B) CONTACT TOOLS -
CRIMP TOOL: M22520/1-01
POSITIONER: M22520/1-02, YELLOW
INSERTION/REMOVAL: M81969/14-04.

4. INSPECT PARTS PER APPLICABLE INSPECTION PLAN, TJM1126XX OR TJM1127XX.

REV	ECN	APP'D
T	3232	JR 3/16/98
U	3305	JR 4/17/98
X	3309	JR 4/29/98
Y	-	
Z	5493	JT 8/2/04
AA	5510	JS 9/4/99



PCD P/N	SUPPLIED	
	PIN CONTACT M39029/1-103	SEALING PLUG MS27488-12
TJM112603	NONE	NONE
TJM112703	NINE (9)	TWO (2)

DIMENSIONS ANSI Y14.5M UNITS: INCHES ACAD FILE	TOLERANCES .XX ± 01 .XXX ± .005 ANGLES ±2°	PROJECTION 	Amphenol Pcd <i>SPECIFICATION DRAWING</i>		TITLE TERMINAL JUNCTION MODULE SZ-12 FEEDBACK, B2 BUS			
ENGR A. PATRIE 8/15/95								
ORIGINAL 	THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION WHICH IS THE CONFIDENTIAL PROPERTY OF AMPHENOL PCD INC. PEABODY, MA		CHKD A. PATRIE 6/12/01	SIZE B	DWG NO. TJM112603		REV AA	
			APPD J. RUTKOWSKI 8/15/95	CODE: 58982		SCALE: 2X	SHEET 1 OF 1	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[TJM112703](#)