



- 1 CONNECTOR BODY AND COUPLING NUT MATERIAL: 6061-T6 ALUMINUM, ELECTROLESS NICKEL PLATED PER SAE-AMS-C-26074 OR SAE-AMS-2404E
LOCKING RING MATERIAL: BERYLLIUM COPPER, ELECTROLESS NICKEL PLATED PER SAE-AMS-C-26074 OR SAE-AMS-2404E
INSULATOR MATERIAL: LIQUID CRYSTAL POLYMER (LCP) PER ASTM D5138 OR POLYPHENYLENE SULFIDE (PPS) PER ASTM D4067
O-RING MATERIAL: FLUOROSILICONE
- 2 WIRE TERMINATION: 28 AWG SOLID, 30 AWG STRANDED WIRE OR SMALLER
- 3 LUBRICATE O-RING WITH PARKER SUPER-O-LUBE PRIOR TO INSTALLATION
- 4 THIS DRAWING ALSO IDENTIFIED AS NANOONICS 303-0032

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN M. STORRY 27 MAY 99		<div>TE Connectivity</div>						
DIMENSIONS: INCHES		CHK E. PAULUS 11 JUN 99								
		APVD S. KAIN 27 JAN 00						NAME PLUG ASSEMBLY, CIRCULAR, THREADED COUPLING, METAL, 7 POSITION		
		PRODUCT SPEC —								
		APPLICATION SPEC —								
MATERIAL		WEIGHT —		SIZE A2	CAGE CODE 0PJN9	DRAWING NO C-1589063	RESTRICTED TO —			
SEE NOTES		SEE NOTES		CUSTOMER DRAWING				SCALE 6:1	SHEET 1 of 1	REV H

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[TCM007PC2DC006](#)