





R2E175 Series

Motorized Impeller

Ø 175mm Backward Curved

- Backward curved centrifugal fans feature extremely long blades. These impellers are highly resistant to dirt and dust. Their hydraulic efficiency is very high.
- Impeller completely made of plastic PA 6.
- Maintenance-free ball bearings.
- Insulation class "B". Cable exit: variable. Direction of rotation is CW as seen from intake side.
- UL, CSA, VDE approvals on some models, please contact application engineering.
- Recommended inlet ring: 9576-2-4013.

Part Number	Curve	CFM @ 0	VAC	Hertz	Power (W)	dBA	Max Amb. Temp C	Bearing Type	Features	Capacitor (µF)	Wgt. (lbs)
R2S175-AB60-38	2	253	115	60	65	54	45	Ball	Leads	-	2.00
R2E175-AC79-22	1	320	115	60	80	70	40	Ball	Leads	6	3.00
R2E175-AO79-12	1	320	115	60	75	67	60	Ball	Leads	5	3.00
R2S175-AB56-30	2	253	230	60	60	54	45	Ball	Leads	-	2.00
R2E175-AC77-18	1	320	230	60	70	70	40	Ball	Leads	1.5	3.00



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ebm-papst:](#)

[R2S175-AB60-38](#) [R2E175-AC77-18](#) [R2E175-AC79-22](#) [R2E175-AO79-12](#) [R2S175-AB56-30](#) [R2E175-AC77-15](#)
[R2E175-AR70-05](#) [R2E175-AC77-19](#) [R2E175-AC91-05](#) [R2E175-AO77-12](#) [R2E175-AO79-14](#) [R2E175-AO77-14](#)