

# AMP & ELCON Power Connector Layout Forms







# Table of Contents

### Disclaimer

While Tyco Electronics Corporation and its affiliates referenced herein ("Tyco Electronics") have made every reasonable effort to ensure the accuracy of the information in this catalog Tyco Electronics does not guarantee that it is error-free, nor does Tyco Electronics make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current.

Tyco Electronics reserves the right to make any adjustments to the information contained herein at any time without notice. Tyco Electronics expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. Tyco Electronics' only obligations are those in the Tyco Electronics Standard Terms and Conditions of Sale, and in no case will Tyco Electronics be responsible for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of its products. Users should independently evaluate the suitability of, and test each product for, their application.

The dimensions, specifications, designs, construction, materials and processes in this catalog are for reference purposes only and are subject to change without notice. Please consult Tyco Electronics for the most current product information.

The export of certain Tyco Electronics products is restricted by the Arms Export Control Act (Title 22, U.S.C. Sec 2751, et seq.) or the Export Administration Act of 1979, as amended (Title 50, U.S.C., App. 2401 et seq.). Orders may be subject to export approval by the U.S. Government. Buyer must comply with all applicable export laws of all applicable jurisdictions. © Copyright 2007, 2006, and 2005

by Tyco Electronics Corporation. All International Rights Reserved. AMP. ELCON. FLATPAQ. MINIPAK. MULTI-BEAM XL. TE LOGO and TYCO ELECTRONICS are trademarks of Tyco Electronics Corporation.

Other products, logos, and company names mentioned herein may be trademarks of their respective owners.

MULTI-BEAM XL Custom Connector Worksheet	3
MINIPAK Custom Connector Worksheet	4
FLATPAQ Connector Layout Form	5
Mini Drawer Connector Pin Side Layout Form	6
Mini Drawer Connector Socket Side Layout Form	7
Lower Drawer Connector Pin Side Layout Form	8
Lower Drawer Connector Socket Side Layout Form	9
75A Middle Drawer Connector Pin Side Layout Form	. 10
75A Middle Drawer Connector Socket Side Layout Form	. 11
125A Middle Drawer Connector Pin Side Layout Form	. 12
125A Middle Drawer Connector Socket Side Layout Form	. 13
200A Middle Drawer Connector Pin Side Layout Form	
200A Middle Drawer Connector Socket Side Layout Form	
Square Drawer Connector Pin Side Layout Form	. 16
Square Drawer Connector Socket Side Layout Form	. 17
Top Drawer Connector Pin Side Layout Form	
Top Drawer Connector Socket Side Layout Form	. 19
Double Drawer Connector Pin Side Layout Form	
Double Drawer Connector Socket Side Layout Form	. 21
DualPower Drawer Connector Pin Side Layout Form	. 22
DualPower Drawer Connector Socket Side Layout Form	
QuadPower Drawer Connector Pin Side Layout Form	
QuadPower Drawer Connector Socket Side Layout Form	. 25
In-Line QuadPower Drawer Connector Pin Side Layout Form	. 26
In-Line QuadPower Drawer Connector Socket Side Layout Form	
W5 Power Drawer Connector Pin Side Layout Form	
W5 Power Drawer Connector Socket Side Layout Form	. 29
HV8P Drawer Connector Pin Side Layout Form	. 30
HV8P Drawer Connector Socket Side Layout Form	
P10S0 Drawer Connector Pin Side Layout Form	. 32
P10S0 Drawer Connector Socket Side Layout Form	
P10S22 Drawer Connector Pin Side Layout Form	. 34
P10S22 Drawer Connector Socket Side Layout Form	. 35
P12S12 Drawer Connector Pin Side Layout Form	
P12S12 Drawer Connector Socket Side Layout Form	. 37
P0S30 Drawer Connector Pin Side Layout Form	. 38
P0S30 Drawer Connector Socket Side Layout Form	. 39

### Restriction on the use of Hazardous Substances (RoHS)

At Tyco Electronics, we're ready to support your RoHS requirements. We've assessed more than 1.5 million end items/components for RoHS compliance, and issued new part numbers where any change was required to eliminate the restricted materials. Part numbers in this catalog are identified as:

**RoHS Compliant** — Part numbers in this catalog are RoHS Compliant, unless marked otherwise. These products comply with European Union Directive 2002/95/EC as amended 1 January 2006 that restricts the use of lead, mercury, cadmium, hexavalent chromium, PBB, and PBDE in certain electrical and electronic products sold into the EU as of 1 July 2006.

NOTE: For purposes of this Catalog, included within the definition of RoHS Compliant are products that are clearly "Out of Scope" of the RoHS Directive such as hand tools and other non-electrical accessories.

NOTE: Information regarding RoHS compliance is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information provided by our suppliers. This information is subject to change. For latest compliance status, refer to our website referenced at right.

# **Getting the Information You Need**

Our comprehensive on-line RoHS Customer Support Center provides a forum to answer your questions and support your RoHS needs. A RoHS FAQ (Frequently Asked Questions) is available with links to more detailed information. You can also submit RoHS questions and receive a response within 24 hours during a normal work week. The Support Center also provides:

- Cross-Reference from Non-compliant to Compliant Products
- Ability to browse RoHS Compliant Products in our on-line catalog
- Downloadable Technical Data Customer Information
- Presentation More detailed information

regarding the definitions used above

■ So whatever your questions when it comes to RoHS, we've got the answers at www.tycoelectronics.com/leadfree





# **MULTI-BEAM XL Custom Connector Worksheet**

PCB Mount    Compared to the c	Cable Mount  XYZ Floating		Plugs XYZ Float	ting (
Receptacle (Vertical Shown) Electrically Hot	Slide-to-Lock		Squeeze- Release	to-
To create a unique configuration for MULTI-BEAM XL Connector	ors simply comp	lete this worksheet ar	nd forward it to your Ty	yco Electronics sales engineer.
1. Application Board-to-Board			Cable-to-Boa	rd
2. Gender			Receptacle (F	
	d Mate specif t Angle	y Floating or Slid [	e-to-Lock recepta  Vertical	acle Latching
4. Termination (Cable Only)  Power  8 AWG  Signal  22 AWG		10 AWG 24 AWG	☐ 12 AWG ☐ 26 AWG	<del></del>
Sold	ler tail .135″ [ ler tail .165″ [		Press-Fit .120 Press-Fit .135 Press-Fit .165	" [3.43mm]
6. Mounting to PCB	inting holes (	-		
Enter the p	osition(s) to	•	standard length F re-mate contact (	Power Contacts) Receptacles only)
	.200" [5.08m .250" [6.35m .300" [7.62m	m] (HDP) m] (P)		
Enter the P	ositions with			e. 16, 24, 32) eak-First, Plugs only)
Section C: (Power Contacts) Enter # of Enter the p	Power Conta	cts (Loaded with	standard length F	Power Contacts) Receptacles only)
Contact Centerline Spacings:	.200″ [5.08m .250″ [6.35m .300″ [7.62m	m] (HDP) m] (P)		
8. Additional Requirements				
9. Customer Information				
Name:Comp				
Phone:Fax: _ (Submit to your local Tyco Electronics Sales Engineer)			EAM XL, TE LOGO and TY	/CO ELECTRONICS are trademarks of

www.tycoelectronics.com



# **MINIPAK Custom Connector Worksheet**

# **MINIPAK Connector**

- a. Enter your information in the table to the right.
- b. Specify the design requirements for your MINIPAK Connector configuration in steps 1 through 5 shown below.
- c. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

Tyco Electronics will recommend a MINIPAK Connector configuration based on the specified requirements and issue a Customer Drawing for your approval.

This drawing will have a unique Part Number specific to your configuration, which you should reference whenever you make an inquiry or place an order.

ENTER CUSTOMER INFORMATION							
Company	Location						
Contact Name	Title						
Telephone	Fax						
Email Address							
l am: ☐ End user ☐ Contract manufacturer (end user:							
Signature	Today's Date						
	Annual Quantity Required						

1.	AC INPUT  ☐ No AC input required	☐ 125 VAC space	cing	<b>2</b> 50	0 VAC spacing			
2.	SIGNAL CONTACTS							
	☐ No signal contacts required	6 contacts	☐ 24 contact	ts (	→ 30 contacts	☐ Other:		
	☐ Signal sequencing required (two pin lengths available; write requirements under NOTES below.)							

# 3. DC INPUT/OUTPUT

Write the current, voltage and sequencing requirements for each of the DC lines required by your application. Tyco Electronics will use this information to configure the DC side of your MINIPAK Connector with the appropriate number of contacts and contact spacing.

DC Requirements											
DC1   DC2   DC3   DC4   DC5   DC6   DC7   DC8											
Current (A)	-										
Voltage (V)											
Blade Length	Standard										
	Premate										

# 4. BOARD MOUNTING STYLE

	Straight Socket (choose one)	Right Angle Blade (choose one)
	☐ Short solder tail (.062" thick boards)	☐ Short solder tail (for .062" thick boards)
	☐ Long solder tail (.093/.125" thick boards)	☐ Long solder tail (.093/.125" thick boards)
	☐ Compliant press-fit tails (.093" min. thick board recommended)	
5.	OTHER REQUIREMENTS	NOTES:
	☐ Alignment guides required	
	☐ Connector length restriction, if any: " (mm)	
	For further clarity, you can attach a sketch to this form if necessary.	
	☐ Sketch attached: pages	
ΔΙ./	IP, ELCON, MINIPAK, TE LOGO and TYCO ELECTRONICS are trademarks of	
	co Electronics Corporation.	

www.tycoelectronics.com



# FLATPAQ Connector Layout Form

### Instructions

- 1. Indicate the connector layout by filling in the FP number of each module required in the boxes, one per box. Use one form per mated pair.
- 2. Left to right order of the modules should match mating face views of the connector. When laying out right angle assemblies, make sure you look at the mating face with the termination tails facing downwards.
- 3. For solder terminated assemblies, indicate the tail length for each half of the connector using the checkboxes to the right of the
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

Upon receipt of this form, Tyco Electronics will generate a Customer Drawing for you to check and approve prior to connector production.

ENTER CUSTOMER INFORMATION								
Company	Location							
Contact Name	Title							
Telephone	Fax							
Email Address								
I am: □ End user □ Contract manufacturer (end us	ser: )							
Signature	Today's Date							
	Annual Quantity Required							


Write the "FP" numbers to indicate the layout of one half of the connector assembly, matching the left to right order with the mating face view of the connector (right angle assembly tails facing downwards)

FP	Solder Tail Options													
														□ .115" (2.9 mm); .062" thick boards □ .177" (4.5 mm); .093/.125" boards

Write the "FP" numbers to indicate the layout of the mate of the above assembly, matching the left to right order with the mating face view of the connector (right angle assembly tails facing downwards).

FP	Solder Tail Options													
														☐ .115" (2.9 mm); .062" thick boards ☐ .177" (4.5 mm); .093/.125" boards

# Right Angle Mount





FP206



FP104 **Hot Plug Socket** FP107 FP204 Float, Postmate Hot Plug, Press-fit FP207 Hot Plug, Press-fit Hot Plug, Press-fit Hot Plug, Press-fit



FP512 Spacer, 250 V





FP303 24-Pin Socket FP403 24-Pin, Press-fit



600 V Power Modules



FP205

FP155 Standard Blade Float, Standard FP221



FP122

FP222

FP157 Premate Blade Postmate Blade Float, Premate Float, Postmate FP223 Hot Plug, Press-fit Hot Plug, Press-fit Hot Plug, Press-fit



Hot Plug Socket FP220 Hot Plug Press-fit

# Mounts

24-Pin. Press-fit



FP500 FP501 Right Flange Mount

Signal Modules





Right Angle **Guide Sockets** FP506 Passive FP516 Active

FP507 Right Angle Passive **Guide Pin** 

### Straight Mount

Note: All modules are solder tail termination unless indicated as compliant Press-fit. Select solder tail length using check boxes to the right of the connector layout grid above. 0.093" or thicker boards are recommended for compliant Press-fit termination style. Consult Tyco Electronics for signal module sequencing. See Catalog 1773096 for benefits of Hot Plug and Float options.

# 250 V Power Modules



FP150 Socket, Solder FP250 Socket, Press-fit FP100 Hot Plug, Solder Hot Plug, Press-fit



FP161 Standard Blade FP101 Float, Standard FP201



**Premate Blade** FP102 Float. Premate FP202 Hot Plug



Postmate Blade FP103 Float, Postmate FP203 Hot Plug

Spacer, 600 V

Spacer, 250 V

FP300 24-Pin FP318 24-Pin Socket FP400 24-Pin. Press-fit FP301

24-Pin Skt. Press-fit 24-Pin Skt, 3A Rated FP401 24-Pin Skt, 3A, Press-fit



FP412

FP313 6-Pin Socket 3A rated FP413 Press-fit 6-Pin Skt 3A, Press-fit

### 600 V Power Modules



Socket, Solder FP254 Socket, Press-fit FP116 Hot Plug, Solder FP216 Hot Plug, Press-fit



Standard Blade FP117 Float, Standard FP217 Hot Plug Press-fit



FP167 Premate Blade Postmate Blade FP119 FP118 Float. Premate Finat, Postmate FP218 FP219 Hot Plug, Press-fit Hot Plug, Press-fit



FP513 Spacer, 600 V

### Mounts Guides



FP500 FP501 Left Flange ight Flange Mount Mount



Straight Passive



FP517 Active, 4-40

AMP, ELCON, FLATPAQ, TE LOGO and TYCO ELECTRONICS

are trademarks of Tyco Electronics Corporation.



# Mini Drawer Connector Pin Side Layout Form

# Pin Assembly

- 1. Choose one housing from the Pin Housing Selection Menu table.
- 2. Write the total quantity of each pin contact you require for each pin assembly in the Qty column of the Pin Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired PCB tail contact in the appropriate contact positions on the drawing: e.g., if you need a size #20 premate PCB tail contact to be installed in contact position #10, write "E" in circle #10.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMI	ER INFORMATION
Company	Location
Contact Name	Title
Telephone	Fax
Email Address	
l am: □ End user □ Contract manufacturer (end us	ser: )
Signature	Today's Date
	Annual Quantity Required

Submit to your local Tyco Electronics Sales Engineer.

Pin Connector (Rear Face)
Pin Contact Insertion Side
Pin Connector Rear Face Cavity Identification

Till Collictor rical race c	avity identification
2 3	1648110-1 - #12 or #12HP 1648111-1 - #16 only 1648112-1 - #16 only
6 7 8 9 10 11 12 13 14 15 16 17	─ #20 on all housings
20 19 21	1648110-1 - #12 or #12HP 1648111-1 - #16 only 1648112-1 - #12 or #12HP

Top Asse	embly	/ Part	Number
<b>Assigned</b>	by Ty	/co El	ectronics

Pin Housing Selection Menu		Check
Part Number	Description	One
1648110-1	#12, #20, #12 Pin Housing, Float or Fixed Mounting	
1648111-1	#16, #20, #16 Pin Housing, Float or Fixed Mounting	
1648112-1	#16, #20, #12 Pin Housing, Float or Fixed Mounting	

Size	Re	f.	Part Number	Termination Style & Pin Length	Qty.
O.L.O	A	=	1650155-1	Crimp, standard	Q.y.
	В	=	1650161-1	Crimp, premate	
#20	С	=	1650162-2	Crimp, postmate	
#20	D	=	1650283-1	PCB tail, standard	
	Е	=	1650065-1	PCB tail, premate	
	F	=	1650226-1	PCB tail, postmate	
	G	=	1766194-1	Crimp, standard	
	Η	=	1766198-1	Crimp, premate	
#16	J	=	1766199-1	Crimp, postmate	
πισ	K	=	1766222-1	PCB tail, standard	
	L	=	1766223-1	PCB tail, premate	
	M	=	1766818-1	PCB tail, postmate	
	N	=	1766193-1	Crimp, standard	
	Р	=	1766195-1	Crimp, premate	
#12	Q	=	1766196-1	Crimp, postmate	
π12	R	=	1766245-1	PCB tail, standard	
	S	=	1766250-1	PCB tail, premate	
	T	=	1766249-1	PCB tail, postmate	
	U	=	1650153-2	Crimp, standard, Hot Plug	
#12 Hot	V	=	1650156-2	Crimp, premate, Hot Plug	
Plug	W	=	1650060-2	PCB tail, standard, Hot Plug	
	Χ	=	1650074-3	PCB tail, premate, Hot Plug	

Crimp contacts are removable. PCB tail contacts are non-removable.

Float Mount Shoulder Screw		
Part Number	Description	Qty.
1650402-1	Screw, No 8-32 UNC 2A	
1650106-1	Screw, No 6-32 UNC 2A	
1650589-1	Screw, M4 x 0.7	



# Mini Drawer Connector Socket Side Layout Form

# **Socket Assembly**


- 1. Choose one housing from the Socket Housing Selection Menu table.
- Write the total quantity of each socket contact you require for each socket assembly in the Qty column of the Socket Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired PCB tail contact in the appropriate contact positions on the drawing: e.g., if you need a size #20 PCB tail contact to be installed in contact position #8, write "C" in circle #8.
- Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION				
Company	Location			
Contact Name	Title			
Telephone	Fax			
Email Address				
I am: 🗅 End user 🗅 Contract manufacturer (end us	ser: )			
Signature	Today's Date			
	Annual Quantity Required			

Submit to your local Tyco Electronics Sales Engineer.

# Socket Connector (Rear Face)

Socket Contact Insertion Side Socket Connector Rear Face Cavity Identification



Socket Housing Selection Menu		Check
Part Number	Description	One
1648115-1	#12, #20, #12 Socket Housing, Float or Fixed Mounting	
1648116-1	#16, #20, #16 Socket Housing, Float or Fixed Mounting	
1648117-1	#16, #20, #12 Socket Housing, Float or Fixed Mounting	

Socket C	onta	ct	Selection Me	nu	
Size	Re	f.	Part Number	Termination Style	Qty.
	Α	=	1648325-1	Crimp	
#20	В	=	6648301-1	Compliant Press-fit	
	С	=	1648382-1	PCB Tail	
	D	=	6648319-1	Crimp	
#16	Ε	=	6648306-1	Compliant Press-fit	
	F	=	6648383-1	PCB Tail	
	G	=	6648318-1	Crimp	
#12	Н	=	6648304-1	Compliant Press-fit	
	J	=	6648374-1	PCB Tail	
#40 H-1	K	=	1648384-1	Crimp, Hot Plug	
#12 Hot Plug	L	=	6648305-1	Compliant Press-fit, Hot Plug	
riuy	M	=	1648387-1	PCB Tail, Hot Plug	

Crimp contacts are removable. Press-fit and PCB tail contacts are non-removable.

Float Mount Shoulder Screw		
Part Number	Description	Qty.
1650402-1	Screw, No 8-32 UNC 2A	
1650106-1	Screw, No 6-32 UNC 2A	
1650589-1	Screw, M4 x 0.7	

Top Assembly Part Number Assigned by Tyco Electronics



# **Lower Drawer Connector Pin Side Layout Form**

# Pin Assembly

- 1. Choose one housing from the Pin Housing Selection Menu table.
- 2. Write the total quantity of each pin contact you require for each pin assembly in the Qty column of the Pin Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired PCB tail contact in the appropriate contact positions on the drawing: e.g., if you need a size #20 premate PCB tail contact to be installed in contact position #10, write "E" in circle #10.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION				
Company	Location			
Contact Name	Title			
Telephone	Fax			
Email Address				
I am: 🗅 End user 🗅 Contract manufacturer (end us	ser: )			
Signature	Today's Date			
	Annual Quantity Required			

Submit to your local Tyco Electronics Sales Engineer.

Pin Connector (Rear Face)
Pin Contact Insertion Side
Pin Connector Rear Face Cavity Identificatio

Pin Connector Rear Face Cavit	ty Identification
	1648203-1 - #12 or #12HP 1648204-1 - #16 only 1648205-1 - #16 only
5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25	— #20 on all housings
26 27 29	1648203-1 - #12 or #12HP 1648204-1 - #16 only 1648205-1 - #12 or #12HP

Top Assembly Part Number Assigned by Tyco Electronics

Pin Housing S	election Menu	Check
Part Number	Description	One
1648203-1	#12, #20, #12 Pin Housing, Float or Fixed Mounting	
1648204-1	#16, #20, #16 Pin Housing, Float or Fixed Mounting	
1648205-1	#16, #20, #12 Pin Housing, Float or Fixed Mounting	

Pin Conta	act Sel	ection Menu		
Size	Ref.	Part Number	Termination Style & Pin Length	Qty.
	A =	1650155-1	Crimp, standard	
	B =	1650161-1	Crimp, premate	
#20	C =	1650162-2	Crimp, postmate	
πΔΟ	D =	1650283-1	PCB tail, standard	
	E =	1650065-1	PCB tail, premate	
	F =	1650226-1	PCB tail, postmate	
	G =	1766194-1	Crimp, standard	
	H =	1766198-1	Crimp, premate	
#16	J =	1766199-1	Crimp, postmate	
π10	K =	1766222-1	PCB tail, standard	
	L =	1766223-1	PCB tail, premate	
	M =	1766818-1	PCB tail, postmate	
	N =	1766193-1	Crimp, standard	
	P =	1766195-1	Crimp, premate	
#12	Q =	1766196-1	Crimp, postmate	
π12	R =	1766245-1	PCB tail, standard	
	S =	1766250-1	PCB tail, premate	
	T =	1766249-1	PCB tail, postmate	
	U =	1650153-2	Crimp, standard, Hot Plug	
#12 Hot	V =	1650156-2	Crimp, premate, Hot Plug	
Plug	W =	1650060-2	PCB tail, standard, Hot Plug	
	X =	1650074-3	PCB tail, premate, Hot Plug	

Crimp contacts are removable. PCB tail contacts are non-removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650402-1	Screw, No 8-32 UNC 2A		
1650106-1	Screw, No 6-32 UNC 2A		
1650589-1	Screw, M4 x 0.7		



# **Lower Drawer Connector Socket Side Layout Form**


# **Socket Assembly**

- 1. Choose one housing from the Socket Housing Selection Menu table.
- Write the total quantity of each socket contact you require for each socket assembly in the Qty column of the Socket Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired PCB tail contact in the appropriate contact positions on the drawing: e.g., if you need a size #20 PCB tail contact to be installed in contact position #8, write "C" in circle #8.
- Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMI	ER INFORMATION
Company	Location
Contact Name	Title
Telephone	Fax
Email Address	
l am: □ End user □ Contract manufacturer (end us	ser: )
Signature	Today's Date
	Annual Quantity Required

Submit to your local Tyco Electronics Sales Engineer.

### Socket Connector (Rear Face)



Socket Housing Selection Menu		
Part Number	Description	One
1648206-1	#12, #20, #12 Socket Housing, Float or Fixed Mounting	
1648207-1	#16, #20, #16 Socket Housing, Float or Fixed Mounting	
1648208-1	#16, #20, #12 Socket Housing, Float or Fixed Mounting	

Socket C	onta	ıct	Selection Me	nu	
Size	Re	f.	Part Number	Termination Style	Qty.
	Α	=	1648325-1	Crimp	
#20	В	=	6648301-1	Compliant Press-fit	
	С	=	1648382-1	PCB Tail	
	D	=	6648319-1	Crimp	
#16	Е	=	6648306-1	Compliant Press-fit	
	F	=	6648383-1	PCB Tail	
	G	=	6648318-1	Crimp	
#12	Н	=	6648304-1	Compliant Press-fit	
	J	=	6648374-1	PCB Tail	
#40 H-1	K	=	1648384-1	Crimp, Hot Plug	
#12 Hot Plug	L	=	6648305-1	Compliant Press-fit, Hot Plug	
riuy	M	=	1648387-1	PCB Tail, Hot Plug	

Crimp contacts are removable. Press-fit and PCB tail contacts are non-removable.

Float Mount Shoulder Screw				
Part Number	Description	Qty.		
1650402-1	Screw, No 8-32 UNC 2A			
1650106-1	Screw, No 6-32 UNC 2A			
1650589-1	Screw, M4 x 0.7			

Top Assembly Part Number Assigned by Tyco Electronics



# 75A Middle Drawer Connector Pin Side Layout Form


# Pin Assembly

- 1. Choose one housing from the Pin Housing Selection Menu table.
- 2. Write the total quantity of each pin contact you require for each pin assembly in the Qty column of the Pin Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired PCB tail contact in the appropriate contact positions on the drawing: e.g., if you need a non-hot plug size #12 premate PCB tail contact to be installed in contact position #8, write "Q" in circle #8.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION				
Company	Location			
Contact Name	Title			
Telephone	Fax			
Email Address				
l am: □ End user □ Contract manufacturer (end user:				
Signature	Today's Date			
	Annual Quantity Required			

Submit to your local Tyco Electronics Sales Engineer.

# Pin Connector (Rear Face) Pin Contact Insertion Side Pin Connector Rear Face Cavity Identification



Pin Housing S	election Menu	Check
Part Number	Description	One
1648162-1	Float Mount for Crimp Contacts	
1648163-1	Flush PCB Mount for PCB Tail Contacts	

Pin Conta	act S	Sel	ection Menu		
Size	Re	f.	Part Number	Termination Style & Pin Length	Qty.
	Α	=	1766192-1	Crimp, standard	
#8	В	=	1766197-1	Crimp, premate	
πο	С	=	1766262-1	PCB tail, standard	
	D	=	1766263-1	PCB tail, premate	
	Ε	=	1650155-1	Crimp, standard	
	F	=	1650161-1	Crimp, premate	
#20	G	=	1650162-2	Crimp, postmate	
πΔυ	Н	=	1650283-1	PCB tail, standard	
	J	=	1650065-1	PCB tail, premate	
	K	=	1650226-1	PCB tail, postmate	
	L	=	1766193-1	Crimp, standard	
	M	=	1766195-1	Crimp, premate	
#12	N	=	1766196-1	Crimp, postmate	
π12	Р	=	1766245-1	PCB tail, standard	
	Q	=	1766250-1	PCB tail, premate	
	R	=	1766249-1	PCB tail, postmate	
	S	=	1650153-2	Crimp, standard, Hot Plug	
#12 Hot	T	=	1650156-2	Crimp, premate, Hot Plug	
Plug	U	=	1650060-2	PCB tail, standard, Hot Plug	
	V	=	1650074-3	PCB tail, premate, Hot Plug	

Crimp contacts are removable. PCB tail contacts are non-removable.

Float Mount Shoulder Screw				
Part Number	Description	Qty.		
1650402-1	Screw, No 8-32 UNC 2A			
1650106-1	Screw, No 6-32 UNC 2A			
1650589-1	Screw, M4 x 0.7			

Top Assembly Part Number Assigned by Tyco Electronics

AMP, ELCON, TE LOGO and TYCO ELECTRONICS are trademarks of Tyco Electronics Corporation.

USA: 1-800-522-6752 Canada: 1-905-470-4425 Mexico: 01-800-733-8926 C. America: 52-55-1106-0803 South America: 55-11-2103-6000 Hong Kong: 852-2735-1628 Japan: 81-44-844-8013 UK: +44-(0) 800-267-666



# 75A Middle Drawer Connector Socket Side Layout Form

# **Socket Assembly**

- 1. Choose one housing from the Socket Housing Selection Menu table.
- Write the total quantity of each socket contact you require for each socket assembly in the Qty column of the Socket Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Press-fit and PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the contact in the appropriate contact positions on the drawing: e.g., if you need a non-hot plug size #12 PCB tail contact to be installed in contact position #8, write "J" in circle #8.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMI	ER INFORMATION
Company	Location
Contact Name	Title
Telephone	Fax
Email Address	
l am: □ End user □ Contract manufacturer (end us	ser: )
Signature	Today's Date
	Annual Quantity Required

Submit to your local Tyco Electronics Sales Engineer.

# Socket Connector (Rear Face)

Socket Contact Insertion Side Socket Connector Rear Face Cavity Identification

Cooker Connector Floar Face Cavity facili	imodion
36 37 37 35	Size #8
28 \( \) 29 \( \) 30 \( \) 31 \( \) 32 \( \) 33 \( \)	
22 23 24 25 26 27 16 17 18 19 20 21 10 11 12 13 14 15	Size #20
7 8 9	
4 5 6	Size #12 or #12 HP

Socket Housing Selection Menu				
Part Number	Part Number Description			
6648167-1	Float Mount for Crimp Contacts			
1648168-1	PCB Mount for PCB Tail and Press-fit Contacts			

Socket C	onta	ıct	Selection Me	nu	
Size	Re	f.	Part Number	Termination Style	Qty.
	Α	=	6648317-1	Crimp	
#8	В	=	6648351-1	Knurled Press-fit	
	С	=	6648400-1	PCB Tail	
	D	=	1648325-1	Crimp	
#20	Е	=	6648294-1	Compliant Press-fit (Flush)	
	F	=	1648382-1	PCB Tail	
	G	=	6648318-1	Crimp	
#12	Н	=	6648304-1	Compliant Press-fit	
	J	=	6648374-1	PCB Tail	
"40 !! !	K	=	1648384-1	Crimp, Hot Plug	
#12 Hot	L	=	6648305-1	Compliant Press-fit, Hot Plug	
Plug	M	=	1648387-1	PCB Tail, Hot Plug	

Crimp contacts are removable. Press-fit and PCB tail contacts are non-removable.

Float Mount Shoulder Screw				
Part Number	Description	Qty.		
1650402-1	Screw, No 8-32 UNC 2A			
1650106-1	Screw, No 6-32 UNC 2A			
1650589-1	Screw, M4 x 0.7			

Top Assembly Part Number Assigned by Tyco Electronics



# 125A Middle Drawer Connector Pin Side Layout Form


# Pin Assembly

- 1. Choose one housing from the Pin Housing Selection Menu table.
- 2. Write the total quantity of each pin contact you require for each pin assembly in the Qty column of the Pin Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Threaded and PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a non-hot plug size #12 premate PCB tail contact to be installed in contact position #4, write "Q" in circle #4.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION				
Company	Location			
Contact Name	Title			
Telephone	Fax			
Email Address				
l am: □ End user □ Contract manufacturer (end us	ser: )			
Signature	Today's Date			
	Annual Quantity Required			

Submit to your local Tyco Electronics Sales Engineer.

F	Pin Connector (Rear Face)
	Pin Contact Insertion Side
Pin Conn	ector Rear Face Cavity Identification



Pin Housing Selection Menu				
Part Number	Part Number Description			
1648151-1	Float Mount Pin Housing			
1648152-1	PCB Mount Pin Housing			

Pin Conta	act Se	lection Menu		
Size	Ref.	Part Number	Termination Style & Pin Length	Qty.
	A =	1766232-1	Crimp, standard	
#4	В =	1766812-1	1/4-20 External Thread	
	C =	1766283-1	M5 Internal Thread	
	E =	1650155-1	Crimp, standard	
	F =	1650161-1	Crimp, premate	
#20	G =	1650162-2	Crimp, postmate	
πΖυ	Н =	1650283-1	PCB tail, standard	
	J =	1650065-1	PCB tail, premate	
	K =	1650226-1	PCB tail, postmate	
	L =	1766193-1	Crimp, standard	
	M =	1766195-1	Crimp, premate	
#12	N =	1766196-1	Crimp, postmate	
π12	P =	1766245-1	PCB tail, standard	
	Q =	1766250-1	PCB tail, premate	
	R =	1766249-1	PCB tail, postmate	
	S =	1650153-2	Crimp, standard, Hot Plug	
#12 Hot	T =	1650156-2	Crimp, premate, Hot Plug	
Plug	U =	1650060-2	PCB tail, standard, Hot Plug	
	V =	1650074-3	PCB tail, premate, Hot Plug	

Crimp and Threaded contacts are removable. PCB tail contacts are non-removable.

Float Mount Shoulder Screw				
Part Number	Description	Qty.		
1650402-1	Screw, No 8-32 UNC 2A			
1650106-1	Screw, No 6-32 UNC 2A			
1650589-1	Screw, M4 x 0.7			

Top Assembly Part Number Assigned by Tyco Electronics



# 125A Middle Drawer Connector Socket Side Layout Form

# **Socket Assembly**


- 1. Choose one housing from the Socket Housing Selection Menu table.
- Write the total quantity of each socket contact you require for each socket assembly in the Qty column of the Socket Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Threaded and PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a non-hot plug size #12 PCB tail contact to be installed in contact position #4, write "J" in circle #4.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION				
Company	Location			
Contact Name	Title			
Telephone	Fax			
Email Address				
I am: 🗅 End user 🗅 Contract manufacturer (end us	ser: )			
Signature	Today's Date			
	Annual Quantity Required			

Submit to your local Tyco Electronics Sales Engineer.

# Socket Connector (Rear Face)

Socket Contact Insertion Side Socket Connector Rear Face Cavity Identification



Socket Housing Selection Menu			
Part Number	Description	One	
1648156-1	Float Mount for Crimp Contacts		
1648157-1	PCB Mount for PCB Tail and Press-fit Contacts		

Socket Contact Selection Menu					
Size	Re	f.	Part Number	Termination Style	Qty.
	Α	=	6648434-1	Crimp	
#4	В	=	6648435-1	1/4-20 External Thread	
	С	=	6648335-1	M5 Internal Thread	
	D	=	1648325-1	Crimp	
#20	Ε	=	6648301-1	Compliant Press-fit	
	F	=	1648382-1	PCB Tail	
	G	=	6648318-1	Crimp	
#12	Н	=	6648304-1	Compliant Press-fit	
	J	=	6648374-1	PCB Tail	
#40 H-1	K	=	1648384-1	Crimp, Hot Plug	
#12 Hot Plug	L	=	6648305-1	Compliant Press-fit, Hot Plug	
riug	M	=	1648387-1	PCB Tail, Hot Plug	

Crimp and Threaded contacts are removable. Press-fit and PCB tail contacts are non-removable.

Float Mount Shoulder Screw				
Part Number	Description	Qty.		
1650402-1	Screw, No 8-32 UNC 2A			
1650106-1	Screw, No 6-32 UNC 2A			
1650589-1	Screw, M4 x 0.7			

Top Assembly Part Number Assigned by Tyco Electronics



# 200A Middle Drawer Connector Pin Side Layout Form


# Pin Assembly

- 1. Enter company and contact information (at right).
- Write the total quantity of each pin contact you require for each pin assembly in the Qty column of the Pin Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Threaded and PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a size #4 external thread contact to be installed in contact position #25, write "B" in circle #25.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMI	ER INFORMATION
Company	Location
Contact Name	Title
Telephone	Fax
Email Address	
I am: □ End user □ Contract manufacturer (end us	ser: )
Signature	Today's Date
	Annual Quantity Required

Submit to your local Tyco Electronics Sales Engineer.

# Pin Connector (Rear Face) Pin Contact Insertion Side Pin Connector Rear Face Cavity Identification



# **Pin Housing Part Number** 1648134-1

Pin Conta	act S	Sel	ection Menu		
Size	Re	f.	Part Number	Termination Style & Pin Length	Qty.
#4	Α	=	1766232-1	Crimp, standard	
#4	В	=	1766812-1	1/4-20 External Thread	
#8	С	=	1766192-1	Crimp, standard	
πυ	D	=	1766197-1	Crimp, premate	
	Е	=	1650155-1	Crimp, standard	
	F	=	1650161-1	Crimp, premate	
#20	G	=	1650162-2	Crimp, postmate	
πΖυ	Н	=	1650283-1	PCB tail, standard	
	J	=	1650065-1	PCB tail, premate	
	K	=	1650226-1	PCB tail, postmate	
	L	=	1766193-1	Crimp, standard	
	M	=	1766195-1	Crimp, premate	
#12	N	=	1766196-1	Crimp, postmate	
π12	Р	=	1766245-1	PCB tail, standard	
	Q	=	1766250-1	PCB tail, premate	
	R	=	1766249-1	PCB tail, postmate	
	S	=	1650153-2	Crimp, standard, Hot Plug	
#12 Hot	T	=	1650156-2	Crimp, premate, Hot Plug	
Plug	U	=	1650060-2	PCB tail, standard, Hot Plug	
	V	=	1650074-3	PCB tail, premate, Hot Plug	

Crimp and Threaded contacts are removable. PCB tail contacts are non-removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650402-1	Screw, No 8-32 UNC 2A		
1650589-1	Screw, M4 x 0.7		

Top Assembly Part Number Assigned by Tyco Electronics



# 200A Middle Drawer Connector Socket Side Layout Form

# **Socket Assembly**


- 1. Enter company and contact information (at right).
- Write the total quantity of each socket contact you require for each socket assembly in the Qty column of the Socket Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Threaded and PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a size #4 external thread contact to be installed in contact position #25, write "B" in circle #25.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

Socket	Connector	(Rear	Face)
OOUNCE	COMMICCION	(IICUI	· uoc

Socket Contact Insertion Side Socket Connector Rear Face Cavity Identification

ENTER CUSTOMER INFORMATION				
Company	Location			
Contact Name	Title			
Telephone	Fax			
Email Address				
I am: 🗅 End user 🗅 Contract manufacturer (end us	ser: )			
Signature	Today's Date			
	Annual Quantity Required			

Submit to your local Tyco Electronics Sales Engineer.



# Socket Housing Part Number 1648135-1

Socket C	Socket Contact Selection Menu				
Size	Re	f.	Part Number	Termination Style & Pin Length	Qty.
#4	Α	=	6648434-1	Crimp	
#4	В	=	6648435-1	1/4-20 External Thread	
#8	С	=	6648317-1	Crimp	
πο	D	=	6648400-1	PCB Tail	
#20	Е	=	1648325-1	Crimp	
πΖυ	F	=	1648382-1	PCB Tail	
#12	G	=	6648318-1	Crimp	
#12	Η	=	6648374-1	PCB Tail	
#12 Hot	J	=	1648384-1	Crimp, Hot Plug	
Plug	K	=	1648387-1	PCB Tail, Hot Plug	

Crimp and Threaded contacts are removable. Press-fit and PCB tail contacts are non-removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650402-1	Screw, No 8-32 UNC 2A		
1650589-1	Screw, M4 x 0.7		

Top Assembly Part Number Assigned by Tyco Electronics



# **Square Drawer Connector Pin Side Layout Form**


# Pin Assembly

- 1. Enter company and contact information (at right).
- 2. Write the total quantity of each pin contact you require for each pin assembly in the Qty column of the Pin Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired PCB tail contact in the appropriate contact positions on the drawing: e.g., if you need a non-hot plug size #12 standard PCB tail contact to be installed in contact position #1, write "K" in circle #1.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION				
Company	Location			
Contact Name	Title			
Telephone	Fax			
Email Address				
I am: 🗅 End user 🗅 Contract manufacturer (end us	ser: )			
Signature	Today's Date			
	Annual Quantity Required			

Submit to your local Tyco Electronics Sales Engineer.

# Pin Connector (Rear Face) Pin Contact Insertion Side Pin Connector Rear Face Cavity Identification



# Pin Housing Part Number 1648132-1

Pin Conta	act Sel	ection Menu		
Size	Ref.	Part Number	Termination Style & Pin Length	Qty.
	A =	1650155-1	Crimp, standard	
	В =	1650161-1	Crimp, premate	
#20	C =	1650162-2	Crimp, postmate	
π20	D =	1650283-1	PCB tail, standard	
	E =	1650065-1	PCB tail, premate	
	F =	1650226-1	PCB tail, postmate	
	G =	1766193-1	Crimp, standard	
	H =	1766195-1	Crimp, premate	
#12	J =	1766196-1	Crimp, postmate	
π12	K =	1766245-1	PCB tail, standard	
	L =	1766250-1	PCB tail, premate	
	M =	1766249-1	PCB tail, postmate	
	N =	1650153-2	Crimp, standard, Hot Plug	
#12 Hot	P =	1650156-2	Crimp, premate, Hot Plug	
Plug	Q =	1650060-2	PCB tail, standard, Hot Plug	
	R =	1650074-3	PCB tail, premate, Hot Plug	

Crimp contacts are removable. PCB tail contacts are non-removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650402-1	Screw, No 8-32 UNC 2A		
1650589-1	Screw, M4 x 0.7		

Top Assembly Part Number Assigned by Tyco Electronics



# **Square Drawer Connector Socket Side Layout Form**

# **Socket Assembly**


- 1. Enter company and contact information (at right).
- Write the total quantity of each socket contact you require for each socket assembly in the Qty column of the Socket Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Press-fit and PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a non-hot plug size #12 PCB tail contact to be installed in contact position #1, write "F" in circle #1.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMI	ER INFORMATION
Company	Location
Contact Name	Title
Telephone	Fax
Email Address	
I am: □ End user □ Contract manufacturer (end us	ser: )
Signature	Today's Date
	Annual Quantity Required

Submit to your local Tyco Electronics Sales Engineer.

# Socket Connector (Rear Face)

Socket Contact Insertion Side Socket Connector Rear Face Cavity Identification



# Socket Housing Part Number 1648133-1 = Fixed Mount only

Socket C	ontac	t Selection Me	nu	
Size	Ref.	Part Number	Termination Style & Pin Length	Qty.
	Α =	1648325-1	Crimp	
#20	В =	6648301-1	Compliant Press-fit	
	C =	1648382-1	PCB Tail	
	D =	6648318-1	Crimp	
#12	E =	6648304-1	Compliant Press-fit	
	F =	6648374-1	PCB Tail	
#40 H-1	G =	1648384-1	Crimp, Hot Plug	
#12 Hot Plug	Н =	6648305-1	Compliant Press-fit, Hot Plug	
riug	J =	1648387-1	PCB Tail, Hot Plug	

Crimp contacts are removable. Press-fit and PCB tail contacts are non-removable.

Top Assembly Part Number Assigned by Tyco Electronics



# **Top Drawer Connector Pin Side Layout Form**

# Pin Assembly

- 1. Choose one housing from the **Pin Housing Selection Menu** table. Place an X in the appropriate guide pin circles, if guide pins are required.
- 2. Write the total quantity of each pin contact you require for each pin assembly in the Qty column of the Pin Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Threaded and PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a size #20 premate PCB tail standard contact to be installed in contact position #10, write "Q" in circle #10.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

# Company Location Contact Name Title Telephone Fax Email Address I am: □ End user □ Contract manufacturer (end user: Signature Today's Date Annual Quantity Required

**ENTER CUSTOMER INFORMATION** 

Submit to your local Tyco Electronics Sales Engineer.

# Pin Connector (Rear Face) Pin Contact Insertion Side

Pin Contact Insertion Side Pin Connector Rear Face Cavity Identifica	ation
(G2)	
	Size #0
3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34	Size #20
35 36 37 38 39 40 41 42 43 44 45 46	Size #16
47 48 49	Size #12 or #12HP
50 51 52	
G3 G4	

Pin Housing Selection Menu		Check
Part Number	Description	One
1648183-1	Housing without guides	
	Housing with guides (#6-32 thread)	
	Housing with guides (M3 x 0.5 thread)	

		ection Menu		
Size	Ref.	Part Number	Termination Style & Pin Length	Qty.
	A =		Crimp	
	B =	1766819-1	Probe Proof, crimp	
	C =	1766230-1	1/4-20 Internal Thread	
	D =	1766274-1	M6 x 1 Internal Thread	
#0	E =	1766269-1	Probe Proof, 1/4-20 Internal Thread	
πυ	F =	1766275-1	Probe Proof, M6 x 1 Internal Thread	
	G =	1766268-1	1/4-20 External Thread	
	H =	1766231-1	M6 x 1 External Thread	
	J =	1766270-1	Probe Proof, 1/4-20 External Thread	
	K =	1766276-1	Probe Proof, M6 x 1 External Thread	
-	L =	1650155-1	Crimp, standard	
	M =	1650161-1	Crimp, premate	
#20	N =	1650162-2	Crimp, postmate	
#20	P =	1650283-1	PCB tail, standard	
	Q =	1650065-1	PCB tail, premate	
	R =	1650226-1	PCB tail, postmate	
	S =	1766194-1	Crimp, standard	
	T =	1766198-1	Crimp, premate	
#16	U =	1766199-1	Crimp, postmate	
#10	V =	1766222-1	PCB tail, standard	
	W =	1766223-1	PCB tail, premate	
	X =	1766818-1	PCB tail, postmate	
	Y =	1766193-1	Crimp, standard	
	Z =	1766195-1	Crimp, premate	
#12	AA =	1766196-1	Crimp, postmate	
#12	AB =	1766245-1	PCB tail, standard	
	AC =	1766250-1	PCB tail, premate	
	AD =	1766249-1	PCB tail, postmate	
	AE =	1650153-2	Crimp, standard, Hot Plug	
#12 Hot	AF =	1650156-2	Crimp, premate, Hot Plug	
Plug	AG =	1650060-2	PCB tail, standard, Hot Plug	
	AH =	1650074-3	PCB tail, premate, Hot Plug	

Crimp and Threaded contacts are removable. PCB tail contacts are non-removable.

Float	Float Mount Shoulder Screw		
Part N	umber	Description	Qty.
1650	399-1	Screw, No 10-32 UNC 2A	
1650	401-1	Screw, M5 x 0.8	

# Top Assembly Part Number Assigned by Tyco Electronics

AMP, ELCON, TE LOGO and TYCO ELECTRONICS are trademarks of Tyco Electronics Corporation.

www.tycoelectronics.com



# **Top Drawer Connector Socket Side Layout Form**

# **Socket Assembly**

- Choose one housing from the Socket Housing Selection Menu table.
   Place an X in the appropriate guide pin circles, if guide pins are required.
- Write the total quantity of each socket contact you require for each socket assembly in the Qty column of the Socket Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Threaded, Press-fit and PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a non-hot plug size #12 PCB tail contact to be installed in contact position #51, write "U" in circle #51.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

# Socket Connector (Rear Face) Socket Contact Insertion Side

Socket Connector Rear Face Cavity Identifi	cation
(G2) (G1)	
	Size #0
(10 9 8 7 6 5 4 3) (18 17 16 15 14 13 12 11) (26 25 24 23 22 21 20 19) (34 33 32 31 30 29 28 27)	Size #20
46 45 44 43 42 41	Size #16
49 48 47	Size #12 or #12HP
52 51 50	
G4 G3	

Top Assembly Part Number Assigned by Tyco Electronics

ENTER CUSTOMI	ER INFORMATION
Company	Location
Contact Name	Title
Telephone	Fax
Email Address	
I am: □ End user □ Contract manufacturer (end us	ser: )
Signature	Today's Date
	Annual Quantity Required

Submit to your local Tyco Electronics Sales Engineer.

Pin Housing Selection Menu		Check
Part Number	Description	One
1648186-1	Housing without guides	
	Housing with guides (#6-32 thread)	
	Housing with guides (M3 x 0.5 thread)	

Socket C	onta	ct	Selection Me	nu	
Size	Ref		Part Number	Termination Style & Pin Length	Qty.
	Α	=	6648405-1	Crimp	
	В	=	6648418-1	Probe Proof, crimp	
	С	=	6648416-1	1/4-20 Internal Thread	
	D	=	6648428-1	M6 x 1 Internal Thread	
#0	Е	=	6648419-1	Probe Proof, 1/4-20 Internal Thread	
#0	F	=	6648429-1	Probe Proof, M6 x 1 Internal Thread	
	G	=	6648417-1	1/4-20 External Thread	
	Н	=	6648430-1	M6 x 1 External Thread	
	J	=	6648420-1	Probe Proof, 1/4-20 External Thread	
	K	=	6648431-1	Probe Proof, M6 x 1 External Thread	
	L	=	1648325-1	Crimp	
#20	M	=	6648301-1	Compliant Press-fit	
	N	=	1648382-1	PCB Tail	
	Р	=	6648319-1	Crimp	
#16	Q	=	6648306-1	Compliant Press-fit	
	R	=	6648383-1	PCB Tail	
	S	=	6648318-1	Crimp	
#12	T	=	6648304-1	Compliant Press-fit	
	U	=	6648374-1	PCB Tail	
#40 He*	V	=	1648384-1	Crimp, Hot Plug	
#12 Hot Plug	W	=	6648305-1	Compliant Press-fit, Hot Plug	
riuy	Χ	=	1648387-1	PCB Tail, Hot Plug	

Crimp and Threaded contacts are removable. Press-fit and PCB tail contacts are non-removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650399-1	Screw, No 10-32 UNC 2A		
1650401-1	Screw, M5 x 0.8		



# **Double Drawer Connector Pin Side Layout Form**

# Pin Assembly

- 1. Choose one housing from the **Pin Housing Selection Menu** table. Place an X in the appropriate guide pin circles, if guide pins are required.
- 2. Write the total quantity of each pin contact you require for each pin assembly in the Qty column of the Pin Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Threaded and PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a size #20 premate PCB tail contact to be installed in contact position #13, write "Q" in circle #13.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMI	ER INFORMATION
Company	Location
Contact Name	Title
Telephone	Fax
Email Address	
I am: 🗅 End user 🗅 Contract manufacturer (end us	ser: )
Signature	Today's Date
	Annual Quantity Required

Submit to your local Tyco Electronics Sales Engineer.

Pin Housing Selection Menu		Check
Part Number	Description	One
1648552-1	Housing without guides	
	Housing with guides (#6-32 thread)	
	Housing with guides (M3 x 0.5 thread)	

Size	Ref.	Part Number	Termination Style & Pin Length	Qty.
	A =	1766811-1	Crimp	
	В =	1766819-1	Probe Proof, crimp	
	C =	1766230-1	1/4-20 Internal Thread	
	D =	1766274-1	M6 x 1 Internal Thread	
#0	E =	1766269-1	Probe Proof, 1/4-20 Internal Thread	
#0	F =	1766275-1	Probe Proof, M6 x 1 Internal Thread	
	G =	1766268-1	1/4-20 External Thread	
	H =	1766231-1	M6 x 1 External Thread	
	J =	1766270-1	Probe Proof, 1/4-20 External Thread	
	K =	1766276-1	Probe Proof, M6 x 1 External Thread	
	L =	1650155-1	Crimp, standard	
	M =	1650161-1	Crimp, premate	
#20	N =	1650162-2	Crimp, postmate	
#20	P =	1650283-1	PCB tail, standard	
	Q =	1650065-1	PCB tail, premate	
	R =	1650226-1	PCB tail, postmate	
	S =	1766193-1	Crimp, standard	
	T =	1766195-1	Crimp, premate	
#12	U =	1766196-1	Crimp, postmate	
#12	V =	1766245-1	PCB tail, standard	
	W =	1766250-1	PCB tail, premate	
	X =	1766249-1	PCB tail, postmate	
	Y =	1650153-2	Crimp, standard, Hot Plug	
#12 Hot	Z =	1650156-2	Crimp, premate, Hot Plug	
Plug	AA =	1650060-2	PCB tail, standard, Hot Plug	
	AB =	1650074-3	PCB tail, premate, Hot Plug	

Crimp and Threaded contacts are removable. PCB tail contacts are non-removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650399-1	Screw, No 10-32 UNC 2A		
1650401-1	Screw, M5 x 0.8		

AMP, ELCON, TE LOGO and TYCO ELECTRONICS are trademarks of Tyco Electronics Corporation.

# Pin Connector (Rear Face) Pin Contact Insertion Side

Pin Contact Insertion Side Pin Connector Rear Face Cavity Identifica	ation
G1 G2	
	Size #0
3 4	
$ \begin{array}{ c c c c c c } \hline  & 5 & 6 & 7 & 8 \\ \hline  & 9 & 10 & 11 & 12 \\ \hline \end{array} $	Size #12 or #12HP
21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36	Size #20
37 38 39	Size #12 or #12HP
G3 G4	

**Top Assembly Part Number Assigned by Tyco Electronics** 



# **Double Drawer Connector Socket Side Layout Form**

# **Socket Assembly**

- 1. Choose one housing from the **Socket Housing Selection Menu** table. Place an X in the appropriate guide pin circles, if guide pins are required.
- 2. Write the total quantity of each socket contact you require for each socket assembly in the Qty column of the Socket Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Threaded, Press-fit and PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a non-hot plug size #12 PCB tail contact to be installed in contact position #8, write "R" in circle #8.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION				
Company	Location			
Contact Name	Title			
Telephone	Fax			
Email Address				
I am: ☐ End user☐ Contract manufacturer (end user:				
Signature	Today's Date			
	Annual Quantity Required			

Submit to your local Tyco Electronics Sales Engineer.

Socket Connector (Hear Face)
Socket Contact Insertion Side
Socket Connector Rear Face Cavity Identific

Socket Connector (Hear Face) Socket Contact Insertion Side	
Socket Connector Rear Face Cavity Identifi	cation
(G2) (G1)	
	Size #0
4 3	
8 7 6 5	Size #12 or #12HP
12 11 10 9	
20 19 18 17 16 15 14 13 28 \( \) 27 \( \) 26 \( \) 25 \( \) 24 \( \) 23 \( \) 22 \( \) 21	Size #20
36 35 34 33 32 31 30 29	
39 38 37	Size #12 or #12HP
G3 G3	

Top Asse	mbly	/ Part	Number
Assigned	by Ty	/co El	ectronics

Socket Housing Selection Menu		Check
Part Number	Description	One
1648578-1	Housing without guides	
	Housing with guides (#6-32 thread)	
	Housing with guides (M3 x 0.5 thread)	

Socket C	onta	ict	Selection Me	enu	
Size	Re	f.	Part Number	Termination Style & Pin Length	Qty.
	Α	=	6648405-1	Crimp	
	В	=	6648418-1	Probe Proof, crimp	
	С	=	6648416-1	1/4-20 Internal Thread	
	D	=	6648428-1	M6 x 1 Internal Thread	
#0	Ε	=	6648419-1	Probe Proof, 1/4-20 Internal Thread	
πυ	F	=	6648429-1	Probe Proof, M6 x 1 Internal Thread	
	G	=	6648417-1	1/4-20 External Thread	
	Н	=	6648430-1	M6 x 1 External Thread	
	J	=	6648420-1	Probe Proof, 1/4-20 External Thread	
	K	=	6648431-1	Probe Proof, M6 x 1 External Thread	
	L	=	1648325-1	Crimp	
#20	M	=	6648301-1	Compliant Press-fit	
	N	=	1648382-1	PCB Tail	
	Р	=	6648318-1	Crimp	
#12	Q	=	6648304-1	Compliant Press-fit	
	R	=	6648374-1	PCB Tail	
#40 He*	S	=	1648384-1	Crimp, Hot Plug	
#12 Hot Plug	Τ	=	6648305-1	Compliant Press-fit, Hot Plug	
ı iuy	U	=	1648387-1	PCB Tail, Hot Plug	

Crimp and Threaded contacts are removable. Press-fit and PCB tail contacts are non-removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650399-1	Screw, No 10-32 UNC 2A		
1650401-1	Screw, M5 x 0.8		



# **DualPower Drawer Connector Pin Side Layout Form**

# Pin Assembly


- Choose one housing from the Pin Housing Selection Menu table. Place an X in the appropriate guide pin circles, if guide pins are required.
- Write the total quantity of each pin contact you require for each pin assembly in the Qty column of the Pin Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Threaded contacts are installed by Tyco Electronics; enter the letter reference of the desired threaded contact in the appropriate contact positions on the drawing: e.g., if you need a size #0 1/4-20 external thread contact to be installed in contact position #1, write "G" in circle #1.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION				
Company	Location			
Contact Name	Title			
Telephone	Fax			
Email Address				
I am: □ End user □ Contract manufacturer (end user:				
Signature	Today's Date			
	Annual Quantity Required			

Submit to your local Tyco Electronics Sales Engineer.

# Pin Connector (Rear Face) Pin Contact Insertion Side

Pin Contact Insertion Side
Pin Connector Rear Face Cavity Identification



Top Assembly Part Number Assigned by Tyco Electronics

Pin Housing Selection Menu		Check
Part Number	Description	One
1648549-1	Housing without guides	
	Housing with guides (#6-32 thread)	
	Housing with guides (M3 x 0.5 thread)	

Pin Conta	act Se	lection Menu		
Size	Ref.	Part Number	Termination Style & Pin Length	Qty.
	A =	1766811-1	Crimp	
	В =	1766819-1	Probe Proof, crimp	
	C =	1766230-1	1/4-20 Internal Thread	
	D =	1766274-1	M6 x 1 Internal Thread	
#0	E =	1766269-1	Probe Proof, 1/4-20 Internal Thread	
πυ	F =	1766275-1	Probe Proof, M6 x 1 Internal Thread	
	G =	1766268-1	1/4-20 External Thread	
	Н =	1766231-1	M6 x 1 External Thread	
	J =	1766270-1	Probe Proof, 1/4-20 External Thread	
	K =	1766276-1	Probe Proof, M6 x 1 External Thread	

Contacts are removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650399-1	Screw, No 10-32 UNC 2A		
1650401-1	Screw, M5 x 0.8		



# **DualPower Drawer Connector Socket Side Layout Form**

# **Socket Assembly**


- Choose one housing from the Socket Housing Selection Menu table.
   Place an X in the appropriate guide pin circles, if guide pins are required.
- Write the total quantity of each socket contact you require for each socket assembly in the Qty column of the Socket Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Threaded contacts are installed by Tyco Electronics; enter the letter reference of the desired threaded contact in the appropriate contact positions on the drawing: e.g., if you need a size #0 1/4-20 external thread contact to be installed in contact position #1, write "G" in circle #1.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION					
Company	Location				
Contact Name	Title				
Telephone	Fax				
Email Address					
l am: □ End user □ Contract manufacturer (end user:					
Signature Today's Date					
	Annual Quantity Required				

Submit to your local Tyco Electronics Sales Engineer.

### Socket Connector (Rear Face)

Socket Contact Insertion Side Socket Connector Rear Face Cavity Identification



Top Asse	mbly	Part Nu	mber
Assigned	by Tyo	co Electi	ronics

Socket Housing Selection Menu		
Part Number	Description	One
1648575-1	Housing without guides	
	Housing with guides (#6-32 thread)	
	Housing with guides (M3 x 0.5 thread)	

Socket C	Socket Contact Selection Menu				
Size	Re	f.	Part Number	Termination Style & Pin Length	Qty.
	Α	=	6648405-1	Crimp	
	В	=	6648418-1	Probe Proof, crimp	
	С	=	6648416-1	1/4-20 Internal Thread	
	D	=	6648428-1	M6 x 1 Internal Thread	
#0	Е	=	6648419-1	Probe Proof, 1/4-20 Internal Thread	
πυ	F	=	6648429-1	Probe Proof, M6 x 1 Internal Thread	
	G	=	6648417-1	1/4-20 External Thread	
	Н	=	6648430-1	M6 x 1 External Thread	
	J	=	6648420-1	Probe Proof, 1/4-20 External Thread	
	K	=	6648431-1	Probe Proof, M6 x 1 External Thread	

Contacts are removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650399-1	Screw, No 10-32 UNC 2A		
1650401-1	Screw, M5 x 0.8		



# **QuadPower Drawer Connector Pin Side Layout Form**


# Pin Assembly

- 1. Choose one housing from the **Pin Housing Selection Menu** table. Place an X in the appropriate guide pin circles, if guide pins are required.
- 2. Write the total quantity of each pin contact you require for each pin assembly in the Qty column of the Pin Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Threaded contacts are installed by Tyco Electronics; enter the letter reference of the desired threaded contact in the appropriate contact positions on the drawing: e.g., if you need a size #0 1/4-20 external thread contact to be installed in contact position #1, write "G" in circle #1.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION					
Company	Location				
Contact Name	Title				
Telephone	Fax				
Email Address					
I am: □ End user □ Contract manufacturer (end user:					
Signature	Today's Date				
	Annual Quantity Required				

Submit to your local Tyco Electronics Sales Engineer.

# Pin Connector (Rear Face) Pin Contact Insertion Side Pin Connector Rear Face Cavity Identification



Top Asse	mb	ily Pa	art	Num	ber
Assigned	by	Tyco	El	ectro	nics

Pin Housing Selection Menu		
Part Number	Description	One
1648548-1	Housing without guides	
	Housing with guides (#6-32 thread)	
	Housing with guides (M3 x 0.5 thread)	

Pin Contact Selection Menu				
Size	Ref.	Part Number	Termination Style & Pin Length	Qty.
	A =	1766811-1	Crimp	
	В =	1766819-1	Probe Proof, crimp	
	C =	1766230-1	1/4-20 Internal Thread	
	D =	1766274-1	M6 x 1 Internal Thread	
#0	E =	1766269-1	Probe Proof, 1/4-20 Internal Thread	
πυ	F =	1766275-1	Probe Proof, M6 x 1 Internal Thread	
	G =	1766268-1	1/4-20 External Thread	
	Н =	1766231-1	M6 x 1 External Thread	
	J =	1766270-1	Probe Proof, 1/4-20 External Thread	
	K =	1766276-1	Probe Proof, M6 x 1 External Thread	

Contacts are removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650399-1	Screw, No 10-32 UNC 2A		
1650401-1	Screw, M5 x 0.8		



# **QuadPower Drawer Connector Socket Side Layout Form**

# **Socket Assembly**


- Choose one housing from the Socket Housing Selection Menu table.
   Place an X in the appropriate guide pin circles, if guide pins are required.
- Write the total quantity of each socket contact you require for each socket assembly in the Qty column of the Socket Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Threaded contacts are installed by Tyco Electronics; enter the letter reference of the desired threaded contact in the appropriate contact positions on the drawing: e.g., if you need a size #0 1/4-20 external thread contact to be installed in contact position #1, write "G" in circle #1.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION					
Company	Location				
Contact Name	Title				
Telephone	Fax				
Email Address					
l am: □ End user □ Contract manufacturer (end user:					
Signature Today's Date					
	Annual Quantity Required				

Submit to your local Tyco Electronics Sales Engineer.

### Socket Connector (Rear Face)

Socket Contact Insertion Side Socket Connector Rear Face Cavity Identification



TOP ASSE	mb	ily Pa	ırt	Num	ıber
Assigned	by	Tyco	El	ectro	nics

Socket Housing Selection Menu		Check
Part Number Description		One
1648574-1	Housing without guides	
	Housing with guides (#6-32 thread)	
	Housing with guides (M3 x 0.5 thread)	

Socket Contact Selection Menu					
Size	Re	f.	Part Number	Termination Style & Pin Length	Qty.
	Α	=	6648405-1	Crimp	
	В	=	6648418-1	Probe Proof, crimp	
	С	=	6648416-1	1/4-20 Internal Thread	
	D	=	6648428-1	M6 x 1 Internal Thread	
#0	Е	=	6648419-1	Probe Proof, 1/4-20 Internal Thread	
#0	F	=	6648429-1	Probe Proof, M6 x 1 Internal Thread	
	G	=	6648417-1	1/4-20 External Thread	
	Н	=	6648430-1	M6 x 1 External Thread	
	J	=	6648420-1	Probe Proof, 1/4-20 External Thread	
	K	=	6648431-1	Probe Proof, M6 x 1 External Thread	

Contacts are removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650399-1	Screw, No 10-32 UNC 2A		
1650401-1 Screw, M5 x 0.8			



# In-Line QuadPower Drawer Connector Pin Side Layout Form


# Pin Assembly

- 1. Enter company and contact information (at right).
- Write the total quantity of each pin contact you require for each pin assembly in the Qty column of the Pin Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Threaded contacts are installed by Tyco Electronics; enter the letter reference of the desired threaded contact in the appropriate contact positions on the drawing: e.g., if you need a size #0 M6 x 1 external thread contact to be installed in contact position #1, write "H" in circle #1.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION					
Company	Location				
Contact Name	Title				
Telephone	Fax				
Email Address					
l am: □ End user □ Contract manufacturer (end us	ser: )				
Signature	Today's Date				
	Annual Quantity Required				

Submit to your local Tyco Electronics Sales Engineer.

# Pin Connector (Rear Face) Pin Contact Insertion Side Pin Connector Rear Face Cavity Identification



# Pin Housing Part Number 1651493-1

in Cont	act Se	lection Menu		
Size	Ref.	Part Number	Termination Style & Pin Length	Qty
	Α =	1766811-1	Crimp	
	В =	1766819-1	Probe Proof, crimp	
	C =	1766230-1	1/4-20 Internal Thread	
	D =	1766274-1	M6 x 1 Internal Thread	
#0	E =	1766269-1	Probe Proof, 1/4-20 Internal Thread	
#0	F =	1766275-1	Probe Proof, M6 x 1 Internal Thread	
	G =	1766268-1	1/4-20 External Thread	
	Н =	1766231-1	M6 x 1 External Thread	
	J =	1766270-1	Probe Proof, 1/4-20 External Thread	
	K =	1766276-1	Probe Proof, M6 x 1 External Thread	

Contacts are removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650399-1	Screw, No 10-32 UNC 2A		
1650401-1	Screw, M5 x 0.8		

Top Assembly Part Number Assigned by Tyco Electronics



# In-Line QuadPower Drawer Connector Socket Side Layout Form


# **Socket Assembly**

- 1. Enter company and contact information (at right).
- Write the total quantity of each socket contact you require for each socket assembly in the Qty column of the Socket Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Threaded contacts are installed by Tyco Electronics; enter the letter reference of the desired threaded contact in the appropriate contact positions on the drawing: e.g., if you need a size #0 M6 x 1 external thread contact to be installed in contact position #1, write "H" in circle #1.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION					
Company	Location				
Contact Name	Title				
Telephone	Fax				
Email Address					
I am: □ End user □ Contract manufacturer (end us	ser: )				
Signature	Today's Date				
	Annual Quantity Required				

Submit to your local Tyco Electronics Sales Engineer.

# Socket Connector (Rear Face) Socket Contact Insertion Side



# Socket Housing Part Number 1651404-1

ocket (	Conta	act	<b>Selection Me</b>	nu	
Size	Re	f.	Part Number	Termination Style & Pin Length	Qty.
	Α	=	6648405-1	Crimp	
	В	=	6648418-1	Probe Proof, crimp	
	С	=	6648416-1	1/4-20 Internal Thread	
	D	=	6648428-1	M6 x 1 Internal Thread	
#0	Ε	=	6648419-1	Probe Proof, 1/4-20 Internal Thread	
#0	F	=	6648429-1	Probe Proof, M6 x 1 Internal Thread	
	G	=	6648417-1	1/4-20 External Thread	
	Н	=	6648430-1	M6 x 1 External Thread	
	J	=	6648420-1	Probe Proof, 1/4-20 External Thread	
	K	=	6648431-1	Probe Proof, M6 x 1 External Thread	

Contacts are removable.

Float Mount Shoulder Screw				
Part Number	Description	Qty.		
1650399-1	Screw, No 10-32 UNC 2A			
1650401-1	Screw, M5 x 0.8			

Top Assembly Part Number Assigned by Tyco Electronics



# **W5 Power Drawer Connector Pin Side Layout Form**


# Pin Assembly

- 1. Enter company and contact information (at right).
- Write the total quantity of each pin contact you require for each pin assembly in the Qty column of the Pin Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Threaded contacts are installed by Tyco Electronics; enter the letter reference of the desired threaded contact in the appropriate contact positions on the drawing: e.g., if you need a size #4 1/4-20 external thread contact to be installed in contact position #1, write "B" in circle #1.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION					
Company	Location				
Contact Name	Title				
Telephone	Fax				
Email Address					
I am: □ End user □ Contract manufacturer (end us	ser: )				
Signature	Today's Date				
	Annual Quantity Required				

Submit to your local Tyco Electronics Sales Engineer.

# Pin Connector (Rear Face) Pin Contact Insertion Side



# Pin Housing Part Number 6651457-1

Pin Contact Selection Menu					
Size	Ref.	Part Number	Termination Style & Pin Length	Qty.	
	A =	1766232-1	Crimp, standard		
#4	В =	1766812-1	1/4-20 External Thread		
	C =	1766283-1	M5 Internal Thread		

Contacts are removable.

Float Mount Shoulder Screw		
Part Number	Description	Qty.
1650402-1	Screw, No 8-32 UNC 2A	
1650589-1	Screw, M4 x 0.7	

Top Assembly Part Number Assigned by Tyco Electronics



# **W5 Power Drawer Connector Socket Side Layout Form**

# **Socket Assembly**


- 1. Enter company and contact information (at right).
- Write the total quantity of each socket contact you require for each socket assembly in the Qty column of the Socket Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Threaded contacts are installed by Tyco Electronics; enter the letter reference of the desired threaded contact in the appropriate contact positions on the drawing: e.g., if you need a size #4 1/2-20 external thread contact to be installed in contact position #1, write "B" in circle #1.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION		
Company	Location	
Contact Name	Title	
Telephone	Fax	
Email Address		
I am: ☐ End user☐ Contract manufacturer (end user:		
Signature	Today's Date	
	Annual Quantity Required	

Submit to your local Tyco Electronics Sales Engineer.

### Socket Connector (Rear Face)

Socket Contact Insertion Side Socket Connector Rear Face Cavity Identification



# Socket Housing Part Number 6651458-1

Socket Contact Selection Menu				
Size	Ref.	Part Number	Termination Style & Pin Length	Qty.
	A =	6648434-1	Crimp, standard	
#4	В =	6648435-1	1/4-20 External Thread	
	C =	6648335-1	M5 Internal Thread	

Contacts are removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650402-1	Screw, No 8-32 UNC 2A		
1650589-1	Screw, M4 x 0.7		

Top Assembly Part Number Assigned by Tyco Electronics



# **HV8P Drawer Connector Pin Side Layout Form**


# Pin Assembly

- 1. Enter company and contact information (at right).
- 2. Write the total quantity of each pin contact you require for each pin assembly in the Qty column of the Pin Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a non-hot plug size #12 premate PCB tail contact to be installed in contact position #8, write "E" in circle #8.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION		
Company	Location	
Contact Name	Title	
Telephone	Fax	
Email Address		
Tam: □ End user □ Contract manufacturer (end user:		
Signature	Today's Date	
	Annual Quantity Required	

Submit to your local Tyco Electronics Sales Engineer.

# Pin Connector (Rear Face) Pin Contact Insertion Side Pin Connector Rear Face Cavity Identification



LIII UARIIII	j Part Mullinei
1648127-1	= Fixed Mount

1648127-1	= Fixed Mount

Pin Conta	act Sel	ection Menu		
Size	Ref.	Part Number	Termination Style & Pin Length	Qty.
	A =	1766193-1	Crimp, standard	
	B =	1766195-1	Crimp, premate	
#12	C =	1766196-1	Crimp, postmate	
πιζ	D =	1766245-1	PCB tail, standard	
	E =	1766250-1	PCB tail, premate	
	F =	1766249-1	PCB tail, postmate	
	G =	1650153-2	Crimp, standard, Hot Plug	
#12 Hot	H =	1650156-2	Crimp, premate, Hot Plug	
Plug	J =	1650060-2	PCB tail, standard, Hot Plug	
	K =	1650074-3	PCB tail, premate, Hot Plug	

Crimp contacts are removable. PCB tail contacts are non-removable.

Top Assembly Part Number Assigned by Tyco Electronics



# **HV8P Drawer Connector Socket Side Layout Form**

# **Socket Assembly**


- 1. Enter company and contact information (at right).
- 2. Write the total quantity of each socket contact you require for each socket assembly in the Qty column of the Socket Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Press-fit and PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a non-hot plug size #12 PCB tail contact to be installed in contact position #8, write "C" in circle #8.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION		
Company	Location	
Contact Name	Title	
Telephone	Fax	
Email Address		
I am: □ End user □ Contract manufacturer (end user:		
Signature	Today's Date	
	Annual Quantity Required	

Submit to your local Tyco Electronics Sales Engineer.

### Socket Connector (Rear Face)

Socket Contact Insertion Side Socket Connector Rear Face Cavity Identification



# **Socket Housing Part Number**

1648128-1 = Float Mount

Socket Contact Selection Menu				
Size	Ref.	Part Number	Termination Style & Pin Length	Qty.
	Α =	6648318-1	Crimp	
#12	В =	6648304-1	Compliant Press-fit	
	C =	6648374-1	PCB Tail	
#40 H-1	D =	1648384-1	Crimp, Hot Plug	
#12 Hot Plug	E =	6648305-1	Compliant Press-fit, Hot Plug	
iluy	F =	1648387-1	PCB Tail, Hot Plug	

Crimp contacts are removable. Press-fit and PCB tail contacts are non-removable.

Float Mount Shoulder Screw		
Part Number	Description	Qty.
1650402-1	Screw, No 8-32 UNC 2A	
1650589-1	Screw, M4 x 0.7	

**Top Assembly Part Number Assigned by Tyco Electronics** 

AMP, ELCON, TE LOGO and TYCO ELECTRONICS are trademarks of Tyco Electronics Corporation.

31



# P10S0 Drawer Connector Pin Side Layout Form


# Pin Assembly

- 1. Enter company and contact information (at right).
- 2. Write the total quantity of each pin contact you require for each pin assembly in the Qty column of the Pin Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a hot plug size #12 premate PCB tail contact to be installed in contact position #10, write "K" in circle #10.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION			
Company	Location		
Contact Name	Title		
Telephone	Fax		
Email Address			
I am: ☐ End user☐ Contract manufacturer (end user:			
Signature	Today's Date		
	Annual Quantity Required		

Submit to your local Tyco Electronics Sales Engineer.

Pin Connector (Rear Face)
Pin Contact Insertion Side
Pin Connector Rear Face Cavity Identification



# **Pin Housing Part Number** 1648568-1

Pin Contact Selection Menu				
Size	Ref.	Part Number	Termination Style & Pin Length	Qty.
	A =	1766193-1	Crimp, standard	
	В =	1766195-1	Crimp, premate	
#12	C =	1766196-1	Crimp, postmate	
πιΖ	D =	1766245-1	PCB tail, standard	
	E =	1766250-1	PCB tail, premate	
	F =	1766249-1	PCB tail, postmate	
	G =	1650153-2	Crimp, standard, Hot Plug	
#12 Hot	Н =	1650156-2	Crimp, premate, Hot Plug	
Plug	J =	1650060-2	PCB tail, standard, Hot Plug	
	K =	1650074-3	PCB tail, premate, Hot Plug	

Crimp contacts are removable. PCB tail contacts are non-removable.

Float Mount Shoulder Screw				
Part Number	Description	Qty.		
1650402-1	Screw, No 8-32 UNC 2A			
1650589-1	Screw, M4 x 0.7			

**Top Assembly Part Number Assigned by Tyco Electronics** 



# P10S0 Drawer Connector Socket Side Layout Form

# **Socket Assembly**


- 1. Enter company and contact information (at right).
- 2. Write the total quantity of each socket contact you require for each socket assembly in the Qty column of the Socket Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Press-fit and PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a hot plug size #12 PCB tail contact to be installed in contact position #10, write "F" in circle #10.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

ENTER CUSTOMER INFORMATION				
Company	Location			
Contact Name	Title			
Telephone	Fax			
Email Address				
I am: Dend user Contract manufacturer (end us	ser: )			
Signature	Today's Date			
	Annual Quantity Required			

Submit to your local Tyco Electronics Sales Engineer.

### Socket Connector (Rear Face)

Socket Contact Insertion Side



Socket Housing Part Number

1648596-1	

Socket Contact Selection Menu				
Size Ref.		Part Number	Termination Style & Pin Length	Qty.
	A =	6648318-1	Crimp	
#12	B =	6648304-1	Compliant Press-fit	
	C =	6648374-1	PCB Tail	
#40 H-1	D =	1648384-1	Crimp, Hot Plug	
#12 Hot Plug	E =	6648305-1	Compliant Press-fit, Hot Plug	
1 lug	F =	1648387-1	PCB Tail, Hot Plug	

Crimp contacts are removable. Press-fit and PCB tail contacts are non-removable.

Float Mount Shoulder Screw				
Part Number	Description	Qty.		
1650402-1	Screw, No 8-32 UNC 2A			
1650589-1	Screw, M4 x 0.7			

**Top Assembly Part Number Assigned by Tyco Electronics** 

AMP, ELCON, TE LOGO and TYCO ELECTRONICS are trademarks of Tyco Electronics Corporation.

www.tycoelectronics.com



# P10S22 Drawer Connector Pin Side Layout Form

# Pin Assembly

- 1. Enter company and contact information (at right).
- 2. Write the total quantity of each pin contact you require for each pin assembly in the Qty column of the Pin Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a non-hot plug size #12 standard PCB tail contact to be installed in contact position #1, write "K" in circle #1.
- Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

Pin Connector (Rear Face)
Pin Contact Insertion Side
Pin Connector Bear Face Cavity Identification

	Company	Location	
ire <b>for each pin</b> <b>ction Menu</b> table.	Contact Name	Title	
tacts are installed desired contact	Telephone	Fax	
e.g., if you need be installed in	Email Address		
I Tyco Electronics	I am: □ End user □ Contract manufacturer (end user:		
	Signature	Today's Date	
		Annual Quantity Required	
	Submit to your local Tyco Electronics Sal	les Engineer.	

**ENTER CUSTOMER INFORMATION** 

Size #12
Size #12

# Pin Housing Part Number 1648211-1

Pin Conta	act S	el	ection Menu		
Size	Ref		Part Number	Termination Style & Pin Length	Qty.
	Α	=	1650155-1	Crimp, standard	
	В	=	1650161-1	Crimp, premate	
#20	С	=	1650162-2	Crimp, postmate	
πΖυ	D	=	1650283-1	PCB tail, standard	
	Ε	=	1650065-1	PCB tail, premate	
	F	=	1650226-1	PCB tail, postmate	
#12	G	=	1766193-1	Crimp, standard	
	Н	=	1766195-1	Crimp, premate	
	J	=	1766196-1	Crimp, postmate	
	K	=	1766245-1	PCB tail, standard	
	L	=	1766250-1	PCB tail, premate	
	M	=	1766249-1	PCB tail, postmate	
	N	=	1650153-2	Crimp, standard, Hot Plug	
#12 Hot	Р	=	1650156-2	Crimp, premate, Hot Plug	
Plug	Q	=	1650060-2	PCB tail, standard, Hot Plug	
	R	=	1650074-3	PCB tail, premate, Hot Plug	

Crimp contacts are removable. PCB tail contacts are non-removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650402-1	Screw, No 8-32 UNC 2A		
1650589-1	Screw, M4 x 0.7		

Top Assembly Part Number Assigned by Tyco Electronics




# P10S22 Drawer Connector Socket Side Layout Form

# **Socket Assembly**

- 1. Enter company and contact information (at right).
- Write the total quantity of each socket contact you require for each socket assembly in the Qty column of the Socket Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Press-fit and PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a non-hot plug size #12 PCB tail contact to be installed in contact position #1, write "F" in circle #1.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

Saakat	Connector	/Dage	Eaco)

Socket Contact Insertion Side
Socket Connector Rear Face Cavity Identification



ENTER CUSTOMER INFORMATION			
Company	Location		
Contact Name	Title		
Telephone	Fax		
Email Address			
I am: 🗅 End user 🗅 Contract manufacturer (end us	ser: )		
Signature	Today's Date		
	Annual Quantity Required		

Submit to your local Tyco Electronics Sales Engineer.

# Socket Housing Part Number 1648212-1

Socket Contact Selection Menu				
Size	Ref.	Part Number	Termination Style & Pin Length	Qty.
	A =	1648325-1	Crimp	
#20	B =	6648301-1	Compliant Press-fit	
	C =	1648382-1	PCB Tail	
	D =	6648318-1	Crimp	
#12	E =	6648304-1	Compliant Press-fit	
	F =	6648374-1	PCB Tail	
#40 HeA	G =	1648384-1	Crimp, Hot Plug	
#12 Hot Plug	H =	6648305-1	Compliant Press-fit, Hot Plug	
i iug	J =	1648387-1	PCB Tail, Hot Plug	

Crimp contacts are removable. Press-fit and PCB tail contacts are non-removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650402-1	Screw, No 8-32 UNC 2A		
1650589-1	Screw, M4 x 0.7		

Top Assembly Part Number Assigned by Tyco Electronics




# P12S12 Drawer Connector Pin Side Layout Form

# Pin Assembly

- 1. Enter company and contact information (at right).
- 2. Write the total quantity of each pin contact you require for each pin assembly in the Qty column of the Pin Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a size #20 premate PCB tail contact to be installed in contact position #9, write "E" in circle #9.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

Pin Connector (Rear Face)
Pin Contact Insertion Side
Pin Connector Rear Face Cavity Identification



ENTER CUSTOMER INFORMATION			
Company	Location		
Contact Name	Title		
Telephone	Fax		
Email Address			
I am: 🗅 End user 🗅 Contract manufacturer (end us	ser: )		
Signature	Today's Date		
	Annual Quantity Required		

Submit to your local Tyco Electronics Sales Engineer.

# Pin Housing Part Number 1651202-1

Pin Contact Selection Menu				
Size	Ref. Part Number	Termination Style & Pin Length	Qty.	
	A = 1650155-1	Crimp, standard		
	B = 1650161-1	Crimp, premate		
#20	C = 1650162-2	Crimp, postmate		
πΖυ	D = 1650283-1	PCB tail, standard		
	E = 1650065-1	PCB tail, premate		
	F = 1650226-1	PCB tail, postmate		
	G = 1766194-1	Crimp, standard		
	H = 1766198-1	Crimp, premate		
#16	J = 1766199-1	Crimp, postmate		
πιο	K = 1766222-1	PCB tail, standard		
	L = 1766223-1	PCB tail, premate		
	M = 1766818-1	PCB tail, postmate		

Crimp contacts are removable. PCB tail contacts are non-removable.

Float Mount Shoulder Screw		
Part Number	Description	Qty.
1650402-1	Screw, No 8-32 UNC 2A	
1650589-1	Screw, M4 x 0.7	

Top Assembly Part Number Assigned by Tyco Electronics




# P12S12 Drawer Connector Socket Side Layout Form

# **Socket Assembly**

- 1. Enter company and contact information (at right).
- Write the total quantity of each socket contact you require for each socket assembly in the Qty column of the Socket Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Press-fit and PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a size #20 PCB tail contact to be installed in contact position #9, write "C" in circle #9.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

Socket Connector	r (Rear Face)
------------------	---------------

Socket Contact Insertion Side
Socket Connector Rear Face Cavity Identification



ENTER CUSTOMER INFORMATION			
Company	Location		
Contact Name	Title		
Telephone	Fax		
Email Address			
I am: 🗅 End user 🗅 Contract manufacturer (end us	ser: )		
Signature	Today's Date		
	Annual Quantity Required		

Submit to your local Tyco Electronics Sales Engineer.

# Socket Housing Part Number 1651203-1

Socket Contact Selection Menu				
Size	Ref.	Part Number	Termination Style & Pin Length	Qty.
	A =	1648325-1	Crimp	
#20	В =	6648301-1	Compliant Press-fit	
	C =	1648382-1	PCB Tail	
	D =	6648319-1	Crimp	
#16	E =	6648306-1	Compliant Press-fit	
	F =	6648383-1	PCB Tail	

Crimp contacts are removable. Press-fit and PCB tail contacts are non-removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650402-1	Screw, No 8-32 UNC 2A		
1650589-1	Screw, M4 x 0.7		

Top Assembly Part Number Assigned by Tyco Electronics



# **POS30 Drawer Connector Pin Side Layout Form**

# Pin Assembly

- 1. Enter company and contact information (at right).
- 2. Write the total quantity of each pin contact you require for each pin assembly in the Qty column of the Pin Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a size #20 premate PCB tail contact to be installed in contact position #1, write "E" in circle #1.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

Pin Connector (Rear Face)
Pin Contact Insertion Side
Pin Connector Rear Face Cavity Identification

ENTER CUSTOMER INFORMATION		
Company	Location	
Contact Name	Title	
Telephone	Fax	
Email Address		
I am: □ End user □ Contract manufacturer (end us	eer:	
Signature	Today's Date	
	Annual Quantity Required	
Cubmit to your local Type Floatronics Co	les Fasiassa	

Submit to your local Tyco Electronics Sales Engineer.

nnector Rear Face Cavity Ident	tification
3 2 1 6 5 4 9 8 7 112 11 10 15 14 13 18 17 16 21 20 22 24 23 22 27 26 25 30 29 28	Size #20

# Pin Housing Part Number 6651204-1

Pin Cont	act Sel	ection Menu		
Size	Ref.	Part Number	Termination Style & Pin Length	Qty.
	A =	1650155-1	Crimp, standard	
	В =	1650161-1	Crimp, premate	
#20	C =	1650162-2	Crimp, postmate	
#20	D =	1650283-1	PCB tail, standard	
	E =	1650065-1	PCB tail, premate	
	F =	1650226-1	PCB tail, postmate	

Crimp contacts are removable. PCB tail contacts are non-removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650402-1	Screw, No 8-32 UNC 2A		
1650589-1	Screw, M4 x 0.7		

Top Assembly Part Number Assigned by Tyco Electronics




# **POS30 Drawer Connector Socket Side Layout Form**

# **Socket Assembly**

- 1. Enter company and contact information (at right).
- Write the total quantity of each socket contact you require for each socket assembly in the Qty column of the Socket Contact Selection Menu table.
- 3. Crimp contacts are shipped uninstalled. Press-fit and PCB tail contacts are installed by Tyco Electronics; enter the letter reference of the desired contact in the appropriate contact positions on the drawing: e.g., if you need a size #20 PCB tail contact to be installed in contact position #1, write "C" in circle #1.
- 4. Sign, date and send the completed form to your local Tyco Electronics Sales Engineer.

Sacket	Connector	(Roar	Eaco)

Socket Contact Insertion Side Socket Connector Rear Face Cavity Identification



ENTER CUSTOMER INFORMATION			
Company	Location		
Contact Name	Title		
Telephone	Fax		
Email Address			
I am: 🗅 End user 🗅 Contract manufacturer (end us	ser: )		
Signature	Today's Date		
	Annual Quantity Required		

Submit to your local Tyco Electronics Sales Engineer.

# Socket Housing Part Number

6651205-1

Socket C	Contact	Selection Me	nu	
Size	Ref.	Part Number	Termination Style & Pin Length	Qty.
	A =	1648325-1	Crimp	
#20	В =	6648301-1	Compliant Press-fit	
	C =	1648382-1	PCB Tail	

Crimp contacts are removable. Press-fit and PCB tail contacts are non-removable.

Float Mount Shoulder Screw			
Part Number	Description	Qty.	
1650402-1	Screw, No 8-32 UNC 2A		
1650589-1	Screw, M4 x 0.7		

Top Assembly Part Number Assigned by Tyco Electronics



# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: