



TSM SERIES

IDSS, IDSD

Plating:
Au or Sn over
50 µ" (1.27 µm) Ni
Operating Temp Range:
-55 °C to +105 °C with Tin;
-55 °C to +125 °C with Gold
Voltage Rating:
475 VAC -SV/-DV mated with
BCS or SSM
RoHS Compliant: Yes

Lead-Free Solderable: Yes
-DH/-SH Lead Coplanarity:
 (0.15 mm) .006" max (02-36)*
-DV/-SV Lead Coplanarity:
 (0.10 mm) .004" max (02-05)
 (0.13 mm) .005" max (06-10)*
 (0.15 mm) .006" max (11-36)*
 *.004" stencil solution
 may be available; contact
 IPG@samtec.com)

- Edge Mount and Locking Clips for -SV
- Solder Locks for -DH and Shrouds for -DV
- Other platings

Note:
Some lengths, styles and options are non-standard, non-returnable.

TSM-126-02-L-DH-K

= Full Reel Tape & Reel
(must order maximum quantity per reel;
contact Samtec for quantity breaks)

- SV: 02-22 positions, -DV:02-28 positions,
- SH: 02-30 positions, -DH: 02-29 positions
(Not available with -MT or -TM)

*All parts within this catalog are built to Samtec's specifications.
Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.*

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Samtec:](#)

[TSM-103-02-L-SH-A-TR](#)