



RECOMMENDED P.C. BOARD HOLE LAYOUT

- 1 "AMP", "CSA", "D-C", AND "DATE CODE" WITH .062±.015 HIGH CHARACTERS WHERE SIZE PERMITS.
- 2 HOUSING: 1-70 POSITION SIZES MAY BE PPS, GLASS-FILLED OR PCT, GLASS-FILLED. POSITION SIZES GREATER THAN 70 WILL BE PPS, GLASS-FILLED.
- 3 CONTACT: PHOSPHOR BRONZE.
- 4 CONTACT FINISH: DUPLEX PLATED 0.00076 [.000030] GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] BRIGHT TIN-LEAD ON SOLDER TAILS, ALL OVER 0.00127 [.000050] NICKEL.
- 5 THESE DIMENSIONS PERTAIN TO CAVITY C'S ONLY, NOT TO CONTACT LOCATIONS.
- 6 POINT OF MEASUREMENT FOR PLATING THICKNESS (INSIDE CONTACT BEAMS).
- 7 CSA LOGO INK STAMPED WHITE ON HOUSING.
- 8 PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.
- 9 CONTACT FINISH: DUPLEX PLATED 0.00076 [.000030] GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] MATTE TIN ON SOLDER TAILS, ALL OVER 0.00127 [.000050] NICKEL.
- 10 ROHS 2002/95/EC COMPLIANT.
- 11 RECESSED AREA AROUND MOLD GATE IS OPTIONAL. THIS FEATURE IS ALLOWABLE ON EITHER SIDE OF HOUSING OR MAY NOT BE PRESENT AT ALL.
- 12 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

FINISH	B	A	NO OF POSN	PART NUMBER	FINISH	B	A	NO OF POSN	PART NUMBER	
				34.49 [1.358]					34.49 [1.358]	
			10	22	8-532956-0			10	22	3-532956-0
				39.57 [1.558]					39.57 [1.558]	
			12	26	7-532956-9			12	26	2-532956-9
				62.43 [2.458]					62.43 [2.458]	
			21	44	7-532956-8			21	44	2-532956-8
			79	160	7-532956-7					2-532956-7
			6	14	7-532956-6					2-532956-6
			6	14	7-532956-5					2-532956-5
			89	180	7-532956-4			89	180	2-532956-4
			99	200	7-532956-3			99	200	2-532956-3
			73	148	7-532956-2			73	148	2-532956-2
			69	140	7-532956-1			69	140	2-532956-1
			64	130	7-532956-0			64	130	2-532956-0
			63	128	6-532956-9			63	128	1-532956-9
			59	120	6-532956-8			59	120	1-532956-8
			54	110	6-532956-7			54	110	1-532956-7
			49	100	6-532956-6			49	100	1-532956-6
			47	96	6-532956-5			47	96	1-532956-5
			44	90	6-532956-4			44	90	1-532956-4
			42	86	6-532956-3			42	86	1-532956-3
			39	80	6-532956-2			39	80	1-532956-2
			35	72	6-532956-1			35	72	1-532956-1
			34	70	6-532956-0			34	70	1-532956-0
			29	60	5-532956-9			29	60	532956-9
			24	50	5-532956-8			24	50	532956-8
			19	40	5-532956-7			19	40	532956-7
			17	36	5-532956-6			17	36	532956-6
			14	30	5-532956-5			14	30	532956-5
			11	24	5-532956-4			11	24	532956-4
			9	20	5-532956-3			9	20	532956-3
			7	16	5-532956-2			7	16	532956-2
			5	12	5-532956-1			5	12	532956-1
FINISH	B	A	NO OF POSN	PART NUMBER	FINISH	B	A	NO OF POSN	PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIN: K.L.CLOUSER/UTA 17JAN01
 CHK: DOUG SARVER 05/14/91
 APVD: DON FORKER 05/15/91

TE Connectivity

RECEPTACLE ASSY, MOD II, DBL ROW,
 2.54 X 2.54 [.100 X .100] CL, GUIDE PIN EARS,
 CLOSED ENTRY, SHORT-POINT-OF-CONTACT

SIZE: A1 CAGE CODE: 00779 DRAWING NO: 532956
 WEIGHT: --

CUSTOMER DRAWING SCALE: 6:1 SHEET: 1 OF 1 REV: AF3

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5-532956-8](#)