

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0367831204

Status:

Active

Overview:

MX120G Sealed Connectors

Description:

MX120G Sealed Header Connector Assembly, 12 Circuit, Color Mark Identification Green

Documents:

3D Model

Drawing (PDF)

Product Specification PS-36783-001-001 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA

UL

LR19980

E29179

General

Product Family

Series

3D Viewer

Application

CURRENT-MAX-NUMERIC

Overview

PITCH-MATING-NUMERIC

Product Name

UPC

PCB Headers

36783

Yes

Wire-to-Board

10.5

MX120G Sealed Connectors

3.20

MX120G

884982894136

Physical

(p)ower-(s)ignal Configuration

Breakaway

Circuits (Loaded)

Circuits (maximum)

Color - Resin

Durability (mating cycles max)

First Mate / Last Break

Flammability

Glow-Wire Capable

Guide to Mating Part

Lock to Mating Part

Material - Metal

Material - Plating Mating

Material - Plating Termination

Material - Resin

Net Weight

Number of Rows

Orientation

PC Tail Length

PCB Thickness - Recommended

Packaging Type

Pitch - Mating Interface

Pitch - Termination Interface

Polarized to Mating Part

Polarized to PCB

Robotic Placement

Surface Mount Compatible (SMC)

Temperature Range - Operating

Termination Interface: Style

12p - 0s

No

12

12

Black

10

No

94HB

No

No

Yes

Brass

Tin

Tin

Nylon

8.749/g

2

Right Angle

3.20mm

1.60mm

Carton

3.20mm

3.50mm

Yes

Yes

None

No

-40° to +105°C

Through Hole

Electrical



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

China RoHS

REACH SVHC

Not Contained Per -
ED/71/2019 (16 July
2019)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

Green Image

Not Relevant

Not Contained

Search Parts in this Series

36783 Series

Mates With

367921201 3.20mm MX120G Pitch Sealed
Female Connector Assembly

Current - Maximum per Contact	10.5A
Voltage - Maximum	28V DC
Solder Process Data	
Duration at Max. Process Temperature (seconds)	005
Lead-freeProcess Capability	WAVE
Process Temperature max. C	245
Material Info	
Reference - Drawing Numbers	
Product Specification	PS-36783-001-001
Sales Drawing	SD-36783-004-001

This document was generated on 09/17/2019

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[36783-1204](#)