

A15	UNSEALED/ ungeöffnet	965901-1	A	1	CuSn4	PRETINNED vorverzinkt min.0.8µm	0.5-1.0 FLR	1.4-2.3	E = 2.6 G = 2.8 D _{Dr} = 1.1	H = 3.6 K = 3.9 D = 1.8	3	4	5.5	18.8	0.4	SEE APPLICATION – SPECIFICATION 114-18050 siehe Verarbeitungspezifikation								
		965899-1	A	1	CuSn4	PRETINNED vorverzinkt min.0.8µm	>1.0-2.5 FLR	2.1-3.1	E = 3.6 G = 3.8 D _{Dr} = 1.8	H = 4.7 K = 4.9 D = 2.6	3.3	4.3	5.8	18.8	0.4									
		928876-1	A	1	CuSn4	PLAIN BLANK	0.5-1.0 FLK	2.0-2.7	E = 2.6 G = 2.8 D _{Dr} = 1.1	H = 3.9 K = 4.1 D = 2.4	3	4	5.5	18.8	0.4									
		927775-7	M	1	CuNi12ZN24	PRETINNED vorverzinkt min.0.8µm	0.5-1.0 FLK	2.0-2.7	E = 2.6 G = 2.8 D _{Dr} = 1.1	H = 3.9 K = 4.1 D = 2.4	3	4	5.5	18.8	0.4									
		927775-6	M		CuSn4																			
		927775-3	M		CuSn4	PRETINNED vorverzinkt min. 0.8µm																		
		927775-1	M		CuFe2	PRETINNED vorverzinkt min. 0.8µm																		
		928810-1	A	1	CuFe2	PRETINNED vorverzinkt min. 1µm	0.5-1.0 FLR	1.4-2.3	E = 2.6 G = 2.8 D _{Dr} = 1.1	H = 3.6 K = 3.9 D = 1.8	3.0	4.0	5.5	18.8	0.4									
		963884-1	A	1	CuSn4	PRETINNED vorverzinkt min. 1µm	>1.0-2.5 FLR	2.1-3.1	E = 3.6 G = 3.8 D _{Dr} = 1.8	H = 4.7 K = 4.9 D = 2.6	3.3	4.3	5.8	18.8	0.4									
		927773-3	N	1	CuSn4	PRETINNED vorverzinkt min. 1µm	>1.0-2.5 FLK	2.7-4.1	E = 3.6 G = 3.8 D _{Dr} = 1.8	H = 5.5 K = 5.8 D = 3.6	3.3	4.3	5.8	18.8	0.4									
		927773-1	N		CuFe2																			
		2-927768-1	R	1	CuSn4		>1.0-2.5 FLR	2.1-3.1	E = 3.6 G = 3.8 D _{Dr} = 1.8	H = 4.7 K = 4.9 D = 2.6	3.3	4.3	5.8	18.8	0.4									
		1-927768-1	R		CuFe2																			
		927768-9	P		CuSn4																			
		927768-6	P																					
		927768-3	P														PRETINNED vorverzinkt min. 1µm							
		927768-1	P																					
		1719810-1	A	1	CuFe2		0.5-1.0 FLR	1.4-2.3	E = 2.6 G = 2.8 D _{Dr} = 1.1	H = 3.6 K = 3.9 D = 1.8	3	4	5.5	18.8	0.4									
		2-927771-2	N	CuSn4																				
		2-927771-1	N	CuFe2																				
		1-927771-1	N	CuSn4																				
		927771-9	M																					
		927771-8	N																					
		927771-6	M																					
		927771-3	M		PRETINNED vorverzinkt min. 1µm																			
		927771-1	M	CuFe2		0.2-0.5 FLR											1.0-1.6	E = 2.1 G = 2.1 D _{Dr} = 0.8	H = 2.7 K = 2.8 D = 1.4	2.5	3.5	5.6	18.8	0.4
		2-927774-1	C	CuSn4																				
		1-927774-1	C	CuFe2																				
		927774-6	B	CuSn4																				
		927774-3	B	CuFe2	PRETINNED vorverzinkt min. 1µm																			
		927774-1	B																					
		963708-1	B	2	CuFe2	PRETINNED vorverzinkt min. 1µm	0.08-0.2 Sonderleitung	1.5-1.8	E = 1.7 G = 1.7 D _{Dr} = 0.6	H = 3.1 K = 3.2 D = 1.6	2.5	3.7	5.9	18.8	0.4									
		969137-1	A	3	CuSn4	PRETINNED vorverzinkt min.0.8µm	0.2-0.5 FLR	1.2-2.3	E = 2.1 G = 2.1 D _{Dr} = 0.8	H = 3.5 K = 3.6 D = 2	2.5	3.5	5	18.8	0.4									
1-927778-1	D	3	CuFe2		0.2-0.5 FLK	1.2-2.3	E = 2.1 G = 2.1 D _{Dr} = 0.8	H = 3.5 K = 3.6 D = 2.0	2.5	3.5	5	18.8	0.4											
927778-3	C		CuSn4	PRETINNED vorverzinkt min.0.8µm																				
927778-1	C		CuFe2																					
2112132-1	A	4	CuSn4	PLAIN BLANK	0.2-0.5 FLR	1.15-1.6	E = 2.4 G = 2.3 D _{Dr} = 1	H = 2.9 K = 2.9 D = 1.4	2.5	3.5	5.6	18.8	0.2											
2-927766-1	E	5	CuSn4		>1.0-2.5 FLK	2.7-3.0	E = 3.6 G = 3.8 D _{Dr} = 1.8	H = 5.4 K = 4.6 D = 3.2	3.5	5.9	7.5	18.8	0.4											
1-927766-1	E		CuFe2																					
927766-3	D		CuSn4											PRETINNED vorverzinkt min. 1µm										
927766-1	D		CuFe2																					
2-929937-1	E	5	CuSn4		>1.0-2.5 FLR	2.7-3.0	E = 3.6 G = 3.8 D _{Dr} = 1.8	H = 5.4 K = 4.6 D = 3.2	3.5	5.9	7.5	21	0.4											
1-929937-1	E		CuFe2																					
929937-6	E		CuSn4											PRETINNED vorverzinkt min. 1µm										
929937-3	E		CuFe2																					
929937-1	E	5	CuSn4		0.5-1.0 FLR	1.4-2.1	E = 2.6 G = 2.8 D _{Dr} = 1.1	H = 5.4 K = 4.6 D = 3.2	3	5.4	7	21	0.6											
2-929939-1	E		CuFe2																					
1-929939-1	E		CuSn4																					
929939-6	E		CuFe2											PRETINNED vorverzinkt min. 1µm										
929939-3	E	5	CuSn4		0.5-1.0 FLR	1.4-2.1	E = 2.6 G = 2.8 D _{Dr} = 1.1	H = 5.4 K = 4.6 D = 3.2	3	5.4	7	18.8	0.6											
929939-1	E		CuFe2																					
2-927770-1	G		CuSn4											PRETINNED vorverzinkt min. 1µm										
1-927770-1	G		CuFe2																					
927770-6	F	5	CuSn4		0.5-1.0 FLR	1.4-2.1	E = 2.6 G = 2.8 D _{Dr} = 1.1	H = 5.4 K = 4.6 D = 3.2	3	5.4	7	18.8	0.6											
927770-3	F		CuFe2																					
927770-1	F		CuSn4	PRETINNED vorverzinkt min. 1µm																				
2-929941-1	E	6	CuSn4		0.2-0.5 FLR	1.15-1.6	E = 2.1 G = 2.1 D _{Dr} = 0.8	H = 5.4 K = 4.6 D = 3.2	2.5	4.9	6.5	21	0.9											
1-929941-1	E		CuFe2																					
929941-6	D		CuSn4																					
929941-3	D		PRETINNED vorverzinkt min. 1µm																					
929941-1	D	6	CuFe2		0.2-0.5 FLR	1.15-1.6	E = 2.1 G = 2.1 D _{Dr} = 0.8	H = 5.4 K = 4.6 D = 3.2	2.5	4.9	6.5	18.8	0.9											
1-927772-1	D		CuSn4																					
927772-3	C		CuFe2																					
927772-1	C	6	CuFe2	PRETINNED vorverzinkt min. 1µm	0.2-0.5 FLR	1.15-1.6	E = 2.1 G = 2.1 D _{Dr} = 0.8	H = 5.4 K = 4.6 D = 3.2	2.5	4.9	6.5	18.8	0.9											
TE ORDER NO. STRIP FORM Bandware	REV.	DESIGN Ausführung	MATERIAL Werkstoff	SURFACE Oberfläche	WIRE RANGE Drähtgrößen Bereich (mm²)	INSULATION Isolations [mm]	STRIP FORM WIRE CRIMP INSUL.-CRIMP Isol.-Crimp Bandware		CRIMP DIMENSION (mm) Crimpabmessungen (mm)		A	B	C	D	E	CRIMP DATA AND CRIMP TOOL Crimpdaten u. Crimpwerkzeuge								

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[965899-1](#)