

WIRE RANGE 0.5 TO 1.5 mm²

INS. RANGE 1.6 TO 2.4mm DIA. (THIN WALLED CABLE)

SEALED APPLICATIONS ONLY

PRODUCT SPEC. 108-3069

APPLICATION SPEC. 114-3036

H/TOOL PN. 525316-4 (FOR 0.5 TO 0.75mm² AND 1 TO 1.5mm² WIRES)

PRE-TINNED BRASS				MADE FROM STRIP PN. 344070-1	344995-1
FINISH				MATERIAL	PART NUMBER
CUSTOMER DWG FOR REFERENCE ONLY				©COPYRIGHT 1991 BY AMP OF GREAT BRITAIN LTD. ALL INTERNATIONAL RIGHTS RESERVED. ALL PRODUCTS MAY BE COVERED BY BRITISH AND FOREIGN PATENTS AND/OR PATENTS PENDING.	
-	-	-	-	TOLERANCES UNLESS OTHERWISE STATED DEC \pm 0.5 ANGLES \pm 1°	DR. R.J.S. 25.9.91
-	-	-	-	CH. 28/09/91 APP. J.P.	
-	-	-	-	AMP of Great Britain Ltd.	TERMINAL HOUSE STANMORE MIDDLESEX
A E800-0041-01 14.02.01				.250 SERIES REC. (LOOSE PIECE) ECONOSEAL 3 H.C. (SEALED)	
1 PRELIM. ISSUE	-	25.9.91	SCALE	LOC	SIZE
REV	APPROVED	ECN	4 / 1	E	A3
		DATE	DWG. No. C344995		REV A SHEET 1 / 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[344995-1](#)