

JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
24E1	24.0	.035	.160	2.01	8,000	C-2F
24B1	24.0	.040	.239	3.00	4,000	C-2F
24C1	24.0	.072	.278	3.49	6,000	C-2V
35A1	35.0	.040	.239	3.00	7,500	C-2F
48D1	48.0	.021	.160	2.01	20,000	CC-2F
55C1	55.0	.050	.478	6.01	5,000	CC-2F

		METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS		JKL COMPONENTS CORPORATION								
			THIRD ANGLE PROJECTION	1 PL + 2 PL +	OTHERWISE SPECIFIED TIT 1 PL +/- 0.2 2 PL +/- ANGLE +/- 0		T-2 TELEPHONE SLIDE BASE ANSI #1					
		4/44/07	DRAWN BY	APPV'D BY		SIZE	FSCM NO.			SE AN	QI #1	
A	ADD PART NO. 24C1 RELEASED	8/16/00	L. WENGSTROM	S.C.	4/11/07	Α	55335					
REV. NO.		APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE		RELEASED DATE 8/16/0		^N 4/11/07	NO. A	SHEET 1 _{OF} 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

JKL Components: 48D1 24E1