

## Printed-circuit board connector - PC 35 HC/ 4-GF-15,00 BK - 1831963

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 125 A, Color: black, Contact surface: Silver, Mounting: Wave soldering



### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	25 pc
Weight per Piece (excluding packing)	88.8 g
Custom tariff number	85366990
Country of origin	Poland

### Technical data

Product type	PCB headers
Approval	UL Recognized
	cUL Recognized
	EAC
	cULus Recognized
Rated voltage (IEC)	1000
Rated current (IEC)	125
Mounting type	Wave soldering
Levels	single-level
Type of locking	Threaded flange
Plug-in system	POWER COMBICON 35
Contact type	Male connector

### Classifications

eCl@ss

eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 8.0	27440402
eCl@ss 9.0	27440402

## Printed-circuit board connector - PC 35 HC/ 4-GF-15,00 BK - 1831963

### Classifications

#### ETIM

ETIM 4.0	EC002637
ETIM 5.0	EC002637

### Approvals

#### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

---

#### Ex Approvals

---

#### Approvals submitted

---

#### Approval details

UL Recognized 		
	B	C
Nominal current IN	115 A	115 A
Nominal voltage UN	600 V	600 V

cUL Recognized 		
	B	C
Nominal current IN	105 A	105 A
Nominal voltage UN	600 V	600 V

EAC
-----

cULus Recognized 
--

---

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1831963](#)