



## Datasheet for part number DBM-25S

Our Catalog Part Number: DBM-25S
Our Global Manufacturing Part Number: 053513-0023
Brand: Cannon Product Category: D Sub Product Line: D Sub Series: D*M

Product Datasheet	
General	D*M High reliable D-Sub Connectors
Wire Gauge Range AWG	AWG 20-28
Mating Cycles	200
Contact Arrangement	25 contacts size 20
Dielectric Withstanding Voltage	1000 VAC at sea level
Current Rating	7.5 A max
Contact Resistance	7.5 milli Ohm max
Operating Temperature	-55°/+125°
Salt Spray Test	20 hours
Shell Material	steel
Shell Finish	Yellow chromate over zinc
Insulator Material	Thermoplastic, type PCT UL 94V-0
Insulator Color	black
Gender	Socket
Contact Type	Solder Pot
Contact Material	copper alloy
Contact Finish	gold over nickel
Hardware	.120" (3,05mm) Through Hole
Disclaimer	Our facility is not currently certified by the DLA and this product is not covered by the QPL/QML.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## ITT Cannon:

[DBM-25S-H](#) [DBM-25S](#) [DBMA-25S](#) [DBMA-25S-F0](#) [DBMA-25S-K52](#) [DBM-25S-A197](#) [DBMA-25S-A197-F0](#) [DBM-](#)  
[25S-D-NMBK52](#) [DBM-25S-0L3-NMBK52](#) [DBM-25S-S](#) [DBM-25S-F179](#) [DBM-25S-D](#) [DBMA-25S-NMBK52](#) [DBM-25S-](#)  
[Z](#) [DBM-25S-L](#) [DBM-25S-F179A](#) [DBM-25S-E](#) [DBM-25S-W](#) [DBM-25S-B](#) [DBM-25S-A](#) [DBM-25S-N-K126](#) [DBM-25S-G](#)  
[DBMA-25S-NMK52](#) [DBM-25S-K126](#) [DBM-25S-K](#) [DBM25S](#) [DBMA25S](#)