



**Product:** <u>82741</u> ♂

Electronic, 2 Pr #22 Str TC, FEP Ins, PVC Jkt, CMP

# **Product Description**

High Temperature Electronic, 2 Pair 22AWG (7x30) Tinned Copper, FEP Insulation, PVC Outer Jacket, CMP

## **Technical Specifications**

## **Product Overview**

Suitable Applications: indoor plenum applications; low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; voice communications; panel wiring

# **Physical Characteristics (Overall)**

#### Conductor

AWG	Stranding	Material	No. of Pairs
22	7x30	TC - Tinned Copper	2
Condu	ctor Count:		4

#### Insulation

Material	Nominal Wall Thickness
FEP - Fluorinated Ethylene Propylene	0.0065 in

#### **Color Chart**

Number	Color
1	Black & Red
2	Black & White

### Outer Shield Material



#### **Outer Jacket Material**

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	Flamarrest®	0.179 in	0.014 in

# **Electrical Characteristics**

#### **Conductor DCR**

Nominal Conductor DCR	Nominal Conductor Loop DCR
16 Ohm/1000ft	32 Ohm/1000ft

# Capacitance

Nom. Capacitance Conductor to Conductor 21 pF/ft

#### Inductance

Nominal Inductance

Impedance

# Nominal Characteristic Impedance 80 Ohm

#### Current

#### Max. Recommended Current [A]

3.3 Amps per Conductor at 25°C (10°C Temperature Rise)

#### Voltage

#### **UL Voltage Rating**

300 V RMS

#### **Temperature Range**

Operating Temp Range:	0°C To +60°C

#### **Mechanical Characteristics**

Bulk Cable Weight:	16 lbs/1000ft
Max. Pull Tension:	18 lbs
Min Bend Radius/Minor Axis:	2 in

#### **Standards**

NEC Articles:	Article 800
NEC/(UL) Compliance:	CMP
CEC/C(UL) Compliance:	CMP

#### **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

# Flammability, LS0H, Toxicity Testing

UL Flammability:	NFPA 262
CSA Flammability:	FT6
UL voltage rating:	300 V RMS

#### Plenum/Non-Plenum

Plenum (Y/N):	Yes	

# **Part Number**

Non-Plenum Number:	8741		

#### Variants

Item #	Color	Putup Type	Length	UPC
82741 8771000	Natural	Reel	1,000 ft	612825197676
Footnote:			C - C	RATE REEL PU

## **History**

Update and Revision:	Revision Number: 0.302 Revision Date: 06-24-2020

# © 2020 Belden, Inc

#### All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief

at the date of its publication. This information is d Disclosure is not to be considered a warranty or or regulations based on their individual usage of the	esigned only as a general guide for the sat yuality specification. Regulatory information product.	fe handling, storage, and any othen n is for guidance purposes only. Pr	r operation of the product itself or tr oduct users are responsible for det	ne one that it becomes a part of. T ermining the applicability of legisla	ne Product ition and

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: 82741 8771000