


**Product:** [5439W5](#) 

Surveillance CCTV, RG-59 #20 BC, Duobond+95% TC Braid, CM, Gel Fill



**Product Description**

Surveillance & CCTV Cable, RG59, Rated-CM, 20 AWG solid bare copper, foam polyolefin core, Duobond® + 95% tinned copper braid, CoreGuard® gel filled, PVC jacket

**Technical Specifications**

**Product Overview**

Suitable Applications:	CATV, MATV, Wet Location, Below-Grade Duct
------------------------	--

**Physical Characteristics (Overall)**

**Conductor**

AWG	Material	Nominal Diameter	No. of Coax
20	BC - Bare Copper	0.032 in	1

Conductor Count:	1
------------------	---

**Insulation**

Layer	Material	Nominal Diameter
1	PE - Polyethylene (Foam)	0.145 in

Table Notes:	Gas Injected
--------------	--------------

**Outer Shield Material**

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Tri-Laminate (Alum+Poly+Alum)	Duobond®	100%
Braid	2	Tinned Copper (TC)		95%

Table Notes:	Coreguard®
--------------	------------

**Outer Jacket Material**

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.236 in

**Electrical Characteristics**

**Conductor DCR**

Nominal Conductor DCR	Nominal Conductor DCR	Conductor Resistance	Nominal Outer Shield DCR	Outer Conductor DCR
10 Ohm/1000ft	10 Ohm/1000ft		2.5 Ohm/1000ft	2.5 Ohm/1000ft

**Capacitance**

Max. Capacitance Unbalance	Nom. Capacitance Conductor to Shield
1 pF/ft	16.3 pF/ft
1 pF/ft	

**Inductance**

Nominal Inductance
0.097 µH/ft

**Impedance**

**Nominal Characteristic Impedance**

75 Ohm

**High Frequency (Nominal/Typical)**

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.29 dB/100ft
5 MHz	0.63 dB/100ft
10 MHz	0.87 dB/100ft
50 MHz	1.7 dB/100ft
100 MHz	2.3 dB/100ft
200 MHz	3.4 dB/100ft
400 MHz	4.7 dB/100ft
700 MHz	6.3 dB/100ft
900 MHz	7.3 dB/100ft
1000 MHz	7.8 dB/100ft

**Delay**

Max. Delay Skew	Nominal Delay	Nominal Velocity of Propagation (VP) [%]
83 ns/100m	1.22 ns/ft	83%

**High Freq**

Frequency [MHz]
1 MHz
5 MHz
10 MHz
50 MHz
100 MHz
200 MHz
400 MHz
700 MHz
900 MHz
1000 MHz

**Voltage**

UL Voltage Rating
300 V RMS

**Temperature Range**

Non-UL Temp Rating:	75°C
Operating Temp Range:	-30°C To +75°C

**Mechanical Characteristics**

Bulk Cable Weight:	32 lbs/1000ft
Max. Pull Tension:	51 lbs
Min Bend Radius/Minor Axis:	2.4 in

**Standards**

NEC Articles:	Article 800
NEC/(UL) Compliance:	CL2, CM
CEC/C(UL) Compliance:	CM
CPR Euroclass:	Eca
RG Type:	59/U Type

**Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	Yes

EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Aerial:	Yes - Black only, when supported by messenger wire
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes - Black only
Suitability - Sunlight Resistance:	Yes - Black only

## Flammability, LSOH, Toxicity Testing

C(UL) Flammability:	FT1
UL Flammability:	UL1685 UL Loading
IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Part Number

### Variants

Item #	Color	Putup Type	Length	UPC
5439W5 010500	Black	Reel	500 ft	612825162384
5439W5 0101000	Black	Reel	1,000 ft	612825162377
5439W5 010U1000	Black	UnReel	1,000 ft	612825162360

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

## Product Notes

Notes:	Flooding grease between braid and jacket. Sequential footage marks in print legend. Can be used for MATV applications. Recommend 1545A or 1546A for CATV applications.
--------	--

## History

Update and Revision:	Revision Number: 0.342 Revision Date: 09-30-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.