

XS1L04NA310L2

inductive sensor XS1 Ø4 - L29mm - brass - Sn1mm - 5..24VDC - cable 10m



Product availability: Non-Stock - Not normally stocked in distribution facility



Main

| | |
|------------------------------------|--|
| Commercial Status | Commercialised |
| Range of product | OsiSense XS |
| Series name | General purpose |
| Sensor type | Inductive proximity sensor |
| Product specific application | - |
| Sensor name | XS1 |
| Sensor design | Cylindrical Ø 4 mm plain |
| Size | 29 mm |
| Body type | Fixed |
| Detector flush mounting acceptance | Flush mountable |
| Material | Metal |
| Type of output signal | Discrete |
| Wiring technique | 3-wire |
| [Sn] nominal sensing distance | 0.04 in (1 mm) |
| Discrete output function | 1 NO |
| Output circuit type | DC |
| Discrete output type | NPN |
| Electrical connection | Cable |
| Cable length | 32.81 ft (10 m) |
| [Us] rated supply voltage | 5...24 V DC |
| Switching capacity in mA | <= 100 mA with overload and short-circuit protection |
| IP degree of protection | IP67 conforming to IEC 60529 |

Complementary

| | |
|--------------------------|-------------------------------|
| Detection face | Frontal |
| Front material | PPS |
| Enclosure material | Nickel plated brass |
| Operating zone | 0...0.03 in (0...0.8 mm) |
| Cable composition | 3 x 0.11 mm ² |
| Wire insulation material | PvR |
| Status LED | 1 LED yellow for output state |
| Supply voltage limits | 5..30 V DC |
| Switching frequency | <= 5000 Hz |
| Voltage drop | <= 2 V at closed state |
| Current consumption | <= 10 mA at no-load |
| Delay first up | <= 5 ms |
| Delay response | <= 1 ms |
| Delay recovery | <= 1 ms |
| Marking | CE |
| Threaded length | 0 in (0 mm) |
| Height | 0.16 in (4 mm) |

| | |
|----------------|------------------------|
| Length | 1.14 in (29 mm) |
| Product weight | 0.76 lb(US) (0.345 kg) |

Environment

| | |
|---------------------------------------|---|
| Product certifications | CSA UL |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient air temperature for storage | -40...185 °F (-40...85 °C) |
| Vibration resistance | 25 gn amplitude = +/- 2 mm (f = 10...55 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 50 gn for 11 ms conforming to IEC 60068-2-27 |

Ordering and shipping details

| | |
|-----------------------|---|
| Category | 22486 - SENSORS, PROXIMITY |
| Discount Schedule | DS2 |
| GTIN | 003389110914719 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.01 |
| Product availability | Non-Stock - Not normally stocked in distribution facility |
| Returnability | N |
| Country of origin | FR |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS | Compliant - since 0935 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available Download Product Environmental |
| Product end of life instructions | Available Download End Of Life Manual |

Contractual warranty

| | |
|--------|-----------|
| Period | 18 months |
|--------|-----------|

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[XS1L04NA310L2](#)