

## Housing - VC-AL-T2-Z-M20-S - 1583636

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Aluminum die-cast sleeve housing, with grommet, locking screws with cylinder head, for a metric M20 cable gland, angled cable outlet, type VC2

### Product Features

- Hosing with two cable entries is available
- Angled cable outlet so the cable can be routed as desired, from the side and straight
- Aluminum housing with extended cabling space for high-position and power contact inserts



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 5 pc     |
| Weight per Piece (excluding packing) | 174.82 g |
| Custom tariff number                 | 85369010 |
| Country of origin                    | Poland   |

### Technical data

#### Dimensions

|        |       |
|--------|-------|
| Height | 80 mm |
|--------|-------|

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 125 °C |
|---------------------------------|-------------------|

#### General

|                                   |   |
|-----------------------------------|---|
| Note                              | When using fiber optics, the bending radii of the cable manufacturers must be observed. |
| Size                              | VC2   |
| Color                             | gray aluminum   |
| Locking type                      | Screw locking, cylinder head  |
| Tightening torque, mounting screw | 1.5 Nm ±0.3 Nm  |

# Housing - VC-AL-T2-Z-M20-S - 1583636

## Technical data

### General

|  |                   |
|--|-------------------|
| Fixing screws                          | M4                |
| No. of cable outlets                   | 1                 |
| Cable exit                             | Angled            |
| Screw connection                       | none              |
| Type of the screw connection           | M20 x 1.5         |
| Housing material                       | Aluminum die-cast |
| Seal material                          | NBR, conductive   |
| Material of locking screw              | V2A               |
| Flammability rating according to UL 94 | V0                |

### Standards and Regulations

|  |    |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27143424 |
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27371205 |
| eCl@ss 7.0 | 27371205 |
| eCl@ss 8.0 | 27440202 |
| eCl@ss 9.0 | 27440202 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000437 |
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31261502 |
| UNSPSC 7.0901 | 31261502 |
| UNSPSC 11     | 31261502 |
| UNSPSC 12.01  | 31261502 |
| UNSPSC 13.2   | 31261502 |

## Housing - VC-AL-T2-Z-M20-S - 1583636

### Approvals

#### Approvals

---

Approvals

EAC / EAC / EAC

---

Ex Approvals

---

Approvals submitted

---

### Approval details

EAC

---

EAC

---

EAC

---

### Accessories

Accessories

Device marking

Engraving material - GPE 22X22 SR/R - 0806628



Engraving material, Sheet, silver, unlabeled, can be labeled with: Engraving, Plotter, Mounting type: Adhesive, Lettering field: 22 x 22 mm

---

Full screw connection

Cable gland - HC-M-KV-M20(9-13) - 1690561



Metal screw connection up to 5 bar, thread length: 6 mm, cable diameter: 9 - 13 mm, WAF 22, screw connection: M20

## Housing - VC-AL-T2-Z-M20-S - 1583636

### Accessories

Cable gland - HC-M-KV-M20(11-16) - 1645998



Metal screw connection up to 5 bar, thread length: 6 mm, cable diameter: 11 - 16 mm, WAF 27, screw connection: M20


Cable gland - HC-EMV-KV-M20(7-12,5) - 1690503



EMC screw connection up to 5 bar, thread length: 5 mm, cable diameter: 7.0 - 12.5 mm, WAF 24, screw connection: M20

### Drawings


Dimensional drawing



Dimensional drawing



Dimensional drawing



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1583636](#)