

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC

DIST

CM

00

REVISONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
D		REVISED PER ECO-06-014772	13NOV06	KW	DC

1

MATERIAL: HOUSING — NYLON, UL94V-0 (COLOR — WHITE).

2

PINS TO COMPLY WITH SOLDERABILITY SPEC 109-11-3.

3

0.00381 [.000150] MINIMUM TIN LEAD OVER 0.00127 [.000050] MINIMUM NICKEL, ENTIRE LENGTH OF PIN.

4

NOTE DELETED.

5

0.00381 [.000150] MINIMUM TIN OVER 0.00127 [.000050] MINIMUM NICKEL, ENTIRE LENGTH OF PIN.

18.0
[.71]

12.80
[.504]

>PA66/6<

AMP

CIRCUIT #8

CIRCUIT #4

CIRCUIT #1

3.40±0.08
[.134±.003]

0.40
[.016]

3.20
[.126]

(1.067)
[.0420]
SQUARE

4.2 [.17]

(3.8)
[.15]

10.0
[.39]

1.40±0.05
[.055±.002]

1.067
[.0420]
SQUARE
TYP

4.2
[.17]

6.4
[.25]

5.50±0.10
[.217±.004]

3.25±0.05
[.128±.002]

3.5±0.5
[.14±.02]

SECTION A—A

ø1.8±0.5
[ø.07±.02]
TYP

4.2±0.1
[.17±.00]
NON-CUMULATIVE
TYP

5.50±0.10
[.217±.004]

6.4
[.25]

7.30±0.08
[.287±.003]

ø3.0±0.1
[ø.12±.00]
2X

CIRCUIT #1

RECOMMENDED MOUNTING HOLE PATTERN
FOR 1.78 [.070] MAX THICK P.C. BOARD
COMPONENT SIDE SHOWN

1

5

1

1

1-794529-1

1

3

1

1

794529-1

MATERIAL

FINISH

MATERIAL

COLOR

ASSEMBLY

PIN

HOUSING

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm [INCHES]

0 PLC ± 0.2 [.01]

1 PLC ± 0.13 [.005]

2 PLC ± 0.13 [.005]

3 PLC ± 0.13 [.005]

4 PLC ± 0.13 [.005]

ANGLES ± 30°

SEE CHART

SEE CHART

DWN
S. HOOVER

CHK
D. COLEY

APVD
D. COLEY

02-MAR-2005

02-MAR-2005

02-MAR-2005

NAME

108-1646

114-6067

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

Tyco Electronics Corporation
Harrisburg, Pa 17105-3608

ASSEMBLY, HEADER,
RIGHT ANGLE, 8 POSITION, W/PEGS,
94V-0, AMP-DUAC(TM) POWER CONNECTOR

SIZE
A1

CAGE CODE
00779

DRAWING NO
C=794529

RESTRICTED TO

CUSTOMER DRAWING

SCALE
5:1

SHEET
1

OF
1

REV
D

METRIC

AMP 4805 REV 31MAR2000

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-794529-1](#)