

THREAD DIM'S BEFORE PLATING: (G-0695)
 MAJOR DIA. .506 MIN.
 PITCH DIA. .477/.481
 MINOR DIA. .457/.461

THREAD DIM'S AFTER PLATING: (G-0684)
 MAJOR DIA. .505 MIN.
 PITCH DIA. .476/.481
 MINOR DIA. .456/.461

FINISH NOTE:

ELECTRODEPOSITED ZINC COATING WITH SUPPLEMENTARY FINISH PER: ASTM B633-98
 CLASSIFICATION Fe/Zn 12 SERVICE CONDITION SC3 TYPE II YELLOW CHROMATE CONVERSION COATING (SEE NOTE 4)

NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M

BILL OF MATERIAL			
CDPLIES TO	MATL SPEC (AS SUPPLIED STEEL POWDER(S))	FINISH	SEE FINISH NOTE & NOTE 4
1	9 18 DRW	JMB	DATE 2/18/88 SCALE 2=1
2	10 19	CHK	DATE SUPER DRW
3	12 20	APPD	DATE RAW STK WT
4	13 21		
5	14 23		
6	15 33		
7	16 43		
8	17 53		


TOLERANCE UNLESS OTHERWISE SPECIFIED
 TWO PLACE DEC ±.01 FRACTION ±1
 THREE PLACE DEC ±.005 ANGULAR ±1°

HEX NUT

<p>Littelfuse® DES PLAINES, ILL INOIS 60016</p>	DRAWING NO. AT 903-012
--	---------------------------

LTR	REVISION	CHK	APD
AR	39025C- REVISED & REDRAWN ON NEW FORMAT 3/13/98 JMB		
AS	80518C - ADD FINISH, CHG. NOTE 4	BJJ	
--	4/4/2000		
AT	82142D-CHG F0005-20 TO F-00006-.65 MIN. DEN. 5/22/02 P.J.M		

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.
 DENOTES CRITICAL CHARACTERISTICS.
 DENOTES CPK DIMENSIONS - MINIMUM CPK VALUE
 DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF THE ASSOCIATED MEASUREMENT PROCEDURE FOR MEASUREMENT OF THIS CHARACTERISTIC TO BE USED IN THE INSPECTION INSTRUCTIONS.
 DENOTES CP DIMENSIONS - MINIMUM CP VALUE
 DIMENSIONS WITHIN THE DIMENSIONAL LIMITATIONS SHOWN BE WITHIN THE DIMENSIONAL TOLERANCE SPECIFIED FOR MAXIMUM TOOL LIFE.



NOTES:

1. AXIS OF THREAD TO BE ⊥ WITHIN 1" TO FACE OF NUT. PITCH DIA. & MAJOR DIA. TO BE CONCENTRIC WITH MINOR DIA. WITHIN .007 T.I.R.
2. PART MUST SPIN FREELY ON "GO" GAGE. PART MAY ENTER "NO-GO" GAGE A MAXIMUM OF TWO THREADS. USE GAGE G-0695 BEFORE PLATING. USE GAGE G-0684 AFTER PLATING.
3. UNPLATED PARTS TO BE PROTECTED AGAINST OXIDATION UNTIL PLATING; PLATING TO BE DONE AS SOON AS POSSIBLE AFTER FABRICATION.
4. PLATED PARTS SHALL MEET THE SALT SPRAY REQUIREMENTS ASTM B-117 96 HOUR SALT SPRAY TEST. (CERTIFICATION REQUIRED).
5. VENDOR & L/F THREAD GAGE CORRELATION REQUIRED.
6. LITTELFUSE TO PLACE 100 NUTS IN BAG -896-259.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Littelfuse:](#)

[903-012](#)