



Standardausführung: V42254-A2115-B*** V42254-A2415-B*** 3)
 standard type: V42254-A2117-B*** V42254-A2417-B*** 3)
 V42254-A2315-B*** V42254-A2515-B*** 3)
 V42254-A2317-B*** V42254-A2517-B*** 3)


- 1) nach DIN 41652 T.2 und T.4
 - 2) Bemerkung: 50-polig: dreireihig
 - 3) nicht für 50-polig
 - 4) keine TE-Beschriftung bei:
 V42254-A2*17-B*** V42254-A2132-B*** V42254-A2152-B***
 V42254-A2*18-B*** V42254-A2133-B*** V42254-A2153-B***
 V42254-A2122-B*** V42254-A2142-B***
 - 5) Rille zur optischen Erkennung der Bolzentypen mit M3-Gewinde
 - 6) Blechteile örtlich herunter gedrückt
 - 7) Nur bei Ausführung mit Lötstiftlänge P = 3,2mm
 - 8) Sicke nur bei den 4 äußeren Masselötstiften.
- 1) according to DIN 41652 p.2 and p.4
 - 2) note: 50-contact version: 3 contact rows
 - 3) not for 50-contact version
 - 4) no TE-marking for:
 V42254-A2*17-B*** V42254-A2132-B*** V42254-A2152-B***
 V42254-A2*18-B*** V42254-A2133-B*** V42254-A2153-B***
 V42254-A2122-B*** V42254-A2142-B***
 - 5) groove in the stud bolts with M3 thread (visual recognition)
 - 6) shells pressed down locally
 - 7) only for versions with soldering-pin length of P = 3,2mm
 - 8) only the four corner grounding soldering-pins have a rib

9) OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI
 10) OBSOLETE



5,3 Min. Einbauhöhe
 min. mounting height

alle Kontakte
 all contacts



Ordering code Sachnr. V42254-A2*1*-	dimension Maß	A	B	C	D	E	F	G	H	J	K
B*09	09	31.19	16.46	25.0 ±0.12 ±0.13	8.02	12.93	2.74	6.3	19.53	10.97	10.64
B*15	15	39.52	24.79	33.3 ±0.15 ±0.1	8.02	12.93	2.74	6.3	27.76	10.97	10.64
B*25	25	53.42	38.5	47.04 ±0.13 ±0.13	8.02	12.93	2.76	6.3	41.53	10.97	10.64
B*37	37	69.7	54.96	63.5 ±0.13 ±0.13	8.02	12.93	2.76	6.3	57.96	10.97	10.64
B*50	50 ²⁾	67.31	52.55	61.1 ±0.14 ±0.11	10.87	15.75	2.76	6.3	55.58	13.82	10.64

Anforderungsstufe
 performance level¹⁾

V42254-	P	Q
A211*-+***	3.2	3.2
A231*-+***	5.55	5.55
A241*-+*** ³⁾	1.55	1.55
A251*-+*** ³⁾	13.65	14.05

dargestellt wird die 9-polige Ausführung
 drawn is the 9-contacts version



TE TE Connectivity		SCALE 2:1		WEIGHT	
LOC GW		DIMENSIONS IN MM		MATERIAL	
DATE 01.03.90		NAME Embo		PART NAME Sub-D Loetstiften gerade Buchsenleiste D-Sub straight soldering pins female connector	
DEP. PE Com PE&SE				PART NO. V42254-A2***-B***-*-27	
K ECO-15-011831 04FEB2016 DG		TOLERANCE UNLESS SPECIFIED OTHERWISE		SHT. 1-	
J ECO-15-007873 24JUN2015 SB					
H ECO-12-022105 02JAN2013 SLB					
REV. CHANGE ORDER		DATE		APP. Customer Drawing Nr. C-7-1393483-1	
				OF 8	

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG PENNSYLVANIA USA


PROPRIETARY:

mit Masselötstiften:
with grounding soldering pins: 3)

V42254-A2215-B***
V42254-A2217-B***
V42254-A2815-B***
V42254-A2817-B***



V42254-	P
A221*-+***	3.2
A281*-+***	5.55



Sachnr. ordering code V42254-A2*1*-	Polzahl No. of contacts	dimension Maß	
		R	S
8*09	09	30.4	12.4
8*15	15	38.8	12.4
8*25	25	52.8	12.4
8*37	37	69.1	12.4

Anforderungsstufe 1)
performance level 1)

Erläuterungen: Seite 1
dargestellt wird die 9-polige Ausführung
remarks: see page 1
drawn is the 9-contacts version

		SCALE 2:1		WEIGHT	
TE Connectivity		DIMENSIONS IN MM		MATERIAL	
DATE 01.03.93		NAME Emco		PART NAME Sub-D Loetstiften gerade	
DEP. PE Com PE&SE		TOLERANCE UNLESS SPECIFIED OTHERWISE		Buchsenleiste	
SEE SHEET 1		PART NO. V42254-A2***-B***-27		D-Sub straight soldering pins	
Customer Drawing Nr. C-7-1393483-1		REV. CHANGE ORDER		femle connector	
DATE		APP		SHT. 3+	
				OF 8	



THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA, USA

PROPRIETARY:

mit Masselötstiften und Gewindebolzen:
with grounding soldering-pins and screwlock stud bolts: 3)

M3: 4-40 UNC:
V42254-A2219-B*** V42254-A2216-B***
V42254-A2218-B***
V42254-A2819-B*** V42254-A2816-B***
V42254-A2818-B***



Verdrehsicherheit ≥ 70 Ncm
torque retention ≥ 70 Ncm




mit Masselötstiften und Stop-Mutter:
with grounding soldering-pins and thread: 3)

M3: 4-40 UNC:
V42254-A2214-B*** V42254-A2212-B***
V42254-A2814-B*** V42254-A2812-B***

Verdrehsicherheit ≥ 130 Ncm
torque retention ≥ 130 Ncm



Leiterplattenbohrung
PCB layout



Polzahl No. of contacts	n	Abmessungen in mm dimensions in mm		
		T	U	X
9	4	10.96	30.4	2.74
15	7	19.18	38.8	2.74
25	12	33.12	52.7	2.76
37	18	49.68	69.1	2.76



Erläuterungen: Seite 1
dargestellt wird die 9-polige Ausführung
remarks: see page 1
drawn is the 9-contacts version

		SCALE 2:1		WEIGHT	
TE Connectivity		MATERIAL		PART NAME Sub-D Loetsliffen gerade Buchsenleiste D-Sub straight soldering pins female connector	
DATE 01.03.90		PART NO. V42254-A2***-B***-27		SHT. 4+	
NAME Embo		REV. CHANGE ORDER		OF 8	
DEP. PE Com PE&SE		TOLERANCE UNLESS SPECIFIED OTHERWISE		Customer Drawing Nr. C-7-1393483-1	
SEE SHEET 1		DATE		APP.	

mit Distanzbolzen :
with distance bolts: 7)


V42254-A2120-B***
V42254-A2122-B***

Verdrehsicherheit ≥ 20 Ncm
torque retention ≥ 20 Ncm



Montageart
mounting type

Wanddicke 0.8 bis 1,6 mm
wall thickness from 0,8 to 1,6 mm





Sechskantbolzen V42254-A171-V2 oder
V42254-A172-V2 verwenden
use hexagonal bolts V42254-A171-V2
or V42254-A172-V2

Falls notwendig Distanzscheiben verwenden
if necessary, use washer(s)


mit Gewinde- und Distanzbolzen:
with screwlock stud bolts and distance bolts: 7)

	Gewindebolzen screwlock stud bolts	Distanzbolzen distance bolts
V42254-A2130-B***	M3	M3
V42254-A2131-B***	4-40 UNC	M3
V42254-A2132-B***	M3	M3
V42254-A2133-B***	4-40 UNC	M3

Verdrehsicherheit ≥ 80 Ncm
torque retention ≥ 80 Ncm



Einzelheit A (5:1)
detail A






Erläuterungen: Seite 1
dargestellt wird die 9-polige Ausführung
remarks: see page 1
drawn is the 9-contacts version

		SCALE 2:1		WEIGHT	
		MATERIAL			
DATE 01.03.90 NAME Embo DEP. PE Com PE&SE		PART NAME Sub-D Loetstiften gerade Buchsenleiste D-Sub straight soldering pins female connector			
TOLERANCE UNLESS SPECIFIED OTHERWISE		PART NO. V42254-A2***-B***-27 SHT. 5+			
SEE SHEET 1		Customer Drawing Nr. C-7-1393483-1			
REV.	CHANGE ORDER	DATE	APP.	OF 8	

mit Distanzbolzen und Clip :
with distance bolts and grounding socket : 7)

M3 : V42254-A2140-B*** 4-40 UNC : V42254-A2141-B***
V42254-A2142-B***

Verdrehsicherheit ≥ 20 Ncm
torque retention ≥ 20 Ncm






Clip für :
grounding socket for:
- Loch: $\varnothing 3,2 \pm 0,1$
hole:
- LP-Dicke: PCB thickness: $1,5 \pm 0,1$

mit Gewinde- und Distanzbolzen mit Clip :
with screwlock stud bolts and distance bolts and grounding socket : 7)

M3 : V42254-A2150-B*** 4-40 UNC : V42254-A2151-B***
V42254-A2152-B*** V42254-A2153-B***


Verdrehsicherheit ≥ 80 Ncm
torque retention ≥ 80 Ncm



Clip für :
grounding socket for:
- Loch: $\varnothing 3,2 \pm 0,1$
hole:
- LP-Dicke: PCB thickness: $1,5 \pm 0,1$

Montageart
mounting type


Wanddicke 0.8 bis 1.6 mm
wall thickness from 0,8 to 1,6 mm



Sachskantbolzen V42254-A171-V2 oder
V42254-A172-V2
verwenden
use hexagonal bolts V42254-A171-V2
or V42254-A172-V2

Falls notwendig Distanzscheiben
verwenden
if necessary, use washer(s)


Einzelheit A (5:1)
detail A



Erläuterungen: Seite 1
dargestellt wird die 9-polige Ausführung
remarks: see page 1
drawn is the 9-contacts version



TE Connectivity



SCALE 2:1

WEIGHT

MATERIAL

PART NAME Sub-D Loetstiften gerade
Buchsenleiste
D-Sub straight soldering pins
female connector

PART NO.

V42254-A2***-B***-27

3-IT

6.1

OF 8

REV CHANGE ORDER

DATE

APP

Customer Drawing Nr. C-7-1393483-1

DATE	01.03.90
NAME	Embo
DEP	PE Com PE&SE
TOLERANCE UNLESS SPECIFIED OTHERWISE	
SEE SHEET 1	

V 4 2 2 5 4 - A 2 * * * - B * * *

Anschlußausführung // connection type	
1	Lotestiftlänge 3,2mm // soldering pin length 3.2mm
2	Lotestiftlänge 3,2mm // soldering pin length 3.2mm mit Massebleistiftan // with grounding soldering pins
3	Lotestiftlänge 5,55mm // soldering pin length 5.55mm
4	Lotestiftlänge 1,35mm // soldering pin length 1.35mm
5	Lotestiftlänge 14,05mm // soldering pin length 14.05mm
6	Lotestiftlänge 5,55mm // soldering pin length 5.55mm mit Massebleistiftan // with grounding soldering pins

Steckerart // connector type	
8	Buchsenstele // female connector

Kontaktüberfläche // Kontaktart // contact surface // contact type	
1	Anforderungsstufe 1 // parallel Kontakte // performance level 1 // rolled contacts
2	Anforderungsstufe 2 // parallel Kontakte // performance level 2 // rolled contacts

Polzahl // no. of contacts	
09	9-polig // 9-contacts
15	15-polig // 15-contacts
24	23-polig // 23-contacts
37	37-polig // 37-contacts
50	50-polig // 50-contacts

PERFORMANCE LEVEL 2 CONTACT FINISH:
Au or Au FLASH OVER PONI

Stückverbindeunterzeichnung // connector hardware

1* Ausführung mit Gewindebolzen und Abstandsbolzen standard version + version with thread insert or screwlock stud bolts			
all TE - Beschreibung auf Blechteil with TE - marking on the shell	all TE - Bolzen with thread insert	all TE - Bolzen with screwlock stud bolts	
12	ja // yes	4-40UNC	nein // no
14	ja // yes	M3	nein // no
15	ja // yes	nein // no	nein // no
16	ja // yes	nein // no	4-40UNC
17	nein // no	nein // no	nein // no
18	nein // no	nein // no	4-40UNC
19	ja // yes	nein // no	M3

2* Ausführung mit Abstandsbolzen version with distance bolts		
Distancebolzen distance bolts	all TE - Beschreibung auf Blechteil with TE - marking on the shell	
20	M3	ja // yes
22	M3	nein // no

3* Ausführung mit Gewindebolzen und Abstandsbolzen version with screwlock stud bolts and distance bolts			
all Gewinde- bolzen with screwlock stud bolts	all Distance- bolzen with distance bolts	all TE - Beschreibung auf Blechteil with TE - marking on the shell	
30	M3	M3	ja // yes
31	4-40UNC	M3	ja // yes
32	M3	M3	nein // no
33	4-40UNC	M3	nein // no

4* Ausführung mit Abstandsbolzen mit Clip version with distance bolts and grounding socket		
all Distance- bolzen with distance bolts	all TE - Beschreibung auf Blechteil with TE - marking on the shell	
40	M3 + grounding socket	ja // yes
41	4-40UNC + grounding socket	ja // yes
42	M3 + grounding socket	nein // no

5* Ausführung mit Gewindebolzen und Abstandsbolzen mit Clip version with screwlock stud bolts and distance bolts and grounding socket			
all Gewinde- bolzen with screwlock stud bolts	all Distance- bolzen with distance bolts	all TE - Beschreibung auf Blechteil with TE - marking on the shell	
50	M3	Clip grounding socket	ja // yes
51	4-40UNC	Clip grounding socket	ja // yes
52	M3	Clip grounding socket	nein // no
53	4-40UNC	Clip grounding socket	nein // no

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN TYCO ELECTRONICS PERSONEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA, USA.


1) nicht für 30-polig
2) nur für Lotestiftlänge 3,2mm
3) nicht für 50-contacts version
2) not for soldering pin length 3.2mm

TE Connectivity		SCALE		WEIGHT	
DATE: 01.02.99		MATERIAL		PART NAME	
NAME: 1800		PART NAME		Sub-D Loetstift gerade	
APP: REC CE GFS		PART NAME		Buchsenstele	
YOUR NAME		PART NAME		D-Sub straight soldering pins	
YOUR NAME		PART NAME		female connector	
SEE SHEET 1		PART NO.		V42254-A2***-B***-27	
REV. CHANGE ORDER		DATE		Customer Drawing No. C-1-1975483-1	
				OF 8	

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA USA

PROPRIETARY:

1			2			3			4			5			6			7			8					
TE PARTNUMBER			OLD PARTNUMER (Description)									TE PARTNUMBER			OLD PARTNUMER (Description)											
1-1393484-0			V42254A2140B125			OBSOLETE						4-1393740-6			V42254A2215B225			OBSOLETE								
1-1393484-1			V42254A2140B137									4-1393740-7			V42254A2215B237			OBSOLETE								
1-1393484-2			V42254A2140B209									6-1393740-6			V42254A2216B109			OBSOLETE								
1-1393484-5			V42254A2141B209			OBSOLETE						6-1393740-7			V42254A2216B115			OBSOLETE								
1-1393484-6			V42254A2141B215			OBSOLETE						6-1393740-8			V42254A2216B125			OBSOLETE								
1-1393484-7			V42254A2141B225			OBSOLETE						6-1393740-9			V42254A2216B137			OBSOLETE								
1-1393484-8			V42254A2141B237						7-1393483-1			SUB D FEDERLEISTE														
1-1393740-3			V42254A2115B250			OBSOLETE			7-1393483-2			V42254A2112B225														
1-1393740-7			V42254A2212B209			OBSOLETE						7-1393483-5			SUB D FEDERLEISTE											
1-1393740-8			V42254A2212B215			OBSOLETE						7-1393483-6			V42254A2114B215			OBSOLETE								
1-1393740-9			V42254A2212B225			OBSOLETE						7-1393740-0			V42254A2216B209											
1393484-3			V42254A2116B209			OBSOLETE						7-1393740-1			V42254A2216B215											
1393484-4			V42254A2116B225			OBSOLETE						7-1393740-2			V42254A2216B225											
1393484-5			V42254A2116B237			OBSOLETE						7-1393740-3			V42254A2216B237											
1393484-8			V42254A2140B109			OBSOLETE						8-1393483-6			V42254A2115B125			 OBSOLETE								
1393484-9			V42254A2140B115									8-1393483-7			V42254A2115B209			OBSOLETE								
1393741-1			V42254A2812B215									8-1393483-8			V42254A2115B215											
1393741-3			V42254A2816B109									8-1393483-9			V42254A2115B225						OBSOLETE					
1393741-4			V42254A2816B115									8-1393740-7			SUB D FEDERLEISTE						OBSOLETE					
1393741-5			V42254A2819B209									8-1393740-8			SUB D FEDERLEISTE											
1393741-6			V42254A2819B225						8-1393740-9			SUB D FEDERLEISTE														
1485839-1			V42254A21XXB209			OBSOLETE						9-1393483-0			V42254A2115B237						OBSOLETE					
1485839-2			V42254A21XXB215									9-1393740-0			V42254A2219B209						 OBSOLETE					
1485839-3			V42254A21XXB215P									9-1393740-1			V42254A2219B215											
1485839-4			V42254A21XXB225									9-1393740-2			V42254A2219B225											
1485839-5			V42254A21XXB225P									9-1393740-3			V42254A2219B237											
1485839-6			V42254A21XXB237									9-1393740-8			V42254A2315B250											
1857984-3			25p Sub-D PCB Rec 4-40 UNC Scr.Lck+Clp			OBSOLETE																				
2-1393484-2			V42254A2151B209			OBSOLETE																				
2-1393484-3			V42254A2151B215																							
2-1393484-4			V42254A2151B225						OBSOLETE																	
2-1393740-8			V42254A2214B209																							
2-1393740-9			V42254A2214B215			OBSOLETE																				
3-1393484-1			V42254A2315B109			OBSOLETE																				
3-1393484-2			V42254A2315B115			OBSOLETE																				
3-1393484-3			V42254A2315B209			OBSOLETE																				
3-1393484-4			V42254A2315B215			OBSOLETE																				
3-1393484-5			V42254A2315B225			OBSOLETE																				
3-1393484-6			V42254A2315B237			OBSOLETE																				
3-1393740-0			V42254A2214B225			OBSOLETE																				
3-1393740-1			V42254A2214B237			OBSOLETE																				
4-1393740-4			V42254A2215B209			OBSOLETE																				
4-1393740-5			V42254A2215B215			OBSOLETE																				

			TE Connectivity						SCALE 2:1			WEIGHT		
									DIMENSIONS IN MM			MATERIAL		
						DATE 01.03.90			PART NAME			Sub-D Loetstiften gerade		
						NAME Embo						Buchsenleiste		
						DEP. PE Com PE&SE						D-Sub straight soldering pins		
												female connector		
						TOLERANCE UNLESS SPECIFIED OTHERWISE			PART NO.			SHT.		
									V42254-A2***-B***-*-27			8+		
SEE SHEET 1														
REV. CHANGE ORDER			DATE			APP.			Customer Drawing Nr. C-7-1393483-1			OF 8		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[7-1393740-2](#)