

THIS DRAWING IS UNPUBLISHED

RELEASED FOR PUBLICATION



© COPYRIGHT

 $\Theta_Y =$


ALL RIGHTS RESERVED

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	P5	REVISED PER ECO-16-012733	01SEP2016	NK	MM



- | | |
|---|--|
| 1 | TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADERS ARE HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD. |
| 2 | ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS. |
| 3 | .000100-.000200 MATTE TIN-LEAD OVER .000050 NICKEL. |
| 4 | .000100-.000200 BRIGHT TIN OVER .000050 NICKEL. |
| 5 | PRELIMINARY PART - NOT RELEASED FOR PRODUCTION. |
| 6 | HOUSING MATERIAL: FLAME RETARDANT THERMOPLASTIC; COLOR-BLACK. |
| 7 | OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI |



RECOMMENDED HOLE LAYOUT

	5	4	1.684	1.600	16	34	4-103328-9
	5	4	1.284	1.200	12	26	4-103328-8
		4	.884	.800	8	18	4-103328-7
△	OBsolete	4	.584	.500	5	12	4-103328-6
	5	4	3.984	3.900	39	80	4-103328-5
		4	.984	.900	9	20	4-103328-4
		4	.684	.600	6	14	4-103328-3
		4	.284	.200	2	6	4-103328-2
		4	.084	—	—	2	4-103328-1
		3	3.984	3.900	39	80	4-103328-1
△	OBsolete	3	3.884	3.800	38	78	3-103328-9
△	OBsolete	3	3.784	3.700	37	76	3-103328-8
△	OBsolete	3	3.684	3.600	36	74	3-103328-7
△	OBsolete	3	3.584	3.500	35	72	3-103328-6
		3	3.484	3.400	34	70	3-103328-5
△	OBsolete	3	3.384	3.300	33	68	3-103328-4
△	OBsolete	3	3.284	3.200	32	66	3-103328-3
△	OBsolete	3	3.184	3.100	31	64	3-103328-2
△	OBsolete	3	3.084	3.000	30	62	3-103328-1
△	OBsolete	3	2.984	2.900	29	60	3-103328-0
△	OBsolete	3	2.884	2.800	28	58	2-103328-9
△	OBsolete	3	2.784	2.700	27	56	2-103328-8
△	OBsolete	3	2.684	2.600	26	54	2-103328-7
△	OBsolete	3	2.584	2.500	25	52	2-103328-6
		3	2.484	2.400	24	50	2-103328-5
△	OBsolete	3	2.384	2.300	23	48	2-103328-4
△	OBsolete	3	2.284	2.200	22	46	2-103328-3
△	OBsolete	3	2.184	2.100	21	44	2-103328-2
△	OBsolete	3	2.084	2.000	20	42	2-103328-1
		3	1.984	1.900	19	40	2-103328-0
△	OBsolete	3	1.884	1.800	18	38	1-103328-9
△	OBsolete	3	1.784	1.700	17	36	1-103328-8
		3	1.684	1.600	16	34	1-103328-7
		3	1.584	1.500	15	32	1-103328-6
△	OBsolete	3	1.484	1.400	14	30	1-103328-5
		3	1.384	1.300	13	28	1-103328-4
		3	1.284	1.200	12	26	1-103328-3
		3	1.184	1.100	11	24	1-103328-2
BY 6-146254-1		3	1.084	1.000	10	22	1-103328-1
		3	.984	.900	9	20	1-103328-0
		3	.884	.800	8	18	103328-9
		3	.784	.700	7	16	103328-8
		3	.684	.600	6	14	103328-7
		3	.584	.500	5	12	103328-6
		3	.484	.400	4	10	103328-5
		3	.384	.300	3	8	103328-4
		3	.284	.200	2	6	103328-3
		3	.184	.100	1	4	103328-2
		3	.084	—	—	2	103328-1
		PLATING	C	B	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.						OWN MARTINELLI		10/15/92				TE Connectivity	
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPROVED BY JOHN KNITTLE		DATE 23NOV92		NAME		ASSEMBLY, HEADER, BREAKAWAY, MOD II, DOUBLE ROW .100 X .100 C/L, VERTICAL, WITH .025 SQUARE POSTS			
INCHES				PRODUCT SPEC									
		0 PLC ± — 1 PLC ± — 2 PLC ± — 3 PLC ± .005 4 ANGLES ± — FINISH		APPLICATION SPEC				SIZE		CAGE CODE	DRAWING NO	RESTRICTED TO	
MATERIAL		SEE TABLE		WEIGHT		—		A1		00779	C=103328	—	
POST: COPPER ALLOY				CUSTOMER DRAWING				SCALE		4:1	SHEET	1 OF 1	
												REV. PA	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[103328-4](#)