

Surface Mount Ultrafast Plastic Rectifier


SMA (DO-214AC)

RoHS
 COMPLIANT
 HALOGEN
FREE
 Available

FEATURES

- Low profile package
- Ideal for automated placement
- Glass passivated pellet chip junction
- Ultrafast recovery times for high efficiency
- Low forward voltage, low power losses
- High forward surge capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- AEC-Q101 qualified available
 - Automotive ordering code: P/NHE3 or P/NHM3
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

TYPICAL APPLICATIONS

For use in high frequency rectification and freewheeling application in switching mode converters and inverters for consumer, computer, automotive and telecommunication.

MECHANICAL DATA

Case: SMA (DO-214AC)

Molding compound meets UL 94 V-0 flammability rating

Base P/N-E3 - RoHS-compliant, commercial grade

Base P/N-M3 - halogen-free, RoHS-compliant, commercial grade

Base P/NHE3_X - RoHS-compliant and AEC-Q101 qualified
 Base P/NHM3_X - halogen-free, RoHS-compliant, and AEC-Q101 qualified

("_X" denotes revision code e.g. A, B,)

Terminals: matte tin plated leads, solderable per J-STD-002 and JESD 22-B102

E3, M3, HE3, and HM3 suffix meets JESD 201 class 2 whisker test

Polarity: color band denotes cathode end

PRIMARY CHARACTERISTICS	
$I_{F(AV)}$	1.0 A
V_{RRM}	50 V, 100 V, 150 V, 200 V
I_{FSM}	30 A
t_{rr}	15 ns
V_F at I_F	0.92 V
T_J max.	150 °C
Package	SMA (DO-214AC)
Diode variations	Single

MAXIMUM RATINGS ($T_A = 25\text{ °C}$ unless otherwise noted)						
PARAMETER	SYMBOL	ES1A	ES1B	ES1C	ES1D	UNIT
Device marking code		EA	EB	EC	ED	
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	150	200	V
Maximum RMS voltage	V_{RMS}	35	70	105	140	V
Maximum DC blocking voltage	V_{DC}	50	100	150	200	V
Maximum average forward rectified current (fig. 1)	$I_{F(AV)}$	1.0				A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	I_{FSM}	30				A
Operating junction and storage temperature range	T_J, T_{STG}	-55 to +150				°C



ELECTRICAL CHARACTERISTICS (T _A = 25 °C unless otherwise noted)						
PARAMETER	TEST CONDITIONS		SYMBOL	VALUE	UNIT	
Maximum instantaneous forward voltage	I _F = 0.6 A		V _F ⁽¹⁾	0.865	V	
	I _F = 1.0 A		V _F	0.920		
Maximum DC reverse current at rated DC blocking voltage			I _R	T _A = 25 °C	5.0	μA
				T _A = 100 °C	100	
Maximum reverse recovery time	I _F = 0.5 A, I _R = 1.0 A, I _{rr} = 0.25 A		t _{rr}	15	ns	
Maximum reverse recovery time	I _F = 0.6 A, V _R = 30 V, di/dt = 50 A/μs, I _{rr} = 10 % I _{RM}		t _{rr}	T _J = 25 °C	25	ns
				T _J = 100 °C	35	
Maximum stored charge	I _F = 0.6 A, V _R = 30 V, di/dt = 50 A/μs, I _{rr} = 10 % I _{RM}		Q _{rr}	T _J = 25 °C	10	nC
				T _J = 100 °C	25	
Typical junction capacitance	4.0 V, 1 MHz		C _J	10	pF	

Note

(1) Pulse test: 300 μs pulse width, 1 % duty cycle

THERMAL CHARACTERISTICS (T _A = 25 °C unless otherwise noted)						
PARAMETER	SYMBOL	ES1A	ES1B	ES1C	ES1D	UNIT
Typical thermal resistance	R _{θJA} ⁽¹⁾	85				°C/W
	R _{θJL} ⁽¹⁾	35				

Note

(1) Units mounted on PCB 5.0 mm x 5.0 mm (0.013 mm thick) land areas

ORDERING INFORMATION (Example)				
PREFERRED P/N	UNIT WEIGHT (g)	PREFERRED PACKAGE CODE	BASE QUANTITY	DELIVERY MODE
ES1D-E3/61T	0.064	61T	1800	7" diameter plastic tape and reel
ES1D-E3/5AT	0.064	5AT	7500	13" diameter plastic tape and reel
ES1DHE3_A/H ⁽¹⁾	0.064	H	1800	7" diameter plastic tape and reel
ES1DHE3_A/I ⁽¹⁾	0.064	I	7500	13" diameter plastic tape and reel
ES1D-M3/61T	0.064	61T	1800	7" diameter plastic tape and reel
ES1D-M3/5AT	0.064	5AT	7500	13" diameter plastic tape and reel
ES1DHM3_A/H ⁽¹⁾	0.064	H	1800	7" diameter plastic tape and reel
ES1DHM3_A/I ⁽¹⁾	0.064	I	7500	13" diameter plastic tape and reel

Note

(1) AEC-Q101 qualified

RATINGS AND CHARACTERISTICS CURVES ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)




Fig. 1 - Maximum Forward Current Derating Curve




Fig. 4 - Typical Reverse Leakage Characteristics




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current




Fig. 5 - Typical Junction Capacitance




Fig. 3 - Typical Instantaneous Forward Characteristics





Fig. 6 - Typical Thermal Impedance




PACKAGE OUTLINE DIMENSIONS in inches (millimeters)

SMA (DO-214AC)



Mounting Pad Layout





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Vishay:

[ES1A/11T](#) [ES1A/13T](#) [ES1A/2GT](#) [ES1A/5AT](#) [ES1A/61T](#) [ES1A/63T](#) [ES1A-E3/2GT](#) [ES1A-E3/51T](#) [ES1A-E3/5AT](#)
[ES1A-E3/61T](#) [ES1AHE3/2GT](#) [ES1AHE3/5AT](#) [ES1AHE3/61T](#) [ES1B/11T](#) [ES1B/13T](#) [ES1B/2GT](#) [ES1B/5AT](#)
[ES1B/61T](#) [ES1B/63T](#) [ES1B-E3/2GT](#) [ES1B-E3/5AT](#) [ES1B-E3/61T](#) [ES1B-E3/63T](#) [ES1BHE3/2GT](#) [ES1BHE3/5AT](#)
[ES1BHE3/61T](#) [ES1BHE3/63T](#) [ES1C/11T](#) [ES1C/13T](#) [ES1C/2GT](#) [ES1C/5AT](#) [ES1C/61T](#) [ES1C/63T](#) [ES1C-E3/2GT](#)
[ES1C-E3/5AT](#) [ES1C-E3/61T](#) [ES1C-E3/63T](#) [ES1CHE3/2GT](#) [ES1CHE3/5AT](#) [ES1CHE3/61T](#) [ES1CHE3/63T](#)
[ES1D/11T](#) [ES1D/13T](#) [ES1D/2FT](#) [ES1D/5AT](#) [ES1D/61T](#) [ES1D/63T](#) [ES1D-E3/11T](#) [ES1D-E3/13T](#) [ES1D-E3/2GT](#)
[ES1D-E3/5AT](#) [ES1D-E3/61T](#) [ES1D-E3/63T](#) [ES1DHE3/2GT](#) [ES1DHE3/5AT](#) [ES1DHE3/61T](#) [ES1DHE3/63T](#) [ES1PA-](#)
[E3/84A](#) [ES1PA-E3/85A](#) [ES1PAHE3/84A](#) [ES1PAHE3/85A](#) [ES1D-M3/61T](#) [ES1A/1T](#) [ES1A/2FT](#) [ES1A-E3/1T](#)
[ES1B/1T](#) [ES1B-E3/1T](#) [ES1C/1T](#) [ES1C-E3/1T](#) [ES1D/1T](#) [ES1D/2GT](#) [ES1D-E3/1T](#) [ES1BHE3_A/H](#) [ES1DHE3_A/H](#)
[ES1DHE3_A/I](#) [ES1AHE3_A/I](#) [ES1AHE3_A/H](#) [ES1B-M3/5AT](#) [ES1C-M3/5AT](#) [ES1C-M3/61T](#) [ES1D-M3/5AT](#) [ES1A-](#)
[M3/61T](#) [ES1B-M3/61T](#) [ES1A-M3/5AT](#)