

IRF7410GPbF

HEXFET® Power MOSFET



- Ultra Low On-Resistance
- P-Channel MOSFET
- Surface Mount
- Available in Tape & Reel
- Lead-Free
- Halogen-Free

| V_{DSS} | $R_{DS(on) \text{ max}}$ | I_D |
|-----------|--|--------|
| -12V | $7\text{m}\Omega @ V_{GS} = -4.5\text{V}$ | -16A |
| | $9\text{m}\Omega @ V_{GS} = -2.5\text{V}$ | -13.6A |
| | $13\text{m}\Omega @ V_{GS} = -1.8\text{V}$ | -11.5A |

Description

These P-Channel HEXFET® Power MOSFETs from International Rectifier utilize advanced processing techniques to achieve the extremely low on-resistance per silicon area. This benefit provides the designer with an extremely efficient device for use in battery and load management applications..

The SO-8 has been modified through a customized leadframe for enhanced thermal characteristics and multiple-die capability making it ideal in a variety of power applications. With these improvements, multiple devices can be used in an application with dramatically reduced board space. The package is designed for vapor phase, infrared, or wave soldering techniques.



Absolute Maximum Ratings

| | Parameter | Max. | Units |
|--------------------------------|---|-------------|-------|
| V_{DS} | Drain- Source Voltage | -12 | V |
| $I_D @ T_A = 25^\circ\text{C}$ | Continuous Drain Current, $V_{GS} @ -4.5\text{V}$ | -16 | A |
| $I_D @ T_A = 70^\circ\text{C}$ | Continuous Drain Current, $V_{GS} @ -4.5\text{V}$ | -13 | |
| I_{DM} | Pulsed Drain Current ① | -65 | |
| $P_D @ T_A = 25^\circ\text{C}$ | Power Dissipation ③ | 2.5 | W |
| $P_D @ T_A = 70^\circ\text{C}$ | Power Dissipation ③ | 1.6 | |
| | Linear Derating Factor | 20 | mW/°C |
| V_{GS} | Gate-to-Source Voltage | ± 8 | V |
| T_J, T_{STG} | Junction and Storage Temperature Range | -55 to +150 | °C |


Thermal Resistance

| | Parameter | Max. | Units |
|-----------------|-------------------------------|------|-------|
| $R_{\theta JA}$ | Maximum Junction-to-Ambient ③ | 50 | °C/W |

Electrical Characteristics @ T_J = 25°C (unless otherwise specified)

| Symbol | Parameter | Min. | Typ. | Max. | Units | Conditions |
|--|--------------------------------------|------|-------|------|-------|--|
| V _{(BR)DSS} | Drain-to-Source Breakdown Voltage | -12 | — | — | V | V _{GS} = 0V, I _D = -250μA |
| ΔV _{(BR)DSS} /ΔT _J | Breakdown Voltage Temp. Coefficient | — | 0.006 | — | V/°C | Reference to 25°C, I _D = -1mA |
| R _{DS(on)} | Static Drain-to-Source On-Resistance | — | — | 7 | mΩ | V _{GS} = -4.5V, I _D = -16A ② |
| | | — | — | 9 | | V _{GS} = -2.5V, I _D = -13.6A ② |
| | | — | — | 13 | | V _{GS} = -1.8V, I _D = -11.5A ② |
| V _{GS(th)} | Gate Threshold Voltage | -0.4 | — | -0.9 | V | V _{DS} = V _{GS} , I _D = -250μA |
| ΔV _{GS(th)} /ΔT _J | Gate Threshold Voltage Coefficient | — | -3.09 | — | mV/°C | |
| g _{fs} | Forward Transconductance | 55 | — | — | S | V _{DS} = -10V, I _D = -16A |
| I _{DSS} | Drain-to-Source Leakage Current | — | — | -1.0 | μA | V _{DS} = -9.6V, V _{GS} = 0V |
| | | — | — | -25 | | V _{DS} = -9.6V, V _{GS} = 0V, T _J = 70°C |
| I _{GSS} | Gate-to-Source Forward Leakage | — | — | -100 | nA | V _{GS} = -8V |
| | Gate-to-Source Reverse Leakage | — | — | 100 | | V _{GS} = 8V |
| Q _g | Total Gate Charge | — | 91 | — | nC | I _D = -16A |
| Q _{gs} | Gate-to-Source Charge | — | 18 | — | | V _{DS} = -9.6V |
| Q _{gd} | Gate-to-Drain ("Miller") Charge | — | 25 | — | | V _{GS} = -4.5V ② |
| t _{d(on)} | Turn-On Delay Time | — | 13 | 20 | ns | V _{DD} = -6V V _{GS} = -4.5V |
| t _r | Rise Time | — | 12 | 18 | | I _D = -1.0A |
| t _{d(off)} | Turn-Off Delay Time | — | 271 | 407 | | R _D = 6Ω |
| t _f | Fall Time | — | 200 | 300 | | R _G = 6Ω ② |
| C _{iss} | Input Capacitance | — | 8676 | — | pF | V _{GS} = 0V |
| C _{oss} | Output Capacitance | — | 2344 | — | | V _{DS} = -10V |
| C _{rss} | Reverse Transfer Capacitance | — | 1604 | — | | f = 1.0 MHz |

Source-Drain Ratings and Characteristics

| Symbol | Parameter | Min. | Typ. | Max. | Units | Conditions |
|-----------------|---|------|------|------|-------|--|
| I _S | Continuous Source Current (Body Diode) | — | — | -2.5 | A | MOSFET symbol showing the integral reverse p-n junction diode.  |
| I _{SM} | Pulsed Source Current (Body Diode) ① | — | — | -65 | | |
| V _{SD} | Diode Forward Voltage | — | — | -1.2 | V | T _J = 25°C, I _S = -2.5A, V _{GS} = 0V ② |
| t _{rr} | Reverse Recovery Time | — | 97 | 145 | ns | T _J = 25°C I _F = -2.5A |
| Q _{rr} | Reverse Recovery Charge | — | 134 | 201 | μC | di/dt = -100A/μs ② |

Notes:

- ① Repetitive rating; pulse width limited by max. junction temperature.
 ② Pulse width ≤ 400μs; duty cycle ≤ 2%.
 ③ Surface mounted on 1 in square Cu board, t ≤ 10sec.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Typical Transfer Characteristics




Fig 4. Normalized On-Resistance Vs. Temperature

IRF7410GPbF




Fig 5. Typical Capacitance Vs. Drain-to-Source Voltage




Fig 6. Typical Gate Charge Vs. Gate-to-Source Voltage




Fig 7. Typical Source-Drain Diode Forward Voltage




Fig 8. Maximum Safe Operating Area




Fig 9. Maximum Drain Current Vs. Case Temperature




Fig 10a. Switching Time Test Circuit




Fig 10b. Switching Time Waveforms




Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient

IRF7410GPbF

International
IR Rectifier




Fig 12. Typical On-Resistance Vs. Gate Voltage




Fig 13. Typical On-Resistance Vs. Drain Current



Fig 14a. Basic Gate Charge Waveform



Fig 14b. Gate Charge Test Circuit




Fig 15. Typical $V_{GS(th)}$ Vs. Junction Temperature





Fig 16. Typical Power Vs. Time

IRF7410GPbF

International
IR Rectifier


SO-8 Package Outline (MOSFET & Fetky)

Dimensions are shown in millimeters (inches)




NOTES:

1. DIMENSIONING & TOLERANCING PER ASME Y14.5M-1994.
2. CONTROLLING DIMENSION: MILLIMETER
3. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
4. OUTLINE CONFORMS TO JEDEC OUTLINE MS-012AA.
- ⑤ DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS. MOLD PROTRUSIONS NOT TO EXCEED 0.15 [.006].
- ⑥ DIMENSION DOES NOT INCLUDE MOLD PROTRUSIONS. MOLD PROTRUSIONS NOT TO EXCEED 0.25 [.010].
- ⑦ DIMENSION IS THE LENGTH OF LEAD FOR SOLDERING TO A SUBSTRATE.



SO-8 Part Marking Information


EXAMPLE: THIS IS AN IRF8707GPBF




Note: For the most current drawing please refer to IR website at <http://www.irf.com/package/>

SO-8 Tape and Reel

Dimensions are shown in millimeters (inches)



- NOTES:
1. CONTROLLING DIMENSION : MILLIMETER.
 2. ALL DIMENSIONS ARE SHOWN IN MILLIMETERS(INCHES).
 3. OUTLINE CONFORMS TO EIA-481 & EIA-541.



- NOTES:
1. CONTROLLING DIMENSION : MILLIMETER.
 2. OUTLINE CONFORMS TO EIA-481 & EIA-541.

Note: For the most current drawing please refer to IR website at <http://www.irf.com/package/>

Data and specifications subject to change without notice.
This product has been designed and qualified for the Consumer market.
Qualification Standards can be found on IR's Web site.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Infineon:](#)

[IRF7410GTRPBF](#)