



Product Description

High Performance Instrumentation, 3 Pair 18AWG (19x30) Tinned Copper, PVC Insulation E2 Color Code, Overall Beldfoil® Shield, PVC Outer Jacket, PLTC-ER

Technical Specifications

Product Overview

Suitable Applications: Instrumentation, Sensors, Valves, Positioners, 4-20mA, 0-10V		
Construction Details		
Conductor		
Element Number of Element AWG Stranding Material		
Pair(s) 3 18 19x30 TC - Tinned Copper		
Insulation		
Element Material Thickness [in] Color Code		
Pair(s) PVC - Polyvinyl Chloride 0.017 Black, Red and Numbered		
Outer Shield Material		
Type Material Coverage Drainwire Type		
Tape Alum / Poly 100% 18 AWG (7x26) TC		
Outer Jacket Material		
Material Thickness Diameter Ripcord		
PVC - Polyvinyl Chloride 0.053 in 0.426 in Yes		
Electrical Characteristics		
Electricals		
Element Nom. Conductor DCR Nom. Capacitance Cond-to-Cond		
Pair(s) 6.0 Ohm/1000ft 35 pF/ft		
Voltage		
UL Voltage Rating		
300 V (PLTC, CMG), 150 V (ITC)		
Mechanical Characteristics		
Temperature		
UL Rating Operating		
105°C -30°C to +105°C		
Table Notes: AWM 80°C		
Bend Radius		
Stationary Min.		
4.1 in		

Max. Pull Tension:	171 lbs
Bulk Cable Weight:	82

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance, Burial
Flammability / Fire Resistance:	UL1685 UL Loading, FT4, T-29-520, 1202
NEC / UL Compliance:	CMG, ITC-ER, PLTC-ER
AWM Compliance:	2464
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:

Revision Number: 0.333 Revision Date: 06-09-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: 9553 0605000