


Model 4814 Cable Assembly, Microwave, SMA (Male) Right Angle To SMA (Male)



	RG 316/U Tinted Brown
	4814-BB-XX
Cap. pF/ft.	29.0
Nom. Imp. Ohms	50
Loss	.56 dB/ft @ 3 GHz Max.
Temperature	+200°C. (+392°F.) Max.

MATERIALS:

Connectors: Right Angle SMA (Male) & SMA (Male)
 Body – Passivated Stainless Steel, Contact: Gold Plated Brass
 Dielectric – Teflon
 Finish: Contact – Hard gold plated
 Body – Nickel plated
 Cable: See Tab Block Marking: “Pomona 4814-X-XX”

RATINGS:

Operating Voltage: 335 VRMS Max.

ORDERING INFORMATION: Model 4814-BB-XX

X=Cable Type (see table)

XX = Cable Lengths, Standard Lengths: 24” (610), 48” (1219) & 60” (1524).

Additional lengths can be quoted upon request.

Ordering Example: 4814-BB-24 Indicates 24” in length.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02” (.51 mm), .xxx = ±.005” (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Made in USA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pomona:

[4814-BB-24](#) [4814-BB-60](#)