

Specification Sheet

Part Number: 173-60600



Electromagnetic Protection Braided Sleeving, Flame Retardant, 6 mm Dia,PET;TNCU, TCBK, 328ft/Reel

Article Number	173-60600
Type	HEGEMIPV006
Color	Tin-coloured and Black (TCBK)
Features & Benefits	• The patented material mix of the HEGMIPV0 braided sleeving offer electromagnetic protection and secure cable bundling. • The special combination of tin-plated copper and PBTVO yarn offers optimal inside and outside abrasion resistance. • In restricted space areas, HEGMIPV0 is easy to apply without any threads and breaks in the metal.
Quantity Per	metre

Product Description	HellermannTyton's patented Helagaine HEGEMIP braided sleeving offers electromagnetic protection on highly sensitive electronic applications. This material mix of braided sleeving is self-extinguishing, according to UL94 V0, and is particularly suitable for areas where fire protection is imperative.
Short Description	Electromagnetic Protection Braided Sleeving, Flame Retardant, 6 mm Dia,PET;TNCU, TCBK, 328ft/Reel
Global Part Name	HEGEMIPV006-PBT/SNCU-SR
Length L (Imperial)	328.0
Length L (Metric)	100.0
Bundle Diameter Min (Imperial)	0.2
Bundle Diameter Min (Metric)	5
Bundle Diameter Max (Imperial)	0.4
Bundle Diameter Max (Metric)	10
Diameter D (imperial)	0.24
Diameter D (metric)	6
Nominal Diameter (Imperial)	0.25
Nominal Diameter (Metric)	6

Material	Polyester (PBT) Tin-plated copper (SNCU)
Material Shortcut	PBT SNCU
Flammability	UL 94 V0 FMVSS 302
Halogen free	No
Operating Temperature (Metric)	-40°F to +302°F (-40°C to +150°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	328
Package Quantity (Metric)	100
Customs Number	5808100000
Content Unit(BMEcat)	metre
Weight (Imperial)	6.28