

WITHOUT PRIOR WRITTEN PERMISSION
FROM KEYSTONE ELECTRONICS CORPORATION

REEL DIA. REF.

FEED DIRECTION

$\pm .030$ [± 0.78]

$.100$ [2.54]

3.937 [100.0]
REF.

$.500$ [12.7] MIN.
DIA. HOLE THRU

$\pm .005$ [± 0.13]

$.157$ [4.0]

$\pm .005$ [± 0.13]

$.059$ [1.5] DIA.
HOLE (TYP.)

$.079$ [2.0]

$.507$ [12.88]
REF.

$\pm .005$ [± 0.13]
WIDTH

$.551$ [14.0]

$.016$ [0.4]
REF.

FEED DIRECTION

PITCH

TAPE AND REEL SPECIFICATIONS:

- MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER
ANSI/EIA-481 STANDARD
1.260 [32.0] WIDE; .787 [20.0] PITCH

- 13.0 [330.2] DIA. 250 PIECES OF
PART NO. 557 PER REEL.

5.9.11	CHANGE AS PER ECN 11-061	C
4.29.11	CHANGE AS PER ECN 11-058	B
4.18.11	CHANGE AS PER ECN 11-055	A
DATE	DESCRIPTION	REV.

KEYSTONE ELECTRONICS CORP.					
www.keyelco.com • ASTORIA, N.Y. 11105-2017 • Tel (718) 956-8900					
PART NAME SM BATTERY CLIP, ON TAPE					
MATERIAL AS NOTED					
FINISH AS NOTED			DRN BY NT		DATE 8.11.09
			APP'D LN		SCALE X
TOLERANCES INCH [MM]		CODE C	DWG NO. 557TR		
DECIMAL ± .015 [± 0.38]					
ANGULAR ± 1° UNLESS OTHERWISE SPECIFIED					

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Keystone Electronics:](#)

[557TR](#)