

OA80 Series



AC Fan - 115V, 230V
80 x 38mm (3.15" x 1.5")



Frame	Diecast Aluminum	<p><u>Operating Temperature</u> Ball Bearing -20C ~ +80C Sleeve Bearing -10C ~ +50C Storage Temp -40C ~ +80C</p> <p><u>Life Expectancy</u> Ball Bearing 60,000 hours (L10 at 40C) Sleeve Bearing 30,000 hours (L10 at 40C)</p> <p>Weight: ~ 0.62 lbs</p>	
Impeller	PBT, UL94V-0 plastic		
Connection	2x Lead Wires 22 AWG or terminals		
Motor	Shaded pole, impedance protected		
Bearing System	Dual ball or Sleeve		
Insulation Resistance	>100M ohm between lead-wire and frame (500VDC)		
Dielectric Strength	1 min at 1,500 VAC, 50/60Hz		

Model Number	Speed (RPM)	Airflow (CFM)	Noise (dB)	Volts AC	Voltage Range	Watts	Max. Static Pressure (\"H ₂ O)
OA80AP-11-1 *	3,000	30	36	115	103~126	9	0.22
OA80AP-11-2 *	2,300	25	32	115	103~126	9	0.16
OA80AP-11-3 *	1,950	17	28	115	103~126	9	0.07
OA80AP-22-1 *	3,000	30	36	230	160~253	12	0.22
OA80AP-22-2 *	2,300	25	32	230	160~253	12	0.16
OA80AP-22-3 *	1,950	17	28	230	160~253	12	0.07

* Indicate "TB" (Terminal Ball Bearing), "WB" (12" Wire Leads, Ball Bearing), "TS" (Terminal, Sleeve Bearing), "WS" (12" Wire Leads, Sleeve Bearing)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Orion Fans:

[OA80AP-11-2WS](#) [OA80AP-11-2TS](#) [OA80AP-11-2TB](#) [OA80AP-11-2WB](#) [OA80AP-11-1WB](#) [OA80AP-11-1WS](#)
[OA80AP-11-3TS](#) [OA80AP-11-3TB](#) [OA80AP-22-2WS](#) [OA80AP-22-2TS](#) [OA80AP-22-2TB](#) [OA80AP-22-2WB](#) [OA80AP-](#)
[11-1TB](#) [OA80AP-11-1TS](#) [OA80AP-22-1WB](#) [OA80AP-22-1TS](#) [OA80AP-22-1TB](#) [OA80AP-22-3TS](#) [OA80AP-22-3TB](#)
[OA80AP-22-3WS](#) [OA80AP-22-3WB](#) [OA80AP-11-3WB](#) [OA80AP-11-3WS](#) [OA80AP-22-1WS](#)