



PCB CONFIGURATION

- 1 ZINC PER QQ-Z-363
- 2 BERYLLIUM COPPER PER ASTM-B-196
- 3 PTFE PER MIL-P-19468
- 4 GOLD PLATE PER MIL-G-45204 0.76µm [0.000030] MINIMUM THICK.
- 5 TIN PLATE PER ASTM-B-545, 3.04µm [0.00120] MINIMUM THICK.
- 6. SEE INSTRUCTION SHEET 408-9889.
- 7 NICKEL PLATE PER QQ-N-290 5.08 µm [0.000200] MINIMUM THICK.
- 8 PACKAGE: 100 PER BAG/CARTON
- 9 PACKAGE: 28 PER TRAY PACKAGE

REVISIONS				
P	CLR	DESCRIPTION	DATE	BY
A1		REVISED PER ECR-17-009300	27JUN2017	LN RS

THIS DRAWING IS A CONTROLLED DOCUMENT.		DATE	VERSION
APPROVED: J. HAVENER		DATE	VERSION
DRAWN: J. HAVENER		DATE	VERSION
CHECKED: J. HAVENER		DATE	VERSION
DIMENSIONS: OTHER DIMENSIONS: OTHERWISE SPECIFIED:		NAME	
NOTES: 0 P.L.C. ±		JACK, VERTICAL, PCB,	
1 P.L.C. ±		75 OHM, COMMERCIAL BNC	
2 P.L.C. ± 0.20 [0.008]		SIZE	
4 P.L.C. ±		A2	
MATERIAL: SEE NOTES 1 - 3		CODE CODE DRAWING NO	
WEIGHT: 0.000000		A2 00779	
CUSTOMER DRAWING		SCALE: 5:1	
		SHEET 1 OF 1	
		REV A1	

9	1-6274291-1
8	6274291-2
5	6274291-1
SHELL FINISH PART NUMBER	

6274291

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[6274291-1](#)