







Leiterplatten-Layout Vorschlag für SMT
PCB-Layout Proposal for SMT




Anforderungsstufe 1
Performance Level 1

Kontaktbereich vergoldet
Mating Area gold plating


Anschlussbereich verzinkt 4-6 µm
Terminal Area 4-6 µm tin plating

Koplanarität der Anschlüsse ≤ 0,1 mm
Coplanarity Area of Termination ≤ 0,1 mm

Verpackt im Gurt nach DIN IEC 60286-3
Tape on Reel Packaging according to DIN IEC 60286-3
Verpackungseinheit: 280 Stück
Packaging unit: 280 pcs



Abspulrichtung - Reel off Direction



BA 8-13 - 8mm Bauhöhe
type 8-13 - Low Profile

Copyright by ERNI GmbH
Proprietary notice pursuant to ISO 9016 to be observed.

Information:				Tolerances		 All Dimensions in mm		Scale 3:1				
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.				Subject to modification without prior notice. Drawing will not be updated.				Designation				
								Messerl. SMC-Q 50-SMD-BA8-13 <i>Male SMC-Q 50-SMD-type 8-13</i>				
 www.ERNI.com								244838				I
												A3
e		30.06.2015						Class SMCQ				
Index		Date										

Copyright by ERNI GmbH
Proprietary notice pursuant to ISO 9006 to be observed.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ERNI Electronics:](#)

[244838](#)