






2			1					
LOC	DIST	REVISIONS						
J		P	LTR	DESCRIPTION		DATE	DWN	APVD
			O	RELEASED FJB0-0871-04		24AUG04	C.W	I.E
			01	REVISED PER ECO-09-024927		09NOV09	KK	AEG



- 1 MATERIAL & FINISH
PLUG HOUSING:THERMOPLASTIC(UL94V-0)
COLOR: BLACK.
REC CONTACT:COPPER ALLOY.
FINISH:OVER NICKEL,MATING END:
0.0002 OR 0.00076 MIN.GOLD,
TERMINATION END:TIN. AND SEALING TREATMENT
ALL OVER.
- 2 P.W.B. LAYOUT AND P.W.B. TREATMENT(REF.)
P.W.B. SURFACE ARE TREATED WITH SOLDER RESIST.
BOARD THICKNESS:1.6mm.
- 3 ON KINK POINT(4 PLACES).
- 4 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



D/D.SINISI	4 OBSOLETE	Au PL. 0.00076 MIN.	20	11	11.43	15.60	19.20	9	20	6—	—5
			60	31	36.83	41.00	44.60	29	60	6—	—4
			50	26	30.48	34.65	38.26	24	50	6—	—3
			40	21	24.13	28.30	31.90	19	40	6—	—2
			30	16	17.78	21.95	25.55	14	30	6—	—1
	4 OBSOLETE	Au PL. 0.0002 MIN.	20	11	11.43	15.60	19.20	9	20		—5
			60	31	36.83	41.00	44.60	29	60		—4
			50	26	30.48	34.65	38.26	24	50		—3
			40	21	24.13	28.30	31.90	19	40		—2
			30	16	17.78	21.95	25.55	14	30		5175710—1
REMARK		N	M	A		B		C	n	POS.	PART NO.
		CIRCUIT NO.			DIMENSION						

LEAD FREE

GENERAL TOLERANCE
10 ≥ : ±0.2
30 ≥ > 10: ±0.25
100 ≥ > 30: ±0.3
ANGLES: ±3°

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
MM

MATERIAL

1

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± -

4 PLC ± -

ANGLES ± -

FINISH 1

DWN COREL WANG 24AUG04

CHK STEVEN YAO 24AUG04

APVD I.ENOMOTO 24AUG04

PRODUCT SPEC 108-60036

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

Tyco Electronics

Tyco Electronics AMP K.K.
Kawasaki,Japan

NAME

PLUG ASSY V WITH KINK
AMPLIMITE .050 SERIES I B-TO-B CONN.

SIZE A3

CAGE CODE 00779

DRAWING NO C-5175710

RESTRICTED TO

SCALE NTS

SHEET 1 OF 1

REV 01

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[6-5175710-5](#)