## **HellermannTyton**

## **Specification Sheet**

Part Number: 170-03178



Braided Sleeving, Expandable, 2" Dia, PET, Black, 200 ft/bulk reel

Article Number 170-03178

Type BSP200B

Color Black (BK)

Features & Benefits

• Weave construction adjusts to twisting and flexing without creating wrinkles or bends. • Durable construction offers excellent abrasion and cut-through resistance as well as inertness to most chemicals and fungus. • Color options available to provide easy visual and safety identification of critical wiring components. • Expands to 150% of nominal diameter for fast, easy installation.

Quantity Per reel

Product Description	Designed to adjust and expand to irregular shapes, this general purpose sleeving is lightweight and offers a high tensile strength while still maintaining flexibility. This sleeving is an excellent choice for protecting wire and cable bundles from abrasion, chafing and heat degradation. Commonly used in electrial and industrial wire harnessing application where economy and durability are required for the protection of wires, cables, tubing, bundles and pneumatic hoses.
Short Description	Braided Sleeving, Expandable, 2" Dia, PET, Black, 200 ft/bulk reel
Global Part Name	BSP200B-PET-BK
Length L (Imperial)	200.0
Length L (Metric)	61.0
Bundle Diameter Min (Imperial)	1.5
Bundle Diameter Min (Metric)	38.1
Bundle Diameter Max (Imperial)	3.5
Bundle Diameter Max (Metric)	88.9
Diameter D (imperial)	2.0

50.8

2

50.8

Diameter D (metric)

**Nominal Diameter (Imperial)** 

**Nominal Diameter (Metric)** 

Material

Polyester (PET)

**Material Shortcut** 

**PET** 

**Flammability** 

UL 94 V0 FMVSS 302 FAR 25

Halogen free

Yes

**Operating Temperature (Metric)** 

-94°F to +257°F (-70°C to +125°C)

Reach Complaint(Article 33)

Yes

**ROHS Complaint** 

Yes

**UL Recognized (US)** 

Yes

Package Quantity(Imperial)

200

**Package Quantity (Metric)** 

60.96

**Customs Number** 

5808100000

Weight (Metric)

2.99

Weight (Imperial)

6.6

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions