

Technical drawing of a reel-to-reel tape cassette, showing top, side, and end views with dimensions in inches and millimeters.

Top View:

- REEL DIA. REF.
- FEED DIRECTION
- .500 [12.7] MIN. DIA. HOLE THRU

Side View:

- $\pm .030$ [± 0.78]
- .100 [2.54]
- 3.937 [100.0] REF.

End View:

- FEED DIRECTION
- $\pm .005$ [± 0.13]
- .630 [16.00]
- $\pm .005$ [± 0.13]
- .157 [4.0]
- $\pm .005$ [± 0.13]
- .059 [1.5] DIA. HOLE (TYP.)
- .071 [1.80]
- .130 [3.30]
- .467 [11.85]
- .016 [0.4] REF.

WITHOUT PRIOR WRITTEN PERMISSION FROM KEYSTONE ELECTRONICS

1. TAPE:
MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER
ANSI/EIA-481 STANDARD
.945 [24.0] WIDE; .630 [16.0] PITCH

2. REEL:
13.0 [330.2] DIA. 1,000 PIECES OF
PART NO. 2983 PER REEL.

4.09.12	CHANGE AS PER ECN 12-044	B
3.07.11	CHANGE AS PER ECN 11-028	A
DATE	DESCRIPTION	REV.

KEYSTONE ELECTRONICS CORP. www.keyelco.com • ASTORIA, N.Y. 11105-2017 • Tel (718) 956-8900			
PART NAME BATTERY CONTACT, ON TAPE			
MATERIAL AS NOTED			
FINISH AS NOTED		DRN BY NT	DATE 11.02.09
		APP'D LN	SCALE X
TOLERANCES INCH [MM] DECIMAL $\pm .015$ [± 0.38] ANGULAR $\pm 1^\circ$ UNLESS OTHERWISE SPECIFIED	CODE C	DWG NO. 2983TR	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Keystone Electronics:](#)

[2983TR](#)