

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT

By -

ALL RIGHTS RESERVED.

LOC

DIST

CM

00

REVISONS

DATE

DWN

APVD

AC1

REVISED PER ECO-12-018706

24OCT12

JR

SM

EDGE OF BOARD

3.96
[.156]
TYP

1.78+0.25
-0.00

0.070+0.010
-0.000

0.25 [.010]

2

RECOMMENDED MOUNTING HOLE PATTERN FOR 1.60 [.063] THICK P.C. BOARD

4.57
[.180]
REF

7.62±0.38
[.300±.015]

0.25/25.40
[.010/1.000]

1.14±0.03
[.045±.001]
SQUARE

0.20 [.008]

0.38 [.015]

3

10

10

1

POST NO. 1

3.18±0.25
[.125±.010]

0.25/25.40
[.010/1.000]

3.96
[.156]
TYP

1.98±0.30
[.078±.012]
TYP

0.25 [.010]

0.38 [.015]

ALL POSTS

16.51±0.38
[.650±.015]

9.27
[.365]
MIN TYP

1.85±0.25
[.073±.010]

0.76
[.030]
MAX

10.80±0.25
[.425±.010]

3.18±0.38
[.125±.015]
TYP

LEAD FREE

95.10	[3.744]	24	5-641208-4
91.14	[3.588]	23	5-641208-3
87.17	[3.432]	22	5-641208-2
83.21	[3.276]	21	5-641208-1
79.25	[3.120]	20	5-641208-0
75.29	[2.964]	19	4-641208-9
71.32	[2.808]	18	4-641208-8
67.36	[2.652]	17	4-641208-7
63.40	[2.496]	16	4-641208-6
59.44	[2.340]	15	4-641208-5
55.47	[2.184]	14	4-641208-4
51.51	[2.028]	13	4-641208-3
47.55	[1.872]	12	4-641208-2
43.59	[1.716]	11	4-641208-1
39.62	[1.560]	10	4-641208-0
35.66	[1.404]	9	3-641208-9
31.70	[1.248]	8	3-641208-8
27.74	[1.092]	7	3-641208-7
23.77	[.936]	6	3-641208-6
19.81	[.780]	5	3-641208-5
15.85	[.624]	4	3-641208-4
11.89	[.468]	3	3-641208-3
7.92	[.312]	2	3-641208-2
DIM (L)		NO.OF POSN	ASSEMBLY

LEAD STRAIGHT

95.10	[3.744]	24	2-641208-4
91.14	[3.588]	23	2-641208-3
87.17	[3.432]	22	2-641208-2
83.21	[3.276]	21	2-641208-1
79.25	[3.120]	20	2-641208-0
75.29	[2.964]	19	1-641208-9
71.32	[2.808]	18	1-641208-8
67.36	[2.652]	17	1-641208-7
63.40	[2.496]	16	1-641208-6
59.44	[2.340]	15	1-641208-5
55.47	[2.184]	14	1-641208-4
51.51	[2.028]	13	1-641208-3
47.55	[1.872]	12	1-641208-2
43.59	[1.716]	11	1-641208-1
39.62	[1.560]	10	1-641208-0
35.66	[1.404]	9	641208-9
31.70	[1.248]	8	641208-8
27.74	[1.092]	7	641208-7
23.77	[.936]	6	641208-6
19.81	[.780]	5	641208-5
15.85	[.624]	4	641208-4
11.89	[.468]	3	641208-3
7.92	[.312]	2	641208-2
DIM (L)		NO.OF POSN	ASSEMBLY

1

POST TO WITHSTAND 13 NEWTONS (3 LBS) MINIMUM AXIAL FORCE IN BOTH DIRECTIONS SHOWN WITHOUT DISLODGING.

2

TOLERANCES APPLY TO SOLDER SIDE OF BOARD.

3

MEASURED AT SURFACE

4

PLASTIC FLASH PERMITTED IN THIS AREA.

5

PARTS COMPLY WITH AMP SOLDERABILITY SPEC. NO. 109-11-2.

6

ONE HOLE MAY BE UNDERSIZED 1.65/1.52 [.065/.060] DIA. FOR ASSEMBLY RETENTION DURING WAVE SOLDERING.

7

MATERIAL: HEADER-THERMOPLASTIC POLYESTER GLASS-FILLED 94V-0 (NATURAL)
POST-COPPER ALLOY (SEE NOTES 13 & 14 FOR PLATING)

8

COORDINATE DIMENSION APPLIES FROM CENTER OF ACTUAL FEATURE.

9

PLASTIC BURRS CAUSED BY CUT-OFF TOOLING ARE PERMITTED WITHIN THE MAXIMUM TOLERANCE ENVELOPE.

10

POST TO BE MEASURED WHEN STRIP IS HELD FLAT.

11

POST MUST WITHSTAND TWO 90° BENDS AGAINST EXTRUSION WITHOUT BREAKING.

12

DIMENSION SHOULD BE 4.45 [.175] MIN WHEN MATING WITH A MTA-156 CONNECTOR ASSEMBLY OR A SL-156 CONNECTOR ASSEMBLY.

13

PLATING: GOLD PLATE AREA, 0.00076 [.000030] GOLD OR 0.00008 [.000003] MIN GOLD FLASH OVER 0.00068 [.000027] PALLADIUM NICKEL, PER TE CONNECTIVITY'S DISCRETION, ALL SIDES, OVER NICKEL UNDERPLATE, 0.00127 [.000050] MIN, ALL SIDES AND ENTIRE LENGTH OF POST.

14

PLATING: BRIGHT TIN/LEAD (93/7) PLATE AREA, 0.00381-0.00889 [.000150-.000350] THICK, ALL FOUR SIDES 3.18 [.125] MINIMUM FOR -2 THRU -24. MATTE TIN PLATE AREA 0.00381-0.00889 [.000150-.000350] THICK ALL FOUR SIDES, 3.18 [.125] FOR -32 THRU -54.

15

OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

METRIC

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±
1 PLC ±
2 PLC ±
3 PLC ± 0.13 [.005]
4 PLC ±
ANGLES ±

7

7

DRAWING NO

00779

07-NOV-2002

NAME

MTA-156 HEADER ASSEMBLY, FRICTION LOCK, STRAIGHT, .045 SQUARE POST, .000030 GOLD

SIZE

A1

CAGE CODE

00779

DRAWING NO

07-NOV-2002

WEIGHT

00779

07-NOV-2002

CUSTOMER DRAWING

SCALE

5:1

SHEET

1

OF

1

REV

AC1

TE Connectivity

MTA-156 HEADER ASSEMBLY, FRICTION LOCK, STRAIGHT, .045 SQUARE POST, .000030 GOLD

00779

07-NOV-2002

00779

07-NOV-2002

4805 (3/11)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[3-641208-8](#)