

8

7

6

5

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC

DIST

REV

LTR

DESCRIPTION

DATE

DWN

APVD

1. USE INSTRUCTION SHEET 9089

2. MAXIMUM PANEL THICKNESS: 6.10 [.240]

3. DIELECTRIC MUST WITHSTAND A 6 POUND PUSHOUT FORCE

4 PACKAGED 1 CONNECTOR PER BAG

5 USE CRIMP TOOL: 220190-1

34.93 MAX
[1.375]

11.07 MAX
[.436]

1

2

5

4

6

3

7

8

12.83 +0.13
-0.00 DIA

.505 +.005
-.000 DIA

5.54 +0.08
-0.00

.218 +.003
-.000

RECOMMENDED PANEL CUTOUT

19.84 REF
[.781]

3.96
[.156]

15.88
[.625]

5.94
[.234]

RECOMMENDED STRIP LENGTH

19.84 REF
[.781]

3.96
[.156]

15.88
[.625]

5.94
[.234]

1.57
[.062]

FOIL

RECOMMENDED STRIP LENGTH FOR 221221-9 ONLY

OBSOLETE	RG-59/U, 59A/U, 59B/U	58085-1	-	-	329633	1-329631-2	1-329632-2	9-50428-0	221200-3	221255-2	9-221221-0								
OBSOLETE	RG-179/U, 179A/U, 179B/U, 187/U, 187A/U	58304-1	227194-2	222001-6	329633	1-329631-2	1-329632-2	9-328666-0	2-221200-0	221255-3	1-221221-0								
OBSOLETE	AT&T 735A	58174-1	-	-	329633	1-329631-2	1-329632-2	9-328666-2	221200-9	221255-3	221221-9								
OBSOLETE	CUSTOM CABLE: (C&M CABLE 25785)	58304-4	-	-	329633	1-329631-2	1-329632-2	3-328666-6	221200-6	221255-4	221221-8								
	BELDEN 9240, 9259, 9266	58085-1	-	-	329633	1-329631-2	1-329632-2	9-50428-0	2-221200-5	221255-2	221221-7								
OBSOLETE	RG-59/U, 59A/U, 59B/U	58085-1	-	-	329633	1-329631-2	1-329632-2	9-50428-0	221200-3	221255-2	221221-6								
	RG-179/U, 179A/U, 179B/U, 187/U, 187A/U	58304-1	227194-2	222001-6	329633	1-329631-2	1-329632-2	9-328666-0	2-221200-0	221255-3	221221-5								
OBSOLETE	BELDEN 8218	58174-1	-	-	329633	1-329631-2	1-329632-2	9-329461-0	221200-9	221255-3	221221-3								
	RG-59/U, 59A/U, 59B/U	58085-1	-	-	329633	1-329631-2	1-329632-2	9-50428-0	221200-3	221255-2	221221-2								
	BELDEN 9248 AND MADISON 18AWG	58086-1	-	-	329633	1-329631-2	1-329632-2	9-50427-0	3-221200-2	221255-1	221221-1								
	CABLE	DIE SET	8	TUBING, PLASTIC QTY=1	7	TUBING, METAL QTY=1	6	GASKET QTY=1	5	JAM NUT QTY=1	4	LOCK WASHER QTY=1	3	FERRULE QTY=1	2	CONTACT QTY=1	1	JACK ASSEMBLY QTY=1	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± 0.41 [.016]
3 PLC ± -
4 PLC ± -
ANGLES ± -
FINISH -

DWN B. SCOTT 1-16-91
CHK J. LIPPERT 1-25-91
APVD M. PHILLIPS 1-25-91

PRODUCT SPEC 108-12095
APPLICATION SPEC -
SIZE -
WEIGHT -
CUSTOMER DRAWING

tyco Electronics
Tyco Electronics Corporation
Harriaburg, PA 17105-3608
JACK.
BULKHEAD, 75 OHM, BNC
A1 00779 221221
SCALE 5:1
SHEET 1 OF 1
REV T1

AMP 4805 REV 31MAR2000

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[221221-5](#)