


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC		DIST		REVISIONS			
AD	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		J2		REVISED PER ECO-11-004917	11MAR11	RK	HMR



CONTACT IDENTIFICATION LETTER "C" (LOCATED IN THIS AREA)

HOUSING (SEE TABLE FOR PART NO.)

POSITION #1 INDICATOR

OBSOLETE	2	2.59	1.295	1-103653-1	12	6-103948-1
OBSOLETE	2	2.39	1.195	1-103653-0	11	6-103948-0
OBSOLETE	2	2.19	1.095	103653-9	10	5-103948-9
OBSOLETE	2	1.99	.995	103653-8	9	5-103948-8
OBSOLETE	2	1.79	.895	103653-7	8	5-103948-7
OBSOLETE	3	2.39	.795	103653-6	7	5-103948-6
	2	1.39	.695	103653-5	6	5-103948-5
	4	2.38	.595	103653-4	5	5-103948-4
	4	1.98	.495	103653-3	4	5-103948-3
	5	1.98	.395	103653-2	3	5-103948-2
	8	2.36	.295	103653-1	2	5-103948-1
OBSOLETE	2	2.59	1.295	1-103653-1	12	1-103948-1
OBSOLETE	2	2.39	1.195	1-103653-0	11	1-103948-0
	2	2.19	1.095	103653-9	10	103948-9
	2	1.99	.995	103653-8	9	103948-8
	2	1.79	.895	103653-7	8	103948-7
	3	2.39	.795	103653-6	7	103948-6
	2	1.39	.695	103653-5	6	103948-5
	4	2.38	.595	103653-4	5	103948-4
	4	1.98	.495	103653-3	4	103948-3
	5	1.98	.395	103653-2	3	103948-2
	8	2.36	.295	103653-1	2	103948-1
PLATING	6	B	A	HOUSING PART NUMBER	NO OF POSN	ASSEMBLY PART NUMBER ON STRIP

- 1 CONTACTS ARE LATCHED INTO THE PRELOAD WINDOWS
- 2 USE WITH #26-#30 AWG WIRE SIZE, .054/.030 INSULATION DIAMETER, .015 MAXIMUM INSULATION THICKNESS
- 3 THE DIMENSION APPLIES WITH THE FORWARD PRELOAD STOP IN CONTACT WITH THE HOUSING SURFACE
- 4 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 5. FOR INDIVIDUAL ASSEMBLIES SEE PART NUMBER 103658
- 6 ASSEMBLIES ARE JOINED BY THE CARRIER STRIP. ORDER QUANTITY REFLECTS TOTAL NUMBER OF INDIVIDUAL ASSEMBLIES REQUIRED. SEE TABLE FOR NUMBER OF ASSEMBLIES PER STRIP.
- 7 MATERIAL- HOUSING: FLAME RETARDANT THERMOPLASTIC, COLOR: BLACK PINS: PHOS. BRONZE
- 8 FINISH- PINS: .000015 GOLD IN THE CONTACT AREA, .000050-.000100 BRIGHT TIN-LEAD ON THE TERMINATION AREA, OVER .000050 NICKEL.
- 9 FINISH- PINS: .000015 GOLD IN THE CONTACT AREA, .000050-.000100 MATTE TIN ON THE TERMINATION AREA, OVER .000050 NICKEL.
- 10 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN	R BROWN	26JUL00
CHK	K WRIGHT	26JUL00
APVD	K WRIGHT	26JUL00

TE Connectivity

SHROUDED PIN ASSY, AMPMDO MTE, SINGLE ROW, .100 CL, POLARIZED, W/ LATCH WINDOWS, FOR #26-#30 AWG WIRE SIZE, STRIP FORM

108-25034
114-25026

SIZE: A2 CAGE CODE: 00779 DRAWING NO: C=103948

SCALE: 4:1 SHEET: 1 of 1 REV: J2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[103948-1](#)