

LOC		DIST		REVISIONS				DATE		DWN		APVD	
—		—		P	LTR	DESCRIPTION							
NUMMER 825435				F		Contact pin base material change from CuSn (Phosphor bronze) to CuZn (Brass). Plating changed to min. 0.7 microns Pd Ni + 0.1 microns gold flash at contact area (Area F).		24JUN2014		TJ		JK	
VERWENDET FÜR E 75-9233													
WAR —													

POLZ.	L±0.5	BESTELL-NR.	
—	—	—	—
2	5.08	825 435 -2	
3	7.62	—	-3 Δ_3
4	10.16	—	-4
5	12.70	—	-5 Δ_3
6	15.24	—	-6 Δ_3
7	17.78	—	-7
8	20.32	—	-8 Δ_3
9	22.86	—	-9 Δ_3
10	25.40	-1	-0 Δ_3
11	27.94	1-	-1
12	30.48	1-	-2
13	33.02	1-	-3
14	35.56	1-	-4 Δ_3
15	38.10	1-	-5
16	40.64	1-	-6
17	43.18	1-	-7
18	45.72	1-	-8
19	48.26	1-	-9
20	50.80	-2-	-0 Δ_3
21	53.34	-2-	-1 Δ_2
22	55.88	-2-	-2 Δ_3
23	58.42	2-	-3
24	60.96	2-	-4
25	63.50	2-	-5
26	66.04	2-	-6
27	68.58	2-	-7 Δ_3
28	71.12	2-	-8
29	73.66	2-	-9 Δ_3
30	76.20	3-	-0 Δ_3
31	78.74	3-	-1
32	81.28	3-	-2
33	83.82	3-	-3
34	86.36	3-	-4
35	88.90	3-	-5
36	91.44	3-	-6
37	93.98	3-	-7 Δ_3
38	96.52	3-	-8
39	99.06	3-	-9
40	101.60	4-	-0
41	104.14	4-	-1
42	106.68	4-	-2
43	109.22	4-	-3
44	111.76	4-	-4
45	114.30	4-	-5
46	116.84	4-	-6
47	119.38	4-	-7
48	121.92	4-	-8
49	124.46	4-	-9
50	127.00	5-	825 435 -0

Δ_1 STECKSEITE: IM BEREICH "F" MIN. 0.7 μ m PdNi+0.1 μ m GOLD FLASH ÜBER 1.27 μ m NICKEL.
 Δ_2 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI
 Δ_3 OBSOLETE

CAD-ORIGINAL ZEICHNUNG NICHT ÄNDERN		
KONTAKTSTIFT	Cu Zn	Δ_1
STIFTGEHÄUSE	PBT GV	GRÜN
BENENNUNG	WERKSTOFF	OBERFLÄCHE FARBE

ZEICHNUNG GÜLTIG AB KW 39/96			
DIMENSIONS:	DWN 11.04.84	MATERIAL	FINISH
mm	A.HO	—	—
TOLERANCES UNLESS OTHERWISE SPECIFIED: ±0.2mm	CHK 11.04.84		
	M.SCHAARSCHMIDT		
0 PLC ± —	APVD —	TE Connectivity	
1 PLC ± —	PRODUCT SPEC	NAME	
2 PLC ± —	108-18012	AMP MODU II PIN HEADER, SINGLE ROW	
3 PLC ± —	APPLICATION SPEC	SIZE	CAGE CODE
4 PLC ± —	—	A4	00779
ANGLES ± —	WEIGHT	DRAWING NO	RESTRICTED TO
	—	C-825435	—
CUSTOMER DRAWING		SCALE 4:1	SHEET 1 OF 1
		REV F	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[825435-4](#)