



8

7

6

5

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT

By

ALL RIGHTS RESERVED.

REVISIONS

| P | LTR | DESCRIPTION | DATE | DWN | APVD |
|---|-----|-------------|------|-----|------|
| — | — | SEE SHEET 1 | — | — | — |

| | | | | | | | | | | | | | | |
|---------|------------|-------|-------|-------|-------|-------|------------|-------------|-------|-------|-------|-------|----|-------------|
| △ | 88 | 3.465 | 64.01 | 2.530 | 32.01 | 1.260 | 64.02 | 2.520 | 65.91 | 2.595 | 60.96 | 2.400 | 25 | 7—1375582—4 |
| △ | 88 | 3.465 | 61.47 | 2.420 | 30.74 | 1.210 | 61.48 | 2.420 | 63.37 | 2.495 | 58.42 | 2.300 | 24 | 7—1375582—3 |
| △ | 88 | 3.465 | 58.93 | 2.320 | 29.47 | 1.160 | 58.94 | 2.320 | 60.83 | 2.395 | 55.88 | 2.200 | 23 | 7—1375582—2 |
| △ | 88 | 3.465 | 56.39 | 2.220 | 28.20 | 1.110 | 56.40 | 2.220 | 58.29 | 2.295 | 53.34 | 2.100 | 22 | 7—1375582—1 |
| △ | 88 | 3.465 | 53.85 | 2.120 | 26.93 | 1.060 | 53.86 | 2.120 | 55.75 | 2.195 | 50.80 | 2.000 | 21 | 7—1375582—0 |
| △ | 72 | 2.835 | 51.31 | 2.020 | 25.66 | 1.010 | 51.32 | 2.020 | 53.21 | 2.095 | 48.26 | 1.900 | 20 | 6—1375582—9 |
| △ | 72 | 2.835 | 48.77 | 1.920 | 24.39 | .960 | 48.78 | 1.920 | 50.67 | 1.995 | 45.72 | 1.800 | 19 | 6—1375582—8 |
| △ | 72 | 2.835 | 46.23 | 1.820 | 23.12 | .910 | 46.24 | 1.820 | 48.13 | 1.895 | 43.18 | 1.700 | 18 | 6—1375582—7 |
| △ | 72 | 2.835 | 43.69 | 1.720 | 21.85 | .860 | 43.70 | 1.720 | 45.59 | 1.795 | 40.64 | 1.600 | 17 | 6—1375582—6 |
| △ | 72 | 2.835 | 41.15 | 1.620 | 20.58 | .810 | 41.16 | 1.620 | 43.05 | 1.695 | 38.10 | 1.500 | 16 | 6—1375582—5 |
| △ | 56 | 2.205 | 38.61 | 1.520 | 19.31 | .760 | 38.62 | 1.520 | 40.51 | 1.595 | 35.56 | 1.400 | 15 | 6—1375582—4 |
| △ | 56 | 2.205 | 36.07 | 1.420 | 18.04 | .710 | 36.08 | 1.420 | 37.97 | 1.495 | 33.02 | 1.300 | 14 | 6—1375582—3 |
| △ | 56 | 2.205 | 33.53 | 1.320 | 16.77 | .660 | 33.54 | 1.320 | 35.43 | 1.395 | 30.48 | 1.200 | 13 | 6—1375582—2 |
| △ | 56 | 2.205 | 30.99 | 1.220 | 15.50 | .610 | 31.00 | 1.220 | 32.89 | 1.295 | 27.94 | 1.100 | 12 | 6—1375582—1 |
| △ | 56 | 2.205 | 28.45 | 1.120 | 14.23 | .560 | 28.46 | 1.120 | 30.35 | 1.195 | 25.40 | 1.000 | 11 | 6—1375582—0 |
| △ | 56 | 2.205 | 25.91 | 1.020 | 12.96 | .510 | 25.92 | 1.020 | 27.81 | 1.095 | 22.86 | .900 | 10 | 5—1375582—9 |
| △ | 44 | 1.732 | 23.37 | .920 | 11.69 | .460 | 23.38 | .920 | 25.27 | .995 | 20.32 | .800 | 9 | 5—1375582—8 |
| △ | 44 | 1.732 | 20.83 | .820 | 10.42 | .410 | 20.84 | .820 | 22.73 | .895 | 17.78 | .700 | 8 | 5—1375582—7 |
| △ | 44 | 1.732 | 18.29 | .720 | 9.15 | .360 | 18.30 | .720 | 20.19 | .795 | 15.24 | .600 | 7 | 5—1375582—6 |
| △ | 32 | 1.260 | 15.75 | .620 | 7.88 | .310 | 15.76 | .620 | 17.65 | .695 | 12.70 | .500 | 6 | 5—1375582—5 |
| △ | 32 | 1.260 | 13.21 | .520 | 6.61 | .260 | 13.22 | .520 | 15.11 | .595 | 10.16 | .400 | 5 | 5—1375582—4 |
| △ | 32 | 1.260 | 10.67 | .420 | 5.34 | .210 | 10.68 | .420 | 12.57 | .495 | 7.62 | .300 | 4 | 5—1375582—3 |
| △ | 32 | 1.260 | 8.13 | .320 | 4.07 | .160 | 8.14 | .320 | 10.03 | .395 | 5.08 | .200 | 3 | 5—1375582—2 |
| △ | 24 | .945 | 5.59 | .220 | 2.80 | .110 | 5.60 | .220 | 7.49 | .295 | 2.54 | .100 | 2 | 5—1375582—1 |
| △ | 88 | 3.465 | 64.01 | 2.530 | 32.01 | 1.260 | 64.02 | 2.520 | 65.91 | 2.595 | 60.96 | 2.400 | 25 | 2—1375582—4 |
| △ | 88 | 3.465 | 61.47 | 2.420 | 30.74 | 1.210 | 61.48 | 2.420 | 63.37 | 2.495 | 58.42 | 2.300 | 24 | 2—1375582—3 |
| △ | 88 | 3.465 | 58.93 | 2.320 | 29.47 | 1.160 | 58.94 | 2.320 | 60.83 | 2.395 | 55.88 | 2.200 | 23 | 2—1375582—2 |
| △ | 88 | 3.465 | 56.39 | 2.220 | 28.20 | 1.110 | 56.40 | 2.220 | 58.29 | 2.295 | 53.34 | 2.100 | 22 | 2—1375582—1 |
| △ | 88 | 3.465 | 53.85 | 2.120 | 26.93 | 1.060 | 53.86 | 2.120 | 55.75 | 2.195 | 50.80 | 2.000 | 21 | 2—1375582—0 |
| △ | 72 | 2.835 | 51.31 | 2.020 | 25.66 | 1.010 | 51.32 | 2.020 | 53.21 | 2.095 | 48.26 | 1.900 | 20 | 1—1375582—9 |
| △ | 72 | 2.835 | 48.77 | 1.920 | 24.39 | .960 | 48.78 | 1.920 | 50.67 | 1.995 | 45.72 | 1.800 | 19 | 1—1375582—8 |
| △ | 72 | 2.835 | 46.23 | 1.820 | 23.12 | .910 | 46.24 | 1.820 | 48.13 | 1.895 | 43.18 | 1.700 | 18 | 1—1375582—7 |
| △ | 72 | 2.835 | 43.69 | 1.720 | 21.85 | .860 | 43.70 | 1.720 | 45.59 | 1.795 | 40.64 | 1.600 | 17 | 1—1375582—6 |
| △ | 72 | 2.835 | 41.15 | 1.620 | 20.58 | .810 | 41.16 | 1.620 | 43.05 | 1.695 | 38.10 | 1.500 | 16 | 1—1375582—5 |
| △ | 56 | 2.205 | 38.61 | 1.520 | 19.31 | .760 | 38.62 | 1.520 | 40.51 | 1.595 | 35.56 | 1.400 | 15 | 1—1375582—4 |
| △ | 56 | 2.205 | 36.07 | 1.420 | 18.04 | .710 | 36.08 | 1.420 | 37.97 | 1.495 | 33.02 | 1.300 | 14 | 1—1375582—3 |
| △ | 56 | 2.205 | 33.53 | 1.320 | 16.77 | .660 | 33.54 | 1.320 | 35.43 | 1.395 | 30.48 | 1.200 | 13 | 1—1375582—2 |
| △ | 56 | 2.205 | 30.99 | 1.220 | 15.50 | .610 | 31.00 | 1.220 | 32.89 | 1.295 | 27.94 | 1.100 | 12 | 1—1375582—1 |
| △ | 56 | 2.205 | 28.45 | 1.120 | 14.23 | .560 | 28.46 | 1.120 | 30.35 | 1.195 | 25.40 | 1.000 | 11 | 1—1375582—0 |
| △ | 56 | 2.205 | 25.91 | 1.020 | 12.96 | .510 | 25.92 | 1.020 | 27.81 | 1.095 | 22.86 | .900 | 10 | 1375582—9 |
| △ | 44 | 1.732 | 23.37 | .920 | 11.69 | .460 | 23.38 | .920 | 25.27 | .995 | 20.32 | .800 | 9 | 1375582—8 |
| △ | 44 | 1.732 | 20.83 | .820 | 10.42 | .410 | 20.84 | .820 | 22.73 | .895 | 17.78 | .700 | 8 | 1375582—7 |
| △ | 44 | 1.732 | 18.29 | .720 | 9.15 | .360 | 18.30 | .720 | 20.19 | .795 | 15.24 | .600 | 7 | 1375582—6 |
| △ | 32 | 1.260 | 15.75 | .620 | 7.88 | .310 | 15.76 | .620 | 17.65 | .695 | 12.70 | .500 | 6 | 1375582—5 |
| △ | 32 | 1.260 | 13.21 | .520 | 6.61 | .260 | 13.22 | .520 | 15.11 | .595 | 10.16 | .400 | 5 | 1375582—4 |
| △ | 32 | 1.260 | 10.67 | .420 | 5.34 | .210 | 10.68 | .420 | 12.57 | .495 | 7.62 | .300 | 4 | 1375582—3 |
| △ | 32 | 1.260 | 8.13 | .320 | 4.07 | .160 | 8.14 | .320 | 10.03 | .395 | 5.08 | .200 | 3 | 1375582—2 |
| △ | 24 | .945 | 5.59 | .220 | 2.80 | .110 | 5.60 | .220 | 7.49 | .295 | 2.54 | .100 | 2 | 1375582—1 |
| PLATING | TAPE WIDTH | H | D | C | B | A | NO OF POSN | PART NUMBER | | | | | | |

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm [INCHES]

0 PLC
1 PLC
2 PLC
3 PLC
4 PLC

± —
± —
± 0.13 [.005]
± —
± —

ANGLES

FINISH

△

2

SEE TABLE

DWN
J. MOSER
26OCT99

CWK
L. BRESKOSKY
26OCT99

APVD
K. WRIGHT
27JUN00

NAME

PRODUCT SPEC
108—25034—2

APPLICATION SPEC
114—25026

WEIGHT
—

SIZE
A1

CAGE CODE
00779

DRAWING NO
1375582

RESTRICTED TO
—

CUSTOMER DRAWING

SCALE
8:1

SHEET
2

OF
2

REV
F

TE Connectivity

AMPMODU MTE SURFACE MOUNT.
VERTICAL HEADER ASSEMBLY

4805 (1/15)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[6-1375582-7](#)