

CLASS 2 TRANSFORMER

FS10-1200-C2

Description:

The FS10-1200-C2 is a series/parallel primary and dual secondary, split bobbin design which operates with either a parallel input of 115V or a series input of 230V. The secondaries are 5V @ 1.2A each. They can be used independently (up to 300V difference between them) or in series for double the voltage or in parallel for double the current. The split bobbin design eliminates the need for costly electrostatic shielding.

Electrical Specifications (@25C)

- 1. Maximum Power: 12.0VA
- 2. Primary: Series: 230V; Parallel: 115V
- 3. Secondaries: 5.0V @ 1.2A each
- 4. Voltage Regulation: 25% TYP @ full load to no load
- 5. Operating Temperature: -40C to 80C
- 6. Storage Temperature: -55C to 150C
- 7. Hipot tested 100% at 4200 VRMS pri to sec
- 8. Hipot tested 100% at 2160 VRMS sec to sec
- 9. Recommended fuse (fuse on primary): For 115V Cooper/Bussman, Type MDL, rated 500mA, 250V. For 230V Littlefuse, Type 313, rated 250mA, 250V

Construction:

Three flange bobbin construction with primaries and secondaries wound side by side for low capacitive coupling. UL Class F Insulation System (155°C).


Agency File:

UL: File E65390, UL 5085-1 & 3 (1585), Class 2 Transformer cUL: File E65390, UL 5085-1 & 3 (1585) For Canadian Use (CSA 22.2, No.66.3-06) TUV Certificate No.: R72120839, EN61558, Safety Isolating xfmr, general use



Max Dimensions: Units in inches.								
Н	W	L	А	В	С	D	E	F
1.516	1.614	1.929	0.315	0.416	1.429	0.041	0.020	0.236
Weight: 0.70 lbs								

Schematic:



RoHS Compliance: As of manufacturing date February 2005, all standard products meet the requirements of 2011/65/EU, known as the RoHS initiative.


Note: Order and shipping documentation may have a "-B" suffix; this indicates Bulk packaging but does not show on the actual part number marked on the transformer.


*Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics website for the most current version. For soldering and washing information please see http://www.triadmagnetics.com/faq.html


www.TriadMagnetics.com Phone: (951) 277-0757 Fax: (951) 277-2757

460 Harley Knox Blvd. Perris, CA 92571









Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Triad Magnetics: FS10-1200-C2