




4

3

2

1

D

C

B

A

PART NO.	GRID	"F" NO. OF SPACES	"H" NO. OF CONTACTS	DIM G	DIM J	DIM K	DIM L	DIM M	DIM N	DIM P	LOAD
1921125-1	21 X 21	20	441	10,000 [.3937]	6,900 [.2717]	14,900 [.5866]	12,40 [.488]	17,4 [.69]	10,550 [.4154]	6,550 [.2579]	24.3 ±6 LBS
1921125-2	22 X 22	21	484	10,500 [.4134]	7,400 [.2913]	15,400 [.6063]	12,90 [.508]	17,9 [.70]	10,300 [.4055]	6,300 [.2480]	26.7 ±7 LBS
1921125-3	23 X 23	22	529	11,000 [.4331]	7,900 [.3110]	15,900 [.6260]	13,40 [.528]	18,4 [.72]	10,050 [.3957]	6,050 [.2382]	29.2 ±7 LBS
1921125-4	24 X 24	23	576	11,500 [.4528]	8,400 [.3307]	16,400 [.6457]	13,90 [.547]	18,9 [.74]	9,800 [.3858]	5,800 [.2283]	31.7 ±8 LBS
1921125-5	25 X 25	24	625	12,000 [.4724]	8,900 [.3504]	16,900 [.6654]	14,40 [.567]	19,4 [.76]	9,550 [.3760]	5,550 [.2185]	34.5 ±9 LBS
1921125-6	26 X 26	25	676	12,500 [.4921]	9,400 [.3701]	17,400 [.6850]	14,90 [.587]	19,9 [.78]	9,300 [.3661]	5,300 [.2087]	37.3 ±9 LBS
1921125-7	27 X 27	26	729	13,000 [.5118]	9,900 [.3898]	17,900 [.7047]	15,40 [.608]	20,4 [.80]	9,050 [.3563]	5,050 [.1988]	40.2 ±10 LBS
1921125-8	28 X 28	27	784	13,500 [.5315]	10,400 [.4094]	18,400 [.7244]	15,90 [.626]	20,9 [.82]	8,800 [.3465]	4,800 [.1890]	43.2 ±11 LBS
1921125-9	29 X 29	28	841	14,000 [.5512]	10,900 [.4291]	18,900 [.7441]	16,40 [.646]	21,4 [.84]	8,550 [.3366]	4,550 [.1791]	46.4 ±11 LBS
1-1921125-0	30 X 30	29	900	14,500 [.5709]	11,400 [.4488]	19,400 [.7638]	16,90 [.665]	21,9 [.86]	8,300 [.3268]	4,300 [.1693]	49.6 ±12 LBS
1-1921125-1	31 X 31	30	961	15,000 [.5906]	11,900 [.4685]	19,900 [.7835]	17,40 [.685]	22,4 [.88]	8,050 [.3169]	4,050 [.1594]	53.0 ±13 LBS
1-1921125-2	32 X 32	31	1024	15,500 [.6102]	12,400 [.4882]	20,400 [.8032]	17,90 [.705]	22,9 [.90]	7,800 [.3071]	3,800 [.1496]	56.4 ±14 LBS
1-1921125-3	33 X 33	32	1089	16,000 [.6299]	12,900 [.5079]	20,900 [.8228]	18,40 [.724]	23,4 [.92]	7,550 [.2972]	3,550 [.1398]	60 ±15 LBS
1-1921125-4	34 X 34	33	1156	16,500 [.6496]	13,400 [.5276]	21,400 [.8425]	18,90 [.744]	23,9 [.94]	7,300 [.2874]	3,300 [.1299]	63.7 ±16 LBS
1-1921125-5	35 X 35	34	1225	17,000 [.6693]	13,900 [.5472]	21,900 [.8622]	19,40 [.764]	24,4 [.96]	7,050 [.2776]	3,050 [.1201]	67.5 ±17 LBS
1-1921125-6	36 X 36	35	1296	17,500 [.6890]	14,400 [.5669]	22,400 [.8819]	19,90 [.783]	24,9 [.98]	6,800 [.2677]	2,800 [.1102]	71.4 ±18 LBS
1-1921125-7	37 X 37	36	1369	18,000 [.7087]	14,900 [.5866]	22,900 [.9016]	20,40 [.803]	25,4 [1.00]	6,550 [.2579]	2,550 [.1004]	75.5 ±19 LBS
1-1921125-8	38 X 38	37	1444	18,500 [.7283]	15,400 [.6063]	23,400 [.9213]	20,90 [.823]	25,9 [1.02]	6,300 [.2480]	2,300 [.0906]	79.6 ±20 LBS
1-1921125-9	39 X 39	38	1521	19,000 [.7480]	15,900 [.6260]	23,900 [.9409]	21,40 [.843]	26,4 [1.04]	6,050 [.2382]	2,050 [.0807]	83.8 ±21 LBS
2-1921125-0	40 X 40	39	1600	19,500 [.7677]	16,400 [.6457]	24,400 [.9606]	21,90 [.862]	26,9 [1.06]	5,800 [.2283]	1,800 [.0709]	88.2 ±22 LBS

REVISION INFO
PRELIMINARY
SEE SHEET 1

REV.

DO NOT SCALE

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE:
X,X ± .25
X,XX ± .13
X,XXX ± .051
ANGLES ± 5°

Tyco Electronics

North Attleboro, Massachusetts 02760

DRAWN BY:
L. SILVA

ENGINEER:
B. SHARP

FILENAME
C-1921125

DATE:
2-24-06

DATE:
3-13-06

PROJECT
PRO-E

MATERIAL:
N/A

FINISH:
N/A

CONFIDENTIAL PROPERTY OF TYCO ELECTRONICS. NOT TO BE DISCLOSED TO OTHERS. REPRODUCED OR USED FOR ANY PURPOSES EXCEPT AS AUTHORIZED IN WRITING BY AN AUTHORIZED OFFICIAL OF TYCO ELECTRONICS. MUST BE RETURNED TO TYCO ELECTRONICS ON DEMAND, ON COMPLETION OF ORDERS OR OTHER PURPOSES FOR WHICH LOANED.

DIMENSIONS ARE IN:
MILLIMETERS

THIRD ANGLE PROJECTION

SCALE:
4:1
SIZE
C

TE PART NO.:
SEE TABLE

DWG. NO.:
C-1921125

TITLE:
CUSTOMER DRAWING,
SOCKET ASSEMBLY
,5mm BGA, MATRIX

SHEET
2 of 2
REV.
4

4

3

2

1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-1921125-4](#)