| SPECIFICATION CONTROL DRAWING | | | | | SCD 55/0832 | |
|--|--|---|--|--|--|--|
| Title THREE CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, OUTER SPACE, 600 VOLT | | | | | Date 1-13-17 | Revision B |
| This specification sheet forms a part of the latest issue of Raychem Specification | | | | | | Б |
| COM | IPONENT WIRES - 55/0812 | | | | | |
| | Γ | CABLE CONST | | |] | |
| CABLE CONSTRUCTION DETAILS | | | | | | |
| | PART NUMBER <u>1</u> / | R CONDUCTOR OUTSIDE DIAMETER SIZE (inch) | | | MAXIMUM WEIGHT (lbs/1000 ft.) | |
| | | (AWC) | NOMINAL | MAXIMUM | (103/100011.) | |
| | 55/0832-26-* | 26 | .086 | .091 | 5.2 | |
| | 55/0832-24-* | 24 | .097 | .102 | 7.0 | |
| | 55/0832-22-* | 22 | .108 | .112 | 9.8 | |
| | 55/0832-20-* | 20 | .125 | .130 | 14.4 | |
| | 55/0832-18-* | 18 | .151 | .158 | 22.0 | |
| | 55/0832-16-* | 16 | .166 | .173 | 27.5 | |
| | 55/0832-14-* 55/0832-12-* | 14 12 | .203 | .210 .246 | 42.2 62.7 | |
| | CABL TEMPERATURE RATING: 200°C Maximum continuous conductor temp. VOLTAGE RATING: 600 volts (rms) at s DIELECTRIC WITHSTAND: 1500 volts NSULATION FLAWS: Spark Test, 3.0 kV (rms) Impulse Dielectric Test, 8.0 kV (peak) | sea level (rms), 60 Hz | 1/ PART I The by cc com nece Exar | NUMBER: "*" in the part n olor code design ponent wire col ssarily reflect t nple: AWG 22 wires: 5 | numbers above sha nators with a slash ors. Colors shown he sequence of ma | n separating the n do not |
| - | Users should evaluate the suitabili to make c | hanges in materials or p | rocessing, which | do not affect comp | liance with any specific | cation, without notification to Buyer. |
| 1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902" MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER. | | | | | | |
| | Raychem, TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks. | | | | | Raychem Wire & Cable 501 Oakside Avenue |
| Page 1 of 1 | DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL Redwood City, CA 94063-3 THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. Phone: 1-800-522-6752 REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID. Formation of the state of | | | | | |
| | | | | | © 2008-2017 Tyco E | Electronics Corporation. All rights reserved |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

55/0832-26-9/93/96 55/0832-22-9/93/96 55/0832-24-0/2/9 55/0832-24-0/4/9