

D

C

B

A

D

C

B

A




FIG. 1




FIG. 2







FIG. 3



P.C.B. HOLE LAYOUT
TOLERANCE ±.003

- INSULATOR MATERIAL – THERMOPLASTIC POLYESTER, PCT, BLACK, UL94 V-0
- MACHINED CONTACT – BECU, PLATED WITH 80–200μ” TIN (LEAD FREE) OVER 75–100μ” COPPER.
- SLEEVE – COPPER, PLATED WITH 180–340μ” THK TIN (LEAD FREE) OVER 75–125 MIN NICKEL.
- MACHINED CONTACT – BECU, PLATED WITH 25μ” MIN. GOLD OVER 30–100μ” NICKEL.
- ELECTRICAL:**
CONTACT RESISTANCE: 10 MILLIOHMS MAX
CONTACT RATING: 3 AMPS
CAPACITANCE: 1.0 pF PER MIL–STD–202, METHOD 305
INSULATION RESISTANCE: 5000 OHMS MIN @ 500 VDC PER MIL–STD–1344, METHOD 3003.1
DIELECTRIC WITHSTANDING VOLTAGE: 1000 VOLTS (RMS) PER MIL–STD–1344, METHOD 3001.1
- MECHANICAL:**
INSERTION FORCE: 134 GRAMS AVG
WITHDRAWAL FORCE: 63 GRAMS AVG
"ACCEPTS IC PIN – .009"X.015" THROUGH .011"X.020", OR .016" TO .021" DIAMETER, .150/.105 LONG"
- ENVIRONMENTAL:**
OPERATING TEMPERATURE: –55°C TO –105°C
- OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

8		7		6		5		4		3		2		1	
THIS DRAWING IS UNPUBLISHED.				RELEASED FOR PUBLICATION				-				-			
COPYRIGHT - By -				ALL RIGHTS RESERVED.											

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2-1571586-5](#)