

SMQ Series

- Downsized from current standard SMG series
- Endurance : 2,000 hours at 85°C
- Non solvent resistant type
- RoHS Compliant

SMQ

↑ Downsized
SMG





◆ SPECIFICATIONS

| Items | Characteristics | | | | | | | | | | | | | | |
|---|--|--|------|------|------|------|------|--------------------------------------|------|-------------|------------------------------|----------------------------|---------------------------|------|---|
| Category Temperature Range | -40 to +85°C(6.3 to 400V _{dc}) -25 to +85°C(450V _{dc}) | | | | | | | | | | | | | | |
| Rated Voltage Range | 6.3 to 450V _{dc} | | | | | | | | | | | | | | |
| Capacitance Tolerance | ±20% (M) (at 20°C, 120Hz) | | | | | | | | | | | | | | |
| Leakage Current | 6.3 to 100V _{dc} | | | | | | | | | | | | 160 to 450V _{dc} | | |
| | ≤φ18 | I=0.03CV or 4μA, whichever is greater. | | | | | | | | | | | CV \ Time After 1 minute | | |
| | | | | | | | | | | | | CV ≤ 1,000 I=0.1CV+40 max. | (at 20°C) | | |
| | | | | | | | | | | | CV > 1,000 I=0.04CV+100 max. | | | | |
| ≥φ20 | I=0.03CV (at 20C after 1 minute) | | | | | | | | | | | (at 20°C after 3 minutes) | | | |
| Where, I : Max. leakage current (μA), C : Nominal capacitance (μF), V : Rated voltage (V) | | | | | | | | | | | | | | | |
| Dissipation Factor (tanδ) | Rated voltage (V _{dc}) | 6.3V | 10V | 16V | 25V | 35V | 50V | 63V | 100V | 160 to 250V | 315 to 400V | 450V | | | |
| | tanδ (Max.) | 0.28 | 0.24 | 0.20 | 0.16 | 0.14 | 0.12 | 0.09 | 0.08 | 0.20 | 0.24 | 0.24 | | | |
| When nominal capacitance exceeds 1,000μF, add 0.02 to the value above for each 1,000μF increase. (at 20°C, 120Hz) | | | | | | | | | | | | | | | |
| Low Temperature Characteristics (Max. Impedance Ratio) | Rated voltage (V _{dc}) | 6.3V | 10V | 16V | 25V | 35V | 50V | 63V | 100V | 160 to 200V | 250V | 350V | 400V | 450V | |
| | Z(-25°C)/Z(+20°C) | ≤φ8 | 5 | 4 | 3 | 2 | 2 | 2 | 2 | 2 | 3 | 3 | 4 | 4 | 6 |
| | | ≥φ10 | 5 | 4 | 3 | 2 | 2 | 2 | 2 | 2 | 3 | 3 | 4 | 4 | 6 |
| | Z(-40°C)/Z(+20°C) | ≤φ8 | 12 | 10 | 8 | 5 | 4 | 3 | 3 | 3 | 8 | 10 | 8 | 8 | — |
| | ≥φ10 | 12 | 10 | 8 | 5 | 4 | 3 | 3 | 3 | 4 | 4 | 6 | 6 | — | |
| (at 120Hz) | | | | | | | | | | | | | | | |
| Endurance | The following specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage is applied for 2,000 hours at 85°C. | | | | | | | | | | | | | | |
| | Capacitance change | ≤±20% of the initial value | | | | | | | | | | | | | |
| | D.F. (tanδ) | ≤200% of the initial specified value | | | | | | | | | | | | | |
| | Leakage current | ≤The initial specified value | | | | | | | | | | | | | |
| Shelf Life | The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours at 85°C without voltage applied. Before the measurement, the capacitor shall be preconditioned by applying voltage according to Item 4.1 of JIS C 5101-4. | | | | | | | | | | | | | | |
| | Rated voltage | 6.3 to 100V _{dc} | | | | | | 160 to 450V _{dc} | | | | | | | |
| | Capacitance change | ≤±20% of the initial value | | | | | | ≤±20% of the initial value | | | | | | | |
| | D.F. (tanδ) | ≤200% of the initial specified value | | | | | | ≤200% of the initial specified value | | | | | | | |
| | Leakage current | ≤The initial specified value | | | | | | ≤500% of the initial specified value | | | | | | | |


◆ DIMENSIONS [mm]

● Terminal Code : E



| | | | | | | | | | |
|-----|------------|-----|-----|-----|------|-----|-----|------------|------|
| φD | 5 | 6.3 | 8 | 10 | 12.5 | 16 | 18 | 20 | 22 |
| φd | 0.5 | 0.5 | 0.6 | 0.6 | 0.6 | 0.8 | 0.8 | 1.0 | 1.0 |
| F | 2.0 | 2.5 | 3.5 | 5.0 | 5.0 | 7.5 | 7.5 | 10.0 | 10.0 |
| φD' | φD+0.5max. | | | | | | | φD+0.5max. | |
| L' | L+1.5max. | | | | | | | L+2.0max. | |

◆ PART NUMBERING SYSTEM



Supplement code
Size code
Capacitance tolerance code
Capacitance code (ex. 1.0μF:1R0, 10μF:100, 100μF:101)
Lead forming-taping code
Terminal code
Voltage code (ex. 6.3V:6R3, 50V:500, 100V:101)
Series code
Category

Please refer to "Product code guide (radial lead type)"

◆STANDARD RATINGS

| WV (Vdc) | Cap (μF) | Case size φD×L(mm) | tanδ | Rated ripple current (mArms/85°C,120Hz) | Part No. | WV (Vdc) | Cap (μF) | Case size φD×L(mm) | tanδ | Rated ripple current (mArms/85°C,120Hz) | Part No. | |
|----------|----------|--------------------|-------|---|--------------------|--------------------|----------|--------------------|--------------------|---|---------------------|--------------------|
| 6.3 | 1,000 | 8×11.5 | 0.28 | 540 | ESMQ6R3E□□102MHB5D | 50 | 330 | 10×16 | 0.12 | 590 | ESMQ500E□□331MJ16S | |
| | 2,200 | 10×16 | 0.30 | 890 | ESMQ6R3E□□222MJ16S | | 470 | 10×20 | 0.12 | 760 | ESMQ500E□□471MJ20S | |
| | 3,300 | 10×20 | 0.32 | 1,190 | ESMQ6R3E□□332MJ20S | | 1,000 | 12.5×25 | 0.12 | 1,350 | ESMQ500E□□102MK25S | |
| | 4,700 | 12.5×20 | 0.34 | 1,550 | ESMQ6R3E□□472MK20S | | 2,200 | 16×31.5 | 0.14 | 1,980 | ESMQ500E□□222MLN3S | |
| | 6,800 | 12.5×25 | 0.38 | 1,920 | ESMQ6R3E□□682MK25S | | 3,300 | 18×35.5 | 0.16 | 2,500 | ESMQ500E□□332MMP1S | |
| | 10,000 | 16×25 | 0.46 | 2,350 | ESMQ6R3E□□103ML25S | | 4,700 | 20×40 | 0.18 | 2,900 | ESMQ500E□□472MNP40S | |
| | 15,000 | 16×31.5 | 0.56 | 2,550 | ESMQ6R3E□□153MLN3S | | 6,800 | 22×50 | 0.22 | 3,500 | ESMQ500E□□682MP50S | |
| | 22,000 | 18×35.5 | 0.70 | 3,200 | ESMQ6R3E□□223MMP1S | | 63 | 22 | 5×11 | 0.09 | 100 | ESMQ630E□□220ME11D |
| | 33,000 | 20×40 | 0.92 | 3,500 | ESMQ6R3E□□333MM40S | | | 33 | 6.3×11 | 0.09 | 140 | ESMQ630E□□330MF11D |
| | 47,000 | 22×50 | 1.20 | 3,900 | ESMQ6R3E□□473MP50S | | | 47 | 6.3×11 | 0.09 | 170 | ESMQ630E□□470MF11D |
| 10 | 220 | 5×11 | 0.24 | 240 | ESMQ100E□□221ME11D | 68 | | 8×11.5 | 0.09 | 220 | ESMQ630E□□680MHB5D | |
| | 330 | 6.3×11 | 0.24 | 290 | ESMQ100E□□331MF11D | 100 | | 8×11.5 | 0.09 | 280 | ESMQ630E□□101MHB5D | |
| | 470 | 6.3×11 | 0.24 | 350 | ESMQ100E□□471MF11D | 220 | | 10×16 | 0.09 | 490 | ESMQ630E□□221MJ16S | |
| | 1,000 | 10×12.5 | 0.24 | 650 | ESMQ100E□□102MJC5S | 330 | | 10×20 | 0.09 | 710 | ESMQ630E□□331MJ20S | |
| | 2,200 | 10×16 | 0.26 | 990 | ESMQ100E□□103ML16S | 470 | | 12.5×20 | 0.09 | 900 | ESMQ630E□□471MK20S | |
| | 3,300 | 12.5×20 | 0.28 | 1,450 | ESMQ100E□□332MK20S | 1,000 | | 16×25 | 0.09 | 1,300 | ESMQ630E□□102ML25S | |
| | 4,700 | 12.5×25 | 0.30 | 1,800 | ESMQ100E□□472MK25S | 2,200 | | 18×35.5 | 0.11 | 2,300 | ESMQ630E□□222MMP1S | |
| | 6,800 | 16×25 | 0.34 | 2,250 | ESMQ100E□□682ML25S | 3,300 | 20×40 | 0.13 | 2,700 | ESMQ630E□□332MNP40S | | |
| | 10,000 | 16×31.5 | 0.42 | 2,550 | ESMQ100E□□103MLN3S | 4,700 | 22×50 | 0.15 | 3,400 | ESMQ630E□□472MP50S | | |
| | 15,000 | 16×35.5 | 0.52 | 2,880 | ESMQ100E□□153MLP1S | 100 | 1.0 | 5×11 | 0.08 | 21 | ESMQ101E□□1R0ME11D | |
| 22,000 | 18×40 | 0.66 | 3,400 | ESMQ100E□□223MM40S | 2.2 | | 5×11 | 0.08 | 30 | ESMQ101E□□2R2ME11D | | |
| 33,000 | 22×50 | 0.88 | 4,500 | ESMQ100E□□333MP50S | 3.3 | | 5×11 | 0.08 | 40 | ESMQ101E□□3R3ME11D | | |
| 16 | 220 | 6.3×11 | 0.20 | 260 | ESMQ160E□□221MF11D | | 4.7 | 5×11 | 0.08 | 45 | ESMQ101E□□4R7ME11D | |
| | 330 | 6.3×11 | 0.20 | 320 | ESMQ160E□□331MF11D | | 10 | 5×11 | 0.08 | 70 | ESMQ101E□□100ME11D | |
| | 470 | 8×11.5 | 0.20 | 440 | ESMQ160E□□471MHB5D | | 22 | 6.3×11 | 0.08 | 130 | ESMQ101E□□220MF11D | |
| | 1,000 | 10×12.5 | 0.20 | 700 | ESMQ160E□□102MJC5S | | 33 | 8×11.5 | 0.08 | 180 | ESMQ101E□□330MHB5D | |
| | 2,200 | 10×20 | 0.22 | 1,000 | ESMQ160E□□222MJ20S | | 47 | 8×11.5 | 0.08 | 200 | ESMQ101E□□470MHB5D | |
| | 3,300 | 12.5×25 | 0.24 | 1,700 | ESMQ160E□□332MK25S | | 68 | 10×12.5 | 0.08 | 270 | ESMQ101E□□680MJC5S | |
| | 4,700 | 16×25 | 0.26 | 2,100 | ESMQ160E□□472ML25S | | 100 | 10×16 | 0.08 | 340 | ESMQ101E□□101MJ16S | |
| | 6,800 | 16×25 | 0.30 | 2,250 | ESMQ160E□□682ML25S | 220 | 12.5×20 | 0.08 | 550 | ESMQ101E□□221MK20S | | |
| | 10,000 | 16×35.5 | 0.38 | 2,710 | ESMQ160E□□103MLP1S | 330 | 12.5×25 | 0.08 | 760 | ESMQ101E□□331MK25S | | |
| | 15,000 | 18×40 | 0.48 | 3,100 | ESMQ160E□□153MM40S | 470 | 16×25 | 0.08 | 1,000 | ESMQ101E□□471ML25S | | |
| 22,000 | 22×40 | 0.62 | 3,800 | ESMQ160E□□223MP40S | 1,000 | 18×35.5 | 0.08 | 1,350 | ESMQ101E□□102MMP1S | | | |
| 2,200 | 22×50 | 0.10 | 2,400 | ESMQ101E□□222MP50S | 160 | 10 | 8×11.5 | 0.20 | 80 | ESMQ161E□□100MHB5D | | |
| 25 | 100 | 5×11 | 0.16 | 180 | | ESMQ250E□□101ME11D | 22 | 10×12.5 | 0.20 | 130 | ESMQ161E□□220MJC5S | |
| | 220 | 6.3×11 | 0.16 | 280 | | ESMQ250E□□221MF11D | 33 | 10×16 | 0.20 | 180 | ESMQ161E□□330MJ16S | |
| | 330 | 8×11.5 | 0.16 | 440 | | ESMQ250E□□331MHB5D | 47 | 10×20 | 0.20 | 210 | ESMQ161E□□470MJ20S | |
| | 470 | 10×12.5 | 0.16 | 550 | | ESMQ250E□□471MJC5S | 68 | 12.5×20 | 0.20 | 350 | ESMQ161E□□680MK20S | |
| | 1,000 | 10×16 | 0.16 | 860 | | ESMQ250E□□102MJ16S | 100 | 12.5×25 | 0.20 | 430 | ESMQ161E□□101MK25S | |
| | 2,200 | 12.5×25 | 0.18 | 1,550 | | ESMQ250E□□222MK25S | 220 | 16×31.5 | 0.20 | 760 | ESMQ161E□□221MLN3S | |
| | 3,300 | 16×25 | 0.20 | 1,980 | | ESMQ250E□□332ML25S | 330 | 18×35.5 | 0.20 | 995 | ESMQ161E□□331MMP1S | |
| | 4,700 | 16×25 | 0.22 | 2,200 | | ESMQ250E□□472ML25S | 470 | 18×40 | 0.20 | 1,200 | ESMQ161E□□471MM40S | |
| | 6,800 | 16×35.5 | 0.26 | 2,600 | | ESMQ250E□□682MLP1S | 200 | 1.0 | 6.3×11 | 0.20 | 22 | ESMQ201E□□1R0MF11D |
| | 10,000 | 18×40 | 0.34 | 2,800 | ESMQ250E□□103MM40S | 2.2 | | 6.3×11 | 0.20 | 33 | ESMQ201E□□2R2MF11D | |
| 15,000 | 22×50 | 0.44 | 3,800 | ESMQ250E□□153MP50S | 3.3 | 6.3×11 | | 0.20 | 40 | ESMQ201E□□3R3MF11D | | |
| 35 | 47 | 5×11 | 0.14 | 130 | ESMQ350E□□470ME11D | 4.7 | | 6.3×11 | 0.20 | 50 | ESMQ201E□□4R7MF11D | |
| | 68 | 6.3×11 | 0.14 | 160 | ESMQ350E□□680MF11D | 10 | | 8×11.5 | 0.20 | 80 | ESMQ201E□□100MHB5D | |
| | 100 | 6.3×11 | 0.14 | 210 | ESMQ350E□□101MF11D | 22 | | 10×16 | 0.20 | 150 | ESMQ201E□□220MJ16S | |
| | 220 | 8×11.5 | 0.14 | 385 | ESMQ350E□□221MHB5D | 33 | | 10×20 | 0.20 | 205 | ESMQ201E□□330MJ20S | |
| | 330 | 10×12.5 | 0.14 | 490 | ESMQ350E□□331MJC5S | 47 | | 12.5×20 | 0.20 | 270 | ESMQ201E□□470MK20S | |
| | 470 | 10×16 | 0.14 | 650 | ESMQ350E□□471MJ16S | 68 | | 12.5×25 | 0.20 | 350 | ESMQ201E□□680MK25S | |
| | 1,000 | 12.5×20 | 0.14 | 1,150 | ESMQ350E□□102MK20S | 100 | | 16×25 | 0.20 | 475 | ESMQ201E□□101ML25S | |
| | 2,200 | 16×25 | 0.16 | 1,800 | ESMQ350E□□222ML25S | 220 | 16×35.5 | 0.20 | 700 | ESMQ201E□□221MLP1S | | |
| | 3,300 | 16×31.5 | 0.18 | 2,100 | ESMQ350E□□332MLN3S | 330 | 18×40 | 0.20 | 950 | ESMQ201E□□331MM40S | | |
| | 4,700 | 16×35.5 | 0.20 | 2,500 | ESMQ350E□□472MLP1S | 250 | 3.3 | 6.3×11 | 0.20 | 40 | ESMQ251E□□3R3MF11D | |
| 6,800 | 18×40 | 0.24 | 2,800 | ESMQ350E□□682MM40S | 4.7 | | 6.3×11 | 0.20 | 50 | ESMQ251E□□4R7MF11D | | |
| 10,000 | 22×50 | 0.32 | 3,700 | ESMQ350E□□103MP50S | 10 | | 10×12.5 | 0.20 | 100 | ESMQ251E□□100MJC5S | | |
| 50 | 1.0 | 5×11 | 0.12 | 17 | ESMQ500E□□1R0ME11D | | 22 | 10×20 | 0.20 | 170 | ESMQ251E□□220MJ20S | |
| | 2.2 | 5×11 | 0.12 | 28 | ESMQ500E□□2R2ME11D | | 33 | 10×20 | 0.20 | 200 | ESMQ251E□□330MJ20S | |
| | 3.3 | 5×11 | 0.12 | 35 | ESMQ500E□□3R3ME11D | | 47 | 12.5×20 | 0.20 | 270 | ESMQ251E□□470MK20S | |
| | 4.7 | 5×11 | 0.12 | 41 | ESMQ500E□□4R7ME11D | | 68 | 16×25 | 0.20 | 380 | ESMQ251E□□680ML25S | |
| | 10 | 5×11 | 0.12 | 60 | ESMQ500E□□100ME11D | | 100 | 16×25 | 0.20 | 440 | ESMQ251E□□101ML25S | |
| | 22 | 5×11 | 0.12 | 95 | ESMQ500E□□220ME11D | | 220 | 18×35.5 | 0.20 | 680 | ESMQ251E□□221MMP1S | |
| | 33 | 5×11 | 0.12 | 125 | ESMQ500E□□330ME11D | | 350 | 2.2 | 6.3×11 | 0.24 | 30 | ESMQ351E□□2R2MF11D |
| | 47 | 6.3×11 | 0.12 | 155 | ESMQ500E□□470MF11D | 3.3 | | 8×11.5 | 0.24 | 46 | ESMQ351E□□3R3MHB5D | |
| | 68 | 6.3×11 | 0.12 | 210 | ESMQ500E□□680MF11D | 4.7 | | 8×11.5 | 0.24 | 55 | ESMQ351E□□4R7MHB5D | |
| | 100 | 8×11.5 | 0.12 | 260 | ESMQ500E□□101MHB5D | | | | | | | |
| 220 | 10×12.5 | 0.12 | 430 | ESMQ500E□□221MJC5S | | | | | | | | |

□□ : Enter the appropriate lead forming or taping code.

◆STANDARD RATINGS

| WV (Vdc) | Cap (μF) | Case size φD×L(mm) | tanδ | Rated ripple current (mA _{rms} /85°C,120Hz) | Part No. | WV (Vdc) | Cap (μF) | Case size φD×L(mm) | tanδ | Rated ripple current (mA _{rms} /85°C,120Hz) | Part No. |
|----------|----------|--------------------|------|--|--------------------|----------|----------|--------------------|------|--|--------------------|
| 350 | 10 | 10×12.5 | 0.24 | 90 | ESMQ351E□□100MJC5S | 450 | 2.2 | 8×11.5 | 0.24 | 28 | ESMQ451E□□2R2MHB5D |
| | 22 | 12.5×20 | 0.24 | 185 | ESMQ351E□□220MK20S | | 3.3 | 10×12.5 | 0.24 | 40 | ESMQ451E□□3R3MJC5S |
| | 33 | 12.5×25 | 0.24 | 240 | ESMQ351E□□330MK25S | | 4.7 | 10×12.5 | 0.24 | 46 | ESMQ451E□□4R7MJC5S |
| | 47 | 16×25 | 0.24 | 325 | ESMQ351E□□470ML25S | | 10 | 10×20 | 0.24 | 80 | ESMQ451E□□100MJ20S |
| | 68 | 16×25 | 0.24 | 400 | ESMQ351E□□680ML25S | | 22 | 12.5×25 | 0.24 | 140 | ESMQ451E□□220MK25S |
| | 100 | 18×31.5 | 0.24 | 530 | ESMQ351E□□101MMN3S | | 33 | 16×25 | 0.24 | 180 | ESMQ451E□□330ML25S |
| 400 | 1.0 | 6.3×11 | 0.24 | 22 | ESMQ401E□□1R0MF11D | | 47 | 16×31.5 | 0.24 | 220 | ESMQ451E□□470MLN3S |
| | 2.2 | 8×11.5 | 0.24 | 38 | ESMQ401E□□2R2MHB5D | | 68 | 18×35.5 | 0.24 | 260 | ESMQ451E□□680MMP1S |
| | 3.3 | 8×11.5 | 0.24 | 48 | ESMQ401E□□3R3MHB5D | | 100 | 18×40 | 0.24 | 280 | ESMQ451E□□101MM40S |
| | 4.7 | 10×12.5 | 0.24 | 60 | ESMQ401E□□4R7MJC5S | | | | | | |
| | 10 | 10×16 | 0.24 | 90 | ESMQ401E□□100MJ16S | | | | | | |
| | 22 | 12.5×25 | 0.24 | 205 | ESMQ401E□□220MK25S | | | | | | |
| | 33 | 16×25 | 0.24 | 275 | ESMQ401E□□330ML25S | | | | | | |
| | 47 | 16×25 | 0.24 | 280 | ESMQ401E□□470ML25S | | | | | | |
| | 68 | 16×31.5 | 0.24 | 340 | ESMQ401E□□680MLN3S | | | | | | |
| | 100 | 18×35.5 | 0.24 | 440 | ESMQ401E□□101MMP1S | | | | | | |

□□ : Enter the appropriate lead forming or taping code.

◆RATED RIPPLE CURRENT MULTIPLIERS

●Frequency Multipliers

(φ5 to φ18)

| Capacitance (μF) | Frequency (Hz) | 50 | 120 | 300 | 1k | 10k | 100k |
|------------------|----------------|------|------|------|------|------|------|
| 1.0 to 4.7 | | 0.65 | 1.00 | 1.35 | 1.75 | 2.30 | 2.50 |
| 10 to 68 | | 0.75 | 1.00 | 1.25 | 1.50 | 1.75 | 1.80 |
| 100 to 1,000 | | 0.80 | 1.00 | 1.15 | 1.30 | 1.40 | 1.50 |
| 2,200 to | | 0.85 | 1.00 | 1.03 | 1.05 | 1.08 | 1.08 |

(φ20 to φ22)

| Rated Voltage (V _{ra}) | Frequency (Hz) | 50 | 120 | 300 | 1k | 10k | 100k |
|----------------------------------|----------------|------|------|------|------|------|------|
| 6.3 to 50 | | 0.95 | 1.00 | 1.03 | 1.05 | 1.08 | 1.08 |
| 63 to 100 | | 0.92 | 1.00 | 1.07 | 1.13 | 1.19 | 1.20 |

The endurance of capacitors is reduced with internal heating produced by ripple current at the rate of halving the lifetime with every 5°C rise. When long life performance is required in actual use, the rms ripple current has to be reduced.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[United Chemi-Con \(UCC\):](#)

[ESMQ500ELL221MJC5S](#) [ESMQ201ELL100MHB5D](#) [ESMQ500ETD470MF11D](#) [ESMQ201ELL3R3MF11D](#)
[ESMQ630ELL101MHB5D](#) [ESMQ101ELL101MJ16S](#) [ESMQ500ELL101MHB5D](#) [ESMQ401ELL3R3MHB5D](#)
[ESMQ500EMC222MLN3S](#) [ESMQ250ELL682MLP1S](#) [ESMQ160ELL472ML25S](#) [ESMQ160ETC331MF11D](#)
[ESMQ101VSD502MA40S](#) [ESMQ500ELL100ME11D](#) [ESMQ250ELL102MJ16S](#) [ESMQ101ELL470MHB5D](#)
[ESMQ350ELL332MLN3S](#) [ESMQ500ELL222MLN3S](#) [ESMQ160EC3682ML25S](#) [ESMQ451ELL101MM40S](#)
[ESMQ351ELL470ML25S](#) [ESMQ201ELL101ML25S](#) [ESMQ350ELL103MP50S](#) [ESMQ101ELL100ME11D](#)
[ESMQ6R3ELL222MJ16S](#) [ESMQ630ELL330MF11D](#) [ESMQ251ELL221MMP1S](#) [ESMQ250ELL153MP50S](#)
[ESMQ100ELL102MJC5S](#) [ESMQ101ELL471ML25S](#) [ESMQ250ELL101ME11D](#) [ESMQ500ELL471MJ20S](#)
[ESMQ201ELL220MJ16S](#) [ESMQ630ELL471MK20S](#) [ESMQ160ELL222MJ20S](#) [ESMQ351ELL2R2MF11D](#)
[ESMQ100ELL103MLN3S](#) [ESMQ500ELL1R0ME11D](#) [ESMQ350ELL471MJ16S](#) [ESMQ401ELL101MMP1S](#)
[ESMQ250ELL471MJC5S](#) [ESMQ160ELL103MLP1S](#) [ESMQ401ELL4R7MJC5S](#) [ESMQ100ELL333MP50S](#)
[ESMQ500ELL331MJ16S](#) [ESMQ161ELL331MMP1S](#) [ESMQ250ELL472ML25S](#) [ESMQ101ELL331MK25S](#)
[ESMQ500ELL2R2ME11D](#) [ESMQ500ELL330ME11D](#) [ESMQ100ELL472MK25S](#) [ESMQ161ELL471MM40S](#)
[ESMQ251ELL330MJ20S](#) [ESMQ351ELL330MK25S](#) [ESMQ101ELL330MHB5D](#) [ESMQ6R3ELL102MHB5D](#)
[ESMQ451ELL330ML25S](#) [ESMQ161ELL470MJ20S](#) [ESMQ251ELL220MJ20S](#) [ESMQ100ELL471MF11D](#)
[ESMQ100ELL682ML25S](#) [ESMQ350ELL222ML25S](#) [ESMQ161ELL680MK20S](#) [ESMQ6R3ELL223MMP1S](#)
[ESMQ101ELL3R3ME11D](#) [ESMQ250ELL103MM40S](#) [ESMQ451ELL220MK25S](#) [ESMQ6R3ELL153MLN3S](#)
[ESMQ401ELL680MLN3S](#) [ESMQ500ELL472MN40S](#) [ESMQ160ELL223MP40S](#) [ESMQ350ELL101MF11D](#)
[ESMQ6R3ELL332MJ20S](#) [ESMQ100ELL223MM40S](#) [ESMQ101ELL680MJC5S](#) [ESMQ500ELL102MK25S](#)
[ESMQ161ELL330MJ16S](#) [ESMQ401ELL330ML25S](#) [ESMQ500ELL332MMP1S](#) [ESMQ160ELL471MHB5D](#)
[ESMQ6R3ELL103ML25S](#) [ESMQ251ELL3R3MF11D](#) [ESMQ351ELL100MJC5S](#) [ESMQ630ELL220ME11D](#)
[ESMQ201ELL331MM40S](#) [ESMQ161ELL220MJC5S](#) [ESMQ351ELL4R7MHB5D](#) [ESMQ451ELL100MJ20S](#)
[ESMQ500ELL682MP50S](#) [ESMQ351ELL101MMN3S](#) [ESMQ160ELL331MF11D](#) [ESMQ350ELL680MF11D](#)
[ESMQ630ELL332MN40S](#) [ESMQ101ELL102MMP1S](#) [ESMQ100ELL221ME11D](#) [ESMQ500ELL680MF11D](#)
[ESMQ630ELL222MMP1S](#) [ESMQ350ELL102MK20S](#) [ESMQ201ELL4R7MF11D](#) [ESMQ100ELL331MF11D](#)