


CONVERSION CHART			
INCH	MM	INCH	MM
.002	0.05	.590	14.99
.010	0.25	.600	15.24
.020	0.51	.620	15.75



SPECIFICATIONS:

MATERIALS:

CASE: THERMOPLASTIC 94V-0.
 FRAME: STEEL, TIN PLATED.
 ACTUATOR: COPPER ALLOY, NICKEL PLATED.
 MOVING CONTACT: COPPER ALLOY, GOLD OVER NICKEL PLATE.
 FIXED CONTACT/TERMINAL: COPPER ALLOY, TIN/LEAD PLATE.
 TERMINAL SEAL: OPTIONAL.

ELECTRICAL:

CONTACT RATING: 0.4 VA MAX. • 20 VDC OR PEAK AC.
 INITIAL CONTACT RESISTANCE: 20 MILLIOHMS MAX.
 INSULATION RESISTANCE: 1,000 MEGOHMS • 500 VDC MIN.
 DIELECTRIC STRENGTH: 1,000 VOLTS RMS • SEA LEVEL.
 LIFE EXPECTANCY: 80,000 CYCLES (2 POS.).
 80,000 CYCLES (3 POS.).

MECHANICAL:



ACTUATION TRAVEL: 26°.

ENVIRONMENTAL:

OPERATING TEMPERATURE: -22°F TO +185°F (-30°C TO +85°C).
 STORAGE TEMPERATURE: -67°F TO +185°F (-55°C TO +85°C).


NOTES:

- INTERPRET DRAWING PER ANSI Y14.5M-1982.
- MOUNTING HARDWARE SUPPLIED: (2) HEX NUTS AND (1) LOCKWASHER.



RECOMMENDED HOLE LAYOUT

TOLERANCE ±.002 UNLESS OTHERWISE NOTED



RECOMMENDED PANEL CUTOUT

TERMINALS CONNECTED WHEN TOGGLE IN POSITIONS SHOWN.			
SWITCH ACTION CODE (*)	FLAT	FLAT	FLAT
N	2 TO 3 5 TO 6 8 TO 9 11 TO 12	NONE	2 TO 1 5 TO 4 8 TO 7 11 TO 10
P	2 TO 3 5 TO 6 8 TO 9 11 TO 12	OFF	2 TO 1 5 TO 4 8 TO 7 11 TO 10
R	2 TO 3 5 TO 6 (MOM) 8 TO 9 11 TO 12	NONE	2 TO 1 5 TO 4 8 TO 7 11 TO 10
PA	2 TO 3 5 TO 6 8 TO 9 11 TO 12	2 TO 3 5 TO 6 8 TO 7 11 TO 10	2 TO 1 5 TO 4 8 TO 7 11 TO 10

NOTE:

DESIGNATION NUMBERS ARE FOR REFERENCE ONLY AND DO NOT APPEAR ON THE SWITCHES.


ACTUATOR NUMBER (X)	DIMENSION "X" ACTUATOR LENGTH	TOGGLE DESCRIPTION
1	.210	TAPPERED TOGGLE
2	.290	TAPPERED TOGGLE
3	.370	TAPPERED TOGGLE
4	.280	BALL END TOGGLE
5	.600	TAPPERED PADDLE
6	.590	ROUND TOGGLE
7	.485	FLAT PADDLE
8	.530	KNURLED TOGGLE
9	.415	TAPPERED TOGGLE

CUSTOMER DRAWING

SPECIFICATIONS ARE SUBJECT TO CHANGES WITHOUT NOTICE

AUGAT D/N 40309

REV	B
REVISIONS	OG3C-0194-05 MZ 28MAR07

		THIRD ANGLE PROJECTION		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES DO NOT SCALE PRINT		ORIGINAL DATE OF DRAWING: 10-2-96		TYCOELECTRONICS	
TOLERANCES (EXCEPT AS NOTED) ANGULAR = ± DECIMAL .XX = ± DECIMAL .XXX = ±.010 DECIMAL .XXXX = ±				PROJECT:		DRAWN: S.KIRCORIAN		DATE: 10-2-96	
		MATERIAL: SEE SPECIFICATIONS				CHECKED:		DATE:	
						APPROVED:		DATE:	
		FINISH:		COL. IDENT. NO.		DWG. SIZE		DWG. NO.	
		SEE SPECIFICATIONS		91506		C		7-1437562-0	
								REV. B	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[TT41NGRA9T1/4](#)