




<div> <div>OBSOLETE</div> <div>6</div> </div>	3.984	3.900	39	40	2-104345-7
	3.484	3.400	34	35	<del>2-104345-6</del>
	2.984	2.900	29	30	<del>2-104345-5</del>
	2.584	2.500	25	26	<del>2-104345-4</del>
	2.484	2.400	24	25	<del>2-104345-3</del>
	2.384	2.300	23	24	<del>2-104345-2</del>
	2.284	2.200	22	23	<del>2-104345-1</del>
	2.184	2.100	21	22	<del>2-104345-0</del>
	2.084	2.000	20	21	<del>1-104345-9</del>
	1.984	1.900	19	20	<del>1-104345-8</del>
	1.884	1.800	18	19	<del>1-104345-7</del>
	1.784	1.700	17	18	<del>1-104345-6</del>
	1.684	1.600	16	17	<del>1-104345-5</del>
	1.584	1.500	15	16	<del>1-104345-4</del>
	1.484	1.400	14	15	<del>1-104345-3</del>
<div> <div>OBSOLETE</div> <div>6</div> </div>	1.384	1.300	13	14	<del>1-104345-2</del>
	1.284	1.200	12	13	<del>1-104345-1</del>
	1.184	1.100	11	12	<del>1-104345-0</del>
	1.084	1.000	10	11	<del>104345-9</del>
	.984	.900	9	10	<del>104345-8</del>
<div> <div>6</div> <div>OBSOLETE</div> </div>	.884	.800	8	9	<del>104345-7</del>
	.784	.700	7	8	104345-6
	.684	.600	6	7	<del>104345-5</del>
	.584	.500	5	6	104345-4
	.484	.400	4	5	104345-3
	.384	.300	3	4	104345-2
	.284	.200	2	3	104345-1
	C	B	A	NO OF POSN	ASSEMBLY PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN H. MOLL	08FEB88		 TE Connectivity	
		CHK R. FEIDT	08FEB88			
DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD R. FEIDT	08FEB88		NAME  HEADER ASSY, MOD II, BREAKAWAY, SINGLE ROW, .100 CL, VERT, .025 SQ POSTS, WITH RETENTION FEATURE	
	0 PLC ± —	PRODUCT SPEC				
	1 PLC ± —	—				
	2 PLC ± —	APPLICATION SPEC				
	3 PLC ± .005	—		SIZECAGE CODEDRAWING NORESTRICTED TO		
4 PLC ± —	—					
ANGLES ± —		WEIGHT —		A200779C-104345		
MATERIAL: HOUSING: FLAME RETARDANT THERMOPLASTIC COLOR-BLACK POST: COPPER ALLOY	FINISH: POST: .00015 GOLD IN CONTACT AREA, .000100—.000200 MATTE TIN—LEAD OR SOLDER TAIL, ALL OVER .000050 NICKEL	CUSTOMER DRAWING		SCALE 4:1 SHEET 1 of 1 REV K		

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[104345-2](#)