


Model 73058
UHF Jack to Jack Adapter



*Model 73058
UHF Jack to Jack Adapter*

Features

- DC – 300MHz bandwidth.
- Connectors are precision machined.

Materials

Center Conductor: Phosphor Bronze, Gold Plated
Connector Body: Brass, Nickel Plated
Insulators: PTFE

Specifications

Frequency Range:	DC – 300MHz
Contact Resistance:	
Center Conductor:	$\leq 1.0 \text{ m}\Omega$
Outer Conductor:	$\leq 0.2 \text{ m}\Omega$
Insulation Resistance:	$\geq 300 \text{ M}\Omega$
Dielectric Withstand Voltage:	750V
For CE compliance, do not hold in hand when voltages exceed 33 Vrms / 70 Vdc.	
Number of Insertions:	500 cycles minimum

Ordering Information

Model: **73058**

USA: Sales: 800-490-2361
Technical Support: technicalsupport@pomonatest.com
Fax: 425-446-5844
Europe: 31-(0) 40 2675 150 **International:** 425-446-5500
Where to Buy: www.pomonaelectronics.com

All dimensions are in inches. Tolerances (except noted): $xx = \pm .02" (.51 \text{ mm})$, $.xxx = \pm .005" (.127 \text{ mm})$. All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Pomona:](#)

[73058](#)