




## Product information GECKO 4TX

Industrial Ethernet: Lite Managed Switches: GECKO 4TX	
<a href="http://dev-catalog.beldensolutions.com/link/57078-24455-402707-402708/en/conf/uistate">http://dev-catalog.beldensolutions.com/link/57078-24455-402707-402708/en/conf/uistate</a>	
Name	GECKO 4TX
	
	Lite Managed Industrial ETHERNET Rail-Switch, Ethernet/Fast-Ethernet Switch, Store and Forward Switching Mode, fanless design.
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Description	Lite Managed Industrial ETHERNET Rail-Switch, Ethernet/Fast-Ethernet Switch, Store and Forward Switching Mode, fanless design.
Port type and quantity	4 x 10/100BASE-TX, TP-cable, RJ45 sockets, auto-crossing, auto-negotiation, auto-polarity
Type	GECKO 4TX
Order No.	942 104-001
<b>More interfaces</b>	
Power supply/signaling contact	1 plug-in terminal block, 3-pin, no signaling contact
<b>Network size - length of cable</b>	
Twisted pair (TP)	0 m ... 100 m
<b>Network size - cascading</b>	
Line - / star topology	any
<b>Power requirements</b>	
Operating voltage	DC 9.6 V - 32 V
Current consumption at 24 V DC	120 mA
Power consumption	2,9 W
<b>Software</b>	
Management	Web-interface, HTTP(s) config file/firmware transfer, SNMP v1/v2/v3
Diagnostics	Device status indication (LEDs), Log-File, RMON (1) statistics, Simple interface statistics, Topology Discovery according to IEEE 802.1AB (LLDP)
Configuration	BOOTP/DHCP, DHCP Option 82, HiDiscovery
Security	SNMPv3 (authNoPriv), Possibility to disable each port
Redundancy functions	RSTP (IEEE 802.1D-2004)
Filter	TOS/DSCP prioritization (Mapping TOS/DSCP to 802.1D/p), Prioritization through 4 queues, Static unicast/multicast filter entries (up to 100)
<b>Ambient conditions</b>	
Operating temperature	0 °C ... 60 °C
Storage/transport temperature	-40 °C ... 85 °C
Relative humidity (non-condensing)	5 % ... 95 %
MTBF	497,250 h (MIL-HDBK217F)
<b>Mechanical construction</b>	
Dimensions (W x H x D)	25 mm x 114 mm x 79 mm
Mounting	DIN Rail
Weight	100 g
Protection class	IP30
<b>Mechanical stability</b>	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	3.5 mm, 5-8.4 Hz, 10 cycles, 1 octave/min; 1 g, 8.4-150 Hz, 10 cycles, 1 octave/min
<b>EMC interference immunity</b>	
EN 61000-4-2 electrostatic discharge (ESD)	4 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80-3000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 2 kV data line IEC61000-4-5: power line 5 kV (line/earth)
EN 61000-4-6 conducted immunity	10 V (150 kHz-80 MHz)



# HIRSCHMANN

A BELDEN BRAND

## Industrial Ethernet:Lite Managed Switches:GECKO 4TX

<http://dev-catalog.beldensolutions.com/link/57078-24455-402707-402708/en/conf/ui/state>

### EMC emitted immunity

FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
-------------------	----------------------------

EN 55022	EN 55022 Class A
----------	------------------

### Approvals

Safety of industrial control equipment	UL61010-1/-2-201
--	------------------

### Scope of delivery and accessories

Scope of delivery	Device, terminal block, operating manual
-------------------	--

Accessories to order separately	Rail power supply RPS 30, RPS 80 EEC or RPS 120 EEC (CC)
---------------------------------	--

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.