

LOC	DIST	REVISIONS					
FX	00	P	LYR	DESCRIPTION	DATE	DWN	APVD
		-		SEE SHEET 1	-	-	-

ASSEMBLY PART NUMBERS																																			
2098376-1																											1924686-1	1924685-1	1924684-1	1924683-1	1924682-1				
I																											I	I	I	I	I	7	CPA	PBT-GF15	RED
I																											I	I	I	I	I	6	SHORTING BAR	S.S.	SEE COMPONENT DRAWING
I																											I	I	I	I	I	5	PERIMETER SEAL	SILICONE	GREEN
I																											I	I	I	I	I	4	GROMMET	SILICONE	BROWN
I																											I	I	I	I	I	3	COVER	PA66 35% GF	BLACK
I																											I	I	I	I	I	2	TPA WITH 3 SHORTING BAR POSITIONS CONFIGURATION	sPS 30% GF	NATURAL
I																															I	3 SHORTING BAR POSITIONS CONFIGURATION	PA66 30% GF	BLACK	
																											I					I	3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK
																													I			I	3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK
																														I		I	3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK
																												I			I	I	3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK
																														I		I	3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	NATURAL
																														I		I	3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	BLACK
																														I		I	3 SHORTING BAR POSITIONS CONFIGURATION	PA66 35% GF	GRAY
QUANTITY																												ITEM		DESCRIPTION		MATERIAL	FINISH/COLOR		

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

9 PLC ±.3
1 PLC ±0.3
2 PLC ±0.10
3 PLC ±.
4 PLC ±.
ANGLES ±°
FINISH -
-

MATERIAL

SEE CHART ABOVE

DWN R. VESTAL 24JUL2007
CHK W. WELLINSKY 24JUL2007
APVD W. WELLINSKY 24JUL2007

PRODUCT SPEC

APPLICATION SPEC

WEIGHT -

CUSTOMER DRAWING

NAME

24 WAY ARM PLUG ASSEMBLY
WITH SELECT LOAD SHORTING BARS
CUSTOMER SPEC.

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A1

00779

1924674

-

SCALE

3:1

SHEET

2

OF

5

REV

S

TE Connectivity

LOC	DIST	REVISIONS					
FX	00	REV	LYR	DESCRIPTION	DATE	OWN	APVD
		-	-	SEE SHEET 1	-	-	-

PIN-OUT CHART																																
		1 / 2																									N	2098376-1	KEY "F"			
		1 / 2																									N	1924686-1	KEY "E"			
		1 / 2																									N	1924685-1	KEY "D"			
		1 / 2																									N	1924684-1	KEY "C"			
		1 / 2																									N	1924683-1	KEY "B"			
		1 / 2																									N	1924682-1	KEY "A"			
5 / 6	3 / 4	1 / 2	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	CPA	ASSEMBLY PART NUMBER	PLUG KEYING OPTION			
SHORTING BAR POSITION			TERMINAL HOLE POSITION																													
CAVITIES W/ A NUMERIC SYMBOL INDICATE SHORTING BAR LOADED			CAVITIES WITH A NUMERIC SYMBOL INDICATE CLOSED TERMINAL HOLE POSITIONS																													
BLANK CAVITIES INDICATE NO SHORTING BAR LOADED			BLANK CAVITIES INDICATE OPEN TERMINAL HOLE POSITIONS																													

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-1924675-1](#)