

| 1 | Product: <u>83002</u> ☑ |
|---------------------|---|
| | Lead Wire, #26 Str SPC, TFE Ins, AWM 1213 105C TYPE E |
| | Request Sample |
| Product Description | |

High Temp Plastic Lead Wire, 26AWG (7x34) Silver Plated Copper, TFE Insulation, AWM 1213 105C TYPE E MIL-W-16878/4 600V 200C

Technical Specifications

Physical Characteristics (Overall)

| | Conductor | | |
|---|---------------------------|---|--|
| AWG Stranding | Material | No. of Conductors | |
| 26 7x34 | 7x34 SC - Silvered Copper | | |
| Conductor Count: | | 1 | |
| nsulation | | | |
| Material | Nominal | Diameter Nominal | |
| PTFE - Polytetrafluo | roethylene 0.039 in | 0.01 in | |
| Electrical Char | acteristics | | |
| | | | |
| Conductor DCR | | | |
| Nominal Conducto | r DCR | | |
| 37.5 Ohm/1000ft | | | |
| Current | | | |
| Eleme | ent Ma | ax. Recommended C | |
| Mil-Std-975M Table | 3.16 (single wire) 2. | 5 amps | |
| Voltage | | | |
| - | tage Rating [V] | | |
| Mil-W-16878/4 600 | V | | |
| Tamana tama D | | | |
| Temperature R | | | |
| Non-UL Temp Ratin | g: | 200°C | |
| UL Temp Rating: | 200. | 105°C -70°C To +200°C | |
| Operating Temp Pag | | | |
| Operating Temp Rai | ige. | | |
| Operating Temp Ran | | | |
| | | 2 lbs/1000ft | |
| Mechanical Ch | | | |
| Mechanical Ch Bulk Cable Weight: Standards | | 2 lbs/1000ft | |
| Mechanical Ch Bulk Cable Weight: Standards UL AWM Style: | aracteristics | 2 lbs/1000ft 1213 | |
| Mechanical Ch Bulk Cable Weight: Standards UL AWM Style: Military Specification | aracteristics | 2 lbs/1000ft 1213 NEMA HP3, MIL-W | |
| Mechanical Ch Bulk Cable Weight: Standards UL AWM Style: Military Specification | aracteristics | 2 lbs/1000ft 1213 | |
| Mechanical Ch Bulk Cable Weight: Standards UL AWM Style: Military Specification | aracteristics | 2 lbs/1000ft 1213 NEMA HP3, MIL-W | |

| EU Directive 2011/65/EU (ROHS II): | Yes |
|---------------------------------------|-------------------------------|
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-04-01 |
| MII Order #39 (China RoHS): | Yes |

Flammability, LS0H, Toxicity Testing

| UL Flammability: | VW-1 |
|--------------------|-----------|
| UL voltage rating: | 600 V RMS |
| Plenum/Non-Plenum | |

Plenum (Y/N):

Part Number

Variants

| Item # | Color | Putup Type | Length | UPC |
|---------------|-------------|------------|-----------|---------------|
| 83002 010100 | Black | Reel | 100 ft | 612825354864 |
| 83002 0101000 | Black | Reel | 1,000 ft | 612825353850 |
| 83002 006100 | Blue, Light | Reel | 100 ft | 612825353874 |
| 83002 0061000 | Blue, Light | Reel | 1,000 ft | 612825399223 |
| 83002 001100 | Brown | Reel | 100 ft | |
| 83002 0011000 | Brown | Reel | 1,000 ft | 612825353911 |
| 83002 008100 | Gray | Reel | 100 ft | |
| 83002 0081000 | Gray | Reel | 1,000 ft | 612825399230 |
| 83002 005100 | Green, Dark | Reel | 100 ft | |
| 83002 0051000 | Green, Dark | Reel | 1,000 ft | |
| 83002 003100 | Orange | Reel | 100 ft | 612825353898 |
| 83002 0031000 | Orange | Reel | 1,000 ft | |
| 83002 002100 | Red | Reel | 100 ft | 612825354895 |
| 83002 0021000 | Red | Reel | 1,000 ft | 612825353904 |
| 83002 007100 | Violet | Reel | 100 ft | |
| 83002 0071000 | Violet | Reel | 1,000 ft | |
| 83002 009100 | White | Reel | 100 ft | |
| 83002 0091000 | White | Reel | 1,000 ft | 612825353867 |
| 83002 004100 | Yellow | Reel | 100 ft | |
| 83002 0041000 | Yellow | Reel | 1,000 ft | 612825399216 |
| Footnote: | | | E - MAY C | ONTAIN MORE |
| Footnote: | | | | ING ADDERS FO |

No

History

Update and Revision: Revision Number: 0.286 Revision Date: 04-28-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable:

 83002 0061000
 83002 0041000
 83002 0101000
 83002 0011000
 83002 0051000
 83002 002100
 83002 003100

 83002 009100
 83002 001100
 83002 0021000
 83002 006100
 83002 0091000
 83002 008100

 007100
 83002 004100
 83002 005100
 83002 008100
 83002 008100
 83002 008100